



Commercial status

This Product is Obsolete :

 This Product is Obsolete

Overview

Lead time	Usually in Stock
-----------	------------------

General

Provided equipment	CD with software Rack Mounting support rails Smart UPS signalling RS-232 cable User Manual
--------------------	---

Physical

Cable length	8 Ft (2.44 m)
Number of rack unit	2U
Color	Beige
Maximum Depth	17.99 In (45.7 cm)
Maximum Height	3.50 In (8.9 cm)
Net Weight	48.10 Lb(US) (21.82 kg)
Maximum Width	19.02 In (48.3 cm)

Input

Input Frequency	50/60 Hz +/- 3 Hz auto-sensing
Plug standard	NEMA 5-15P
Efficiency at full load	75...154 V adjustable 82...144 V
Nominal Input Voltage	120 V

Output

Rated power in W	450 W
Max Configurable Power (Watts)	450 W
Topology	Line Interactive
Nb of power socket outlets	6 NEMA 5-15R
Output voltage	120 V

Conformance

Product certifications	CSA
Standards	FCC Part 15 class A UL 1449 UL 1778
Equipment protection policy	Lifetime : \$150000

Environmental

Ambient air temperature for operation	32...104 °F (0...40 °C)
Relative humidity	0...95 %
Operating altitude	0...10000 ft
Ambient air temperature for storage	5...113 °F (-15...45 °C)
Storage altitude	0...50000 Ft (0.00...15240.00 m)
Acoustic level	42 dBA
Online Thermal Dissipation	68 Btu/H

Batteries & Runtime

Battery type	Lead-Acid battery
Included Battery Modules	0
Battery Slots Empty	0
Typical recharge time	3 H
RBC Quantity	1
Liquid Electrolyte Value	0

Communications & Management

Free slots	1
Control panel	LED status display with load and battery bar-graphs and On Line : On Battery : Replace Battery : and Overload Indicators
Audible Alarm	Alarm when on battery : distinctive low battery alarm : configurable delays
Emergency Power Off (EPO)	Optional

Surge Protection and Filtering

Surge energy rating	459 J
Filtering	Full time multi-pole noise filtering : 0.3% IEEE surge let-through : zero clamping response time : m

Ordering and shipping details

GTIN	00731304013693
Package weight(Lbs)	55.36 Lb(US) (25.11 kg)

Packing Units

Package 1 Height	9.88 In (25.1 cm)
Package 1 width	23.39 In (59.4 cm)
Package 1 Length	23.74 In (60.3 cm)

Contractual warranty

Warranty	2 years repair or replace, optional on-site warranties available, optional extended warranties available
----------	--

Product Life Status : **Post commercialisation**