Product data sheet Characteristics

8502SCG2V03S

NEMA Contactor, Type S, nonreversing, Size 1, 27A, 10 HP at 575 VAC, 3 phase, up to 100 kA, 3 pole, 240 VAC coil, NEMA 1

Product availability: Non-Stock - Not normally stocked in distribution facility



Price*: 518.00 USD



Main

Product Type	Contactor	o o o de la companya		
Туре	8502S			
Control Circuit Type	Separate control circuit			
Control Circuit Voltage	240 V AC 60 Hz 220 V AC 50 Hz			
Contactor Type	Non-reversing			
Current Rating	27 A			
Number of Poles	3P			
Phase	3 phase			
Horsepower Rating	7.5 HP 200 V AC 7.5 HP 230 V AC 10 HP 460 V AC 10 HP 575 V AC	4 4 50 00 00 00 00 00 00 00 00 00 00 00 00		
Maximum Voltage Rating	600 V AC	<u>.</u> 		
SCCR	Circuit-breaker 70 A maximum, SCCR: 100 kA at 480 V AC Fuse J 60 A maximum, SCCR: 100 kA at 600 V AC Fuse T 60 A maximum, SCCR: 100 kA at 600 V AC Fuse RK1 60 A maximum, SCCR: 100 kA at 600 V AC Fuse RK5 60 A maximum, SCCR: 100 kA at 600 V AC			
Control Units	No control units			
Pilot Light	No indicator	<u>.</u>		
Auxiliary Contacts				
Control Circuit Fusing	Fuse not supplied			
Electrical Connection	Screw clamp terminals			
Enclosure Type	Without Fuse not supplied Screw clamp terminals NEMA 1 painted sheet steel UL listed file E78351 CCN NLDX CSA			
Certifications	UL listed file E78351 CCN NLDX CSA			

^{*} Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

NEMA Size	1	
Height	10.00 in (254 mm)	
Depth	5.28 in (134 mm)	-
Width	5.98 in (152 mm)	

Ordering and shipping details

21192 - 8502,36 SC,SD(NOT S*R,T,W)		
CP1		
1		
5 lb(US) (2.27 kg)		
No		
MX		

Contractual warranty

Warranty	18 months	