SPP4435B
P-Channel Enhancement Mode MOSFET

DESCRIPTION

The SPP4435B is the P-Channel logic enhancement mode power field effect transistors are produced using high cell density , DMOS trench technology.

This high density process is especially tailored to minimize on-state resistance.

These devices are particularly suited for low voltage application , notebook computer power management and other battery powered circuits where high-side switching .


APPLICATIONS


- Power Management in Note book
- Portable Equipment
- Battery Powered System
- DC/DC Converter
- Load Switch
- DSC
- LCD Display inverter

FEATURES


- -30V/-9.2A,$R_{DS(ON)}$= 24mΩ@V_{GS}=- 10V
- -30V/-7.0A,$R_{DS(ON)}$= 30mΩ@V_{GS}=-4.5V
- Super high density cell design for extremely low RDS (ON)
- Exceptional on-resistance and maximum DC current capability
- SOP – 8P package design

PIN CONFIGURATION(SOP – 8P)





PART MARKING



SPP4435B
P-Channel Enhancement Mode MOSFET

PIN DESCRIPTION

Pin	Symbol	Description
1	S	Source
2	S	Source
3	S	Source
4	G	Gate
5	D	Drain
6	D	Drain
7	D	Drain
8	D	Drain

ORDERING INFORMATION

Part Number	Package	Part Marking
SPP4435BS8RGB	SOP- 8P	SPP4435B

※ SPP4435BS8RGB : 13”Tape Reel ; Pb – Free; Halogen – Free

ABSOULTE MAXIMUM RATINGS

(T_A=25℃ Unless otherwise noted)

Parameter		Symbol	Typical	Unit
Drain-Source Voltage		V_{DSS}	-30	V
Gate –Source Voltage		V_{GSS}	±20	V
Continuous Drain Current(T_J=150℃)	T_A=25℃	I_D	-10.0	A
	T_A=70℃		-7.0	
Pulsed Drain Current		I_{DM}	-50	A
Continuous Source Current(Diode Conduction)		I_S	-2.3	A
Power Dissipation	T_A=25℃	P_D	2.8	W
	T_A=70℃		1.8	
Operating Junction Temperature		T_J	-55/150	℃
Storage Temperature Range		T_{STG}	-55/150	℃
Thermal Resistance-Junction to Ambient		$R_{\theta JA}$	70	℃/W

SPP4435B
P-Channel Enhancement Mode MOSFET


ELECTRICAL CHARACTERISTICS

(T_A=25℃ Unless otherwise noted)


Parameter	Symbol	Conditions	Min.	Typ	Max.	Unit
Static						
Drain-Source Breakdown Voltage	$V_{(BR)DSS}$	V_{GS}=0V,I_D=-250uA	-30			V
Gate Threshold Voltage	$V_{GS(th)}$	V_{DS}=V_{GS},I_D=-250uA	-0.7		-1.6	
Gate Leakage Current	I_{GSS}	V_{DS}=0V,V_{GS}=±20V			±100	nA
Zero Gate Voltage Drain Current	I_{DSS}	V_{DS}=-24V,V_{GS}=0V			-1	uA
		V_{DS}=-24V,V_{GS}=0V T_J=85℃			-5	
On-State Drain Current	$I_{D(on)}$	V_{DS}= -5V,V_{GS} =-4.5V	-40			A
Drain-Source On-Resistance	$R_{DS(on)}$	V_{GS}=-10V,I_D=-9.2A		0.020	0.024	Ω
		V_{GS}=-4.5V,I_D=-7.0A		0.025	0.030	
Forward Transconductance	gfs	V_{DS}=-10V,I_D=-9.0A		24		S
Diode Forward Voltage	V_{SD}	I_S=-2.3A,V_{GS} =0V		-0.8	-1.2	V
Dynamic						
Total Gate Charge	Q_g	V_{DS}=-15V,V_{GS}=-10V I_D= -9.0A		20	30	nC
Gate-Source Charge	Q_{gs}			3.5		
Gate-Drain Charge	Q_{gd}			4.8		
Input Capacitance	C_{iss}	V_{DS}=-15V,V_{GS}=0V f=1MHz		1850		pF
Output Capacitance	C_{oss}			450		
Reverse Transfer Capacitance	C_{rss}			335		
Turn-On Time	$t_{d(on)}$	V_{DD}=-15V,R_L=15Ω I_D≡-1.0A,V_{GEN}=-10V R_G=6Ω		20	30	nS
	t_r			20	30	
Turn-Off Time	$t_{d(off)}$			75	110	
	t_f			40	80	

TYPICAL CHARACTERISTICS


Output Characteristics




Transfer Characteristics



On-Resistance vs. Drain Current




Capacitance




TYPICAL CHARACTERISTICS


Gate Charge




On-Resistance vs. Junction Temperature




Source-Drain Diode Forward Voltage





On-Resistance vs. Gate-to-Source Voltage




TYPICAL CHARACTERISTICS










SOP- 8 PACKAGE OUTLINE









SYMBOLS	DIMENSIONS IN MILLIMETERS			DIMENSIONS IN INCHES		
	MIN	NOM	MAX	MIN	NOM	MAX
A	1.47	1.60	1.73	0.058	0.063	0.068
A1	0.10	——	0.25	0.004	——	0.010
A2	——	1.45	——	——	0.057	——
b	0.33	0.41	0.51	0.013	0.016	0.020
C	0.19	0.20	0.25	0.0075	0.008	0.0098
D	4.80	4.85	4.95	0.189	0.191	0.195
E	5.80	6.00	6.20	0.228	0.236	0.244
E1	3.80	3.90	4.00	0.150	0.154	0.157
e	——	1.27	——	——	0.050	——
L	0.38	0.71	1.27	0.015	0.028	0.050
2 y	——	——	0.076	——	——	0.003
θ	0°	——	8°	0°	——	8°

Information provided is alleged to be exact and consistent. SYNC Power Corporation presumes no responsibility for the penalties of use of such information or for any violation of patents or other rights of third parties which may result from its use. No license is granted by allegation or otherwise under any patent or patent rights of SYNC Power Corporation. Conditions mentioned in this publication are subject to change without notice. This publication surpasses and replaces all information previously supplied. SYNC Power Corporation products are not authorized for use as critical components in life support devices or systems without express written approval of SYNC Power Corporation.

©The SYNC Power logo is a registered trademark of SYNC Power Corporation
©2004 SYNC Power Corporation – Printed in Taiwan – All Rights Reserved
SYNC Power Corporation
9F-5, No.3-2, Park Street
NanKang District (NKSP), Taipei, Taiwan 115
Phone: 886-2-2655-8178
Fax: 886-2-2655-8468
©http://www.syncpower.com