

**SPECIFICATION SHEET****JFW MODEL 50D-052****DETECTOR**

JFW Industries, Inc.  
 Phone: 317-887-1340  
 sales@jfwindustries.com  
 www.jfwindustries.com

Frequency Range	1-3000 MHz
Impedance	50 Ohms nominal
VSWR	1.2:1 maximum 1-1000 MHz 1.3:1 maximum 1000-2000 MHz 1.4:1 maximum 2000-3000 MHz
Flatness	± 0.2 dB 1-500 MHz ± 0.3 dB 500-2000 MHz ± 0.5 dB 2000-3000 MHz
Typical Sensitivity	
(-20 dBm)	0.006 V
(-10 dBm)	0.050 V
( 0 dBm)	0.220 V
(+10 dBm)	0.840 V
(+20 dBm)	2.650 V
Output Capacitance	1000 pF nominal
DC Output Polarity	Positive or Negative (customer to specify)
RF Input Power	100 mW
RF Input Connector	TNC, N, BNC or SMA male
DC Output Connector	TNC, SMA, BNC or N female
Operating Temperature Range	-40°C to +85°C
Storage Temperature Range	-55°C to +85°C
Humidity	0 to 95% (Non-Condensing)
Outline Drawing Numbers	092-3134 (Connector Chart) 092-5251 (N M / BNC F) 092-5252 (BNC M / BNC F) 092-5402 (SMA M / BNC F)

ECR/ECN #	DATE	REV	APPR / DATE	ECR/ECN #	DATE	REV	APPR / DATE
14148	05/02/2007	A	CLK 05/02/2007	23449	11/11/2013	D	BAC 11/11/2013
15350	02/11/2008	B	CLK 02/11/2008	26700	06/08/2016	E	CLK 06/08/2016
23218	09/05/2013	C	BAC 09/05/2013	27494	01/23/2017	F	TRS 01/23/2017