PASTERNACK ENTERPRISES®
PO Box 16759. Irvine, CA 92623-6759
Toll Free: (866) 727-8376
Direct: +1 (949) 261-1920
FAX: +1 (949) 261-7451
Email: sales@pasternack.com

PE51081 Rubber Duck Antenna 2400- 2500 & 4900-5825 MHz,2dBi & 3dBi

PE51081

Product Features

- Mini Rubber Duck Antenna- with off-white/grey Radome
- 2400-2500 & 4900-5825 MHz Freq Range
- 2dBi and 3dBi Omni Radiation Pattern



Description

The PE51081 swivel style Mini Rubber Duck Dual Band Antenna provides excellent performance in multiple wireless applications. Its small size and rugged construction is perfect for both indoor and portable wireless systems.

Specifications (1)

Parameter	Value	Units	Description
Band 1 Frequency	2400-2500	MHz	
Band 2 Frequency	4900-5825	MHz	
Impedance	50	Ohms	
Gain(B1/B2)	2/3	dBi	2dBi-BW1, 3dBi-BW2
Polarization	O	Omni	
RF Power Rating	30	W	Max
Maximum VSWR	<2.0	ratio	Between Min and Max Freq
Length	130	mm	5.1 inches
Connector Type		RP-SMA(M)	Swivel Style SMA

Ordering Information

Part Number	Description
PE51081	2400-2500 and 4900-5825MHz 2/3dBi Dual Band Rubber Duck-Grey Radome, Reverse Polarity –SMA Male

(1) Pasternack reserves the right to change specifications or information without notice.
(2) All Specifications "Typical" values