
SPN1423A
N-Channel Enhancement Mode MOSFET


DESCRIPTION
The SPN1423A is the N-Channel logic enhancement mode power field effect transistors are produced using high cell density , DMOS trench technology.
This high density process is especially tailored to minimize on-state resistance.
These devices are particularly suited for low voltage application such as cellular phone and notebook computer power management and other battery powered circuits where high-side switching , and low in-line power loss are needed in a very small outline surface mount package.

APPLICATIONS
- Power Management in Note book
- Portable Equipment
- Battery Powered System
- DC/DC Converter
- Load Switch
- DSC
- LCD Display inverter

FEATURES
- 20V/4.0A,$R_{DS(ON)}$=80mΩ@V_{GS}=4.5V
- 20V/3.4A,$R_{DS(ON)}$=90mΩ@V_{GS}=2.5V
- 20V/2.8A,$R_{DS(ON)}$=110mΩ@V_{GS}=1.8V
- 20V/1.0A,$R_{DS(ON)}$=140mΩ@V_{GS}=1.25V
- Super high density cell design for extremely low RDS (ON)
- Exceptional on-resistance and maximum DC current capability
- SOT-353 (SC – 70) package design

PIN CONFIGURATION (SOT-353 ; SC-70)





PART MARKING



Y : Year Code
W : Week Code

SPN1423A
N-Channel Enhancement Mode MOSFET

PIN DESCRIPTION

Pin	Symbol	Description
2	G	Gate
3	S	Source
1 , 4 , 5	D	Drain

ORDERING INFORMATION

Part Number	Package	Part Marking
SPN1423AS35RG	SOT-353	2AYW

※ Week Code : A ~ Z(1 ~ 26) ; a ~ z(27 ~ 52)
※ SPN1423AS35RG : Tape Reel ; Pb – Free

ABSOULTE MAXIMUM RATINGS

(T_A=25℃ Unless otherwise noted)

Parameter		Symbol	Typical	Unit
Drain-Source Voltage		V_{DSS}	20	V
Gate –Source Voltage		V_{GSS}	±12	V
Continuous Drain Current(T_J=150℃)	T_A=25℃	I_D	2.4	A
	T_A=70℃		1.7	
Pulsed Drain Current		I_{DM}	6	A
Continuous Source Current(Diode Conduction)		I_S	1.6	A
Power Dissipation	T_A=25℃	P_D	0.95	W
	T_A=70℃		0..51	
Operating Junction Temperature		T_J	-55/150	℃
Storage Temperature Range		T_{STG}	-55/150	℃
Thermal Resistance-Junction to Ambient		$R_{\theta JA}$	105	℃/W


SPN1423A
N-Channel Enhancement Mode MOSFET


ELECTRICAL CHARACTERISTICS


(T_A=25℃ Unless otherwise noted)


Parameter	Symbol	Conditions	Min.	Typ	Max.	Unit
Static						
Drain-Source Breakdown Voltage	$V_{(BR)DSS}$	V_{GS}=0V,I_D=250uA	20			V
Gate Threshold Voltage	$V_{GS(th)}$	V_{DS}=V_{GS},I_D=250uA	0.4		1.0	
Gate Leakage Current	I_{GSS}	V_{DS}=0V,V_{GS}=±12V			±100	nA
Zero Gate Voltage Drain Current	I_{DSS}	V_{DS}=20V,V_{GS}=0V			1	uA
		V_{DS}=20V,V_{GS}=0V T_J=55℃			5	
On-State Drain Current	$I_{D(on)}$	V_{DS}≦5V,V_{GS}=4.5V	6			A
Drain-Source On-Resistance	$R_{DS(on)}$	V_{GS}=4.5V,I_D=4.0A		0.065	0.080	Ω
		V_{GS}=2.5V,I_D=3.4A		0.075	0.090	
		V_{GS}=1.8V,I_D=2.8A		0.090	0.110	
		V_{GS}=1.25V,I_D=1.0A		0.120	0.140	
Forward Transconductance	gfs	V_{DS}=5V,I_D=-3.6A		10		S
Diode Forward Voltage	V_{SD}	I_S=1.6A,V_{GS}=0V		0.8	1.2	V
Dynamic						
Total Gate Charge	Q_g	V_{DS}=6V,V_{GS}=4.5V I_D≡2.8A		4.8	8	nC
Gate-Source Charge	Q_{gs}			1.0		
Gate-Drain Charge	Q_{gd}			1.0		
Input Capacitance	C_{iss}	V_{DS}=6V,V_{GS}=0V f=1MHz		485		pF
Output Capacitance	C_{oss}			85		
Reverse Transfer Capacitance	C_{rss}			40		
Turn-On Time	$t_{d(on)}$	V_{DD}=6V,R_L=6Ω I_D≡1.0A,V_{GEN}=4.5V R_G=6Ω		8	14	ns
	t_r			12	18	
Turn-Off Time	$t_{d(off)}$			30	35	
	t_f			12	16	

TYPICAL CHARACTERISTICS













TYPICAL CHARACTERISTICS













TYPICAL CHARACTERISTICS







SOT-353 PACKAGE OUTLINE



Symbol	Dimensions In Millimeters		Dimensions In Inches	
	Min	Max	Min	Max
A	0.900	1.100	0.035	0.043
A1	0.000	0.100	0.000	0.004
A2	0.900	1.000	0.035	0.039
b	0.150	0.350	0.006	0.014
c	0.080	0.150	0.003	0.006
D	2.000	2.200	0.079	0.087
E	1.150	1.350	0.045	0.053
E1	2.150	2.450	0.085	0.096
e	0.650 TYP		0.026 TYP	
e1	1.200	1.400	0.047	0.055
L	0.525 REF		0.021 REF	
L1	0.260	0.460	0.010	0.018
θ	0°	8°	0°	8°

Information provided is alleged to be exact and consistent. SYNC Power Corporation presumes no responsibility for the penalties of use of such information or for any violation of patents or other rights of third parties which may result from its use. No license is granted by allegation or otherwise under any patent or patent rights of SYNC Power Corporation. Conditions mentioned in this publication are subject to change without notice. This publication surpasses and replaces all information previously supplied. SYNC Power Corporation products are not authorized for use as critical components in life support devices or systems without express written approval of SYNC Power Corporation.

©The SYNC Power logo is a registered trademark of SYNC Power Corporation
©2004 SYNC Power Corporation – Printed in Taiwan – All Rights Reserved
SYNC Power Corporation
9F-5, No.3-2, Park Street
NanKang District (NKSP), Taipei, Taiwan 115
Phone: 886-2-2655-8178
Fax: 886-2-2655-8468
©http://www.syncpower.com