

MOC8101X, MOC8102X, MOC8103X, MOC8104X, MOC8105X
MOC8101, MOC8102, MOC8103, MOC8104, MOC8105



**NON-BASE LEAD
OPTICALLY COUPLED ISOLATOR
PHOTOTRANSISTOR OUTPUT**

APPROVALS

- UL recognised, File No. E91231
- 'X' SPECIFICATION APPROVALS
 - VDE 0884 in 3 available lead form :-
 - STD
 - G form
 - SMD approved to CECC 00802
 - Certified to EN60950 by the following Test Bodies :-
 - Nemko - Certificate No. P01102464
 - Fimko - Certificate No. FI18166
 - Semko - Reference No. 0202037/01-22
 - Demko - Certificate No. 311158-01
 - BSI approved - Certificate No. 8001

DESCRIPTION



The MOC8101, MOC8102, MOC8103, MOC8104, MOC8105 series of optically coupled isolators consist of infrared light emitting diode and NPN silicon photo transistor in a standard 6 pin dual in line plastic package with the base pin unconnected.

FEATURES

- Options :-
 - 10mm lead spread - add G after part no.
 - Surface mount - add SM after part no.
 - Tape&reel - add SMT&R after part no.
- High Isolation Voltage (5.3kV_{RMS}, 7.5kV_{PK})
- Base pin unconnected for improved noise immunity in high EMI environment

APPLICATIONS

- DC motor controllers
- Industrial systems controllers
- Signal transmission between systems of different potentials and impedances



**ABSOLUTE MAXIMUM RATINGS
(25°C unless otherwise specified)**

| | |
|---|------------------|
| Storage Temperature | -55°C to + 150°C |
| Operating Temperature | -55°C to + 100°C |
| Lead Soldering Temperature (1/16 inch (1.6mm) from case for 10 secs) | 260°C |

INPUT DIODE

| | |
|-------------------|-------|
| Forward Current | 60mA |
| Reverse Voltage | 6V |
| Power Dissipation | 105mW |


OUTPUT TRANSISTOR

| | |
|--------------------------------------|-------|
| Collector-emitter Voltage BV_{CEO} | 30V |
| Emitter-collector Voltage BV_{ECO} | 6V |
| Power Dissipation | 160mW |

POWER DISSIPATION

| | |
|--|-------|
| Total Power Dissipation | 200mW |
| (derate linearly 2.67mW/°C above 25°C) | |

ISOCOM COMPONENTS LTD
Unit 25B, Park View Road West,
Park View Industrial Estate, Brenda Road
Hartlepool, Cleveland, TS25 1YD
Tel: (01429) 863609 Fax :(01429) 863581




ELECTRICAL CHARACTERISTICS ($T_A = 25^\circ\text{C}$ Unless otherwise noted)


| PARAMETER | | MIN | TYP | MAX | UNITS | TEST CONDITION |
|--------------------------|--|--------------------|------|---------------|---|--|
| Input | Forward Voltage (V_F) | 1.0 | 1.15 | 1.5 | V | $I_F = 10\text{mA}$ |
| | Reverse Current (I_R) | | | 10 | μA | $V_R = 6\text{V}$ |
| Output | Collector-emitter Breakdown (BV_{CEO}) (Note 2) | 30 | | | V | $I_C = 1\text{mA}$ |
| | Emitter-collector Breakdown (BV_{ECO}) | 6 | | | V | $I_E = 100\mu\text{A}$ |
| | Collector-emitter Dark Current (I_{CEO}) | | | 50 | nA | $V_{CE} = 10\text{V}$ |
| Coupled | Output Collector Current (I_C) (Note 3) | | | | | |
| | MOC8101 | 5.0 | | 8.0 | mA | $10\text{mA } I_F, 10\text{V } V_{CE}$ |
| | MOC8102 | 7.3 | | 11.7 | mA | $10\text{mA } I_F, 10\text{V } V_{CE}$ |
| | MOC8103 | 10.8 | | 17.3 | mA | $10\text{mA } I_F, 10\text{V } V_{CE}$ |
| | MOC8104 | 16 | | 25.6 | mA | $10\text{mA } I_F, 10\text{V } V_{CE}$ |
| | MOC8105 | 6.5 | | 13.3 | mA | $10\text{mA } I_F, 10\text{V } V_{CE}$ |
| | Collector-emitter Saturation Voltage $V_{CE(SAT)}$ | | 0.15 | 0.4 | V | $5\text{mA } I_F, 0.5\text{mA } I_C$ |
| | Input to Output Isolation Voltage V_{ISO} | 5300 7500 | | | V_{RMS} V_{PK} | See note 1 See note 1 |
| | Input-output Isolation Resistance R_{ISO} | 5×10^{10} | | | Ω | $V_{IO} = 500\text{V}$ (note 1) |
| Response Time (Rise), tr | | 2 | | μs | $V_{CC} = 5\text{V}, I_F = 10\text{mA}$ | |
| Response Time (Fall), tf | | 2 | | μs | $R_L = 75\Omega$, (FIG 1) | |

- Note 1 Measured with input leads shorted together and output leads shorted together.
- Note 2 Special Selections are available on request. Please consult the factory.
- Note 3 Production testing - limits verified with pulse test


FIGURE 1




Collector Power Dissipation vs. Ambient Temperature




Collector Current vs. Collector-emitter Voltage




Forward Current vs. Ambient Temperature



Current Transfer Ratio vs. Forward Current



Relative Current Transfer Ratio vs. Ambient Temperature



Collector-emitter Saturation Voltage vs. Ambient Temperature

