ADELS contact

Screw Connectors

1500/ 5 DS HT

Terminal Block, 5 pole, Insulating Material: PA 6.6-HT, Cross-Section: 10.0 mm², Pin Spacing: 13.5 mm, Wire Protector (DS): yes, Fixing: Screw, Voltage Rating: 500 V, Current Rating: 57 A

Order Info

Reference Number (ref. no.)	127125
Applications	Installation, Electrical Appliances, Transformers
PU	60

Type

Type	Terminal Block
Number of poles	5 pole
Clamping Units per Pole	1
Colour	brown
Cross-Section	10.0 mm²
Connection Type	Screw
Wire Protector (DS)	yes

Technical Data

Voltage Rating	500 V
Current Rating	57 A
Insulating Material	PA 6.6-HT
Contact Material	Brass
Core Cross-Section min.	0.5 mm²
Core Cross-Section max.	6.0 mm²
Flammability Rating	V-2
max. Ambient Temperature Operation	130 °C
Type of Conductor Solid	yes
Type of Conductor Flexible	yes
Type of Conductor Stranded	yes
Stripping Length	8.0-8.5 mm
Assembly Contact Screw	0.8x4.0 / ↻ 1.2 Nm
Pin Spacing	13.5 mm
Fixing	Screw
Approbation EN60998	1500_EN60998_20070823_20160412_VDE_ENEC_40021887_web.p
Approbation UL	1500_2000_19890315_20170213_UL_E63492_1-08_Description_we
Approbation CSA	Schraub_Steck_Schraubenlos_SI_Klemmen_20160429_CSA_700765

Accessories

ZEL 110	196420