SHEET 1 OF 1



RECOMMENDED P.C.B. LAYOUT



CIRCUIT: SPST







ISOMETRIC



NOTES:
1. ALL DIMENSIONS IN MM [INCH]
2. GENERAL TOLERANCE: X.X=±0.4
   X.XX=±0.25
3. TERM. NOS. FOR REFERENCE ONLY.
4. RATING: 50mA @ 12VDC
▲5. OPERATING FORCE: 180 ±50gf
6. TRAVEL: 0.25mm +0.2/-0.1
7. CONTACT RESISTANCE: 100 MILLI OHMS MAX. (INITIAL)
8. MECHANICAL/ELECTRICAL LIFE: 40,000 CYCLES.
▲9. CONTACT MATERIAL: SILVER
▲10. PACKAGE: TAPE AND REEL, 1800 PER
11. ▲ DENOTES CRITICAL PARAMETER
12. 2002/95/EC (ROHS) COMPLIANT



REV	PCR NO	DESCRIPTION	DATE	BY
C	16721	FIXED SWITCH COLORS	11/30/06	TN
B	16704	REVISED AND REDRAWN	11/27/06	TN

THE INFORMATION CONTAINED IN THIS DOCUMENT IS PROPRIETARY TO E-SWITCH AND IS NOT TO BE COPIED OR TRANSFERRED

E-SWITCH®

TITLE TL3302AF180QJ

SCALE	DATE	DR	DWG	REV
4:1	11/30/2006	TN	P020329	C