



CONTACT CONFIGURATION

CIRCUIT: SPD T

NOTES:

1. ALL DIMENSIONS IN MM [INCH]
2. GENERAL TOLERANCE: X.X=±0.4
X.XX=±0.25
3. TERM. NOS. FOR REF. ONLY
4. RATING: 0.4(VA) max. @20V max. (AC or DC)
5. FIXED TERM. & MOVING CONTACT: Copper alloy w/Gold plate over Nickel plate
6. ELECTRICAL LIFE: 50,000 make-and-break cycles at full load.
7. INSULATION RESISTANCE: 1000M ohm min.
8. DIELECTRIC STRENGTH: 1000V RMS min. @sea level.
9. OPERATING TEMP.: -30°C to 85°C

SWITCH FUNCTION		
PDS. 1	PDS. 2	PDS. 3
		
DN	NONE	<DN>
2-3	DPEN	2-1

③ ()=MOMENTARY

B. DIELECTRIC STRENGTH: 1000V RMS min. @sea level. 9. OPERATING TEMP.: -30°C to 85°C			
B	11469	REVISED PART DESCRIPTION	5/16/01 CJB
REV.	ECN No.	DESCRIPTION	DATE CHKD
THE INFORMATION CONTAINED IN THIS DOCUMENT IS PROPRIETARY TO E-SWITCH AND IS NOT TO BE COPIED OR TRANSFERRED			
TITLE			
200A W/MSP-2 T2 A1 M6 R E			
SCALE	DATE	DR	DWG
2:1	4/12/01	CJB	T201210
			REV
			B