








R-4




Rating: 16A 125V AC (UL CUL)
 16A 250V AC (UL CUL VDE ENEC CB CQC)
 Contact Resistance: 50m Ω (Max)
 Insulation Resistance: DC 500V 100M Ω (Min)
 Dielectric Strength: AC1500V 1 minute
 Electrical life: 10,000 cycles
 Operating Temperature: 0℃~85℃
 Safety Approval:

CUT-OUT



	X	Y
	28.0+0.10	22.0+0.10
0.75~1.25	28.2+0.10	22.0+0.10
1.25~2.00	28.4+0.10	22.0+0.10
2.00~3.00		



MATERIAL:

Body:Nylon66, UL rated:94V-0

Actuator:Nylon66, UL rated:94V-0

Terminal:Brass with silver-plate

Marking		角度 ANGLE ± 1°		单位 DIMENSION UNIT	
X	柄	0	1	2	3
0	None				
1					
2					
3					
4					
5					
6					
7					
8					
9					

公差 TOLERANCES

.X± 0.3 .XX± 0.15

比例尺 SCALE

日期 DATE 2014.07.04

版本 VERSION

A1

核对 CHECKED BY

NONE

日期 DATE 2014.07.04

品名 TITLE R-4-210-C5N-BB

核准 APPROVED BY

A1

核对 CHECKED BY

NONE

日期 DATE 2014.07.04

品名 TITLE R-4-210-C5N-BB

重新整理发行

2014.07.04

N/A

变更日期 CHANGE DESCRIPTION

变更日期 CHANGE DESCRIPTION

变更日期 CHANGE DESCRIPTION

变更日期 CHANGE DESCRIPTION

变更日期 CHANGE DESCRIPTION

变更日期 CHANGE DESCRIPTION

变更日期 CHANGE DESCRIPTION

A1

变更日期 CHANGE DESCRIPTION

变更日期 CHANGE DESCRIPTION

变更日期 CHANGE DESCRIPTION

变更日期 CHANGE DESCRIPTION

变更日期 CHANGE DESCRIPTION

变更日期 CHANGE DESCRIPTION

变更日期 CHANGE DESCRIPTION

变更日期 CHANGE DESCRIPTION

变更日期 CHANGE DESCRIPTION

变更日期 CHANGE DESCRIPTION