

PFE500SA-48/T



Sales Region	Worldwide
Series	PFE-SA
Status	Production
Feature	
Option	Mounting stand (Non-threaded through hole)
Option Lineup	Please refer to here.
Recommended EMC Filter	
Accessories	Please refer to the catalog



Electrical Characteristics

Input Voltage Range[AC]	85 to 265V
Input Voltage Range[DC]	
Efficiency	91% Typ.
Rated Output Voltage[DC]	48V
Output Voltage Range[DC]	38.4 to 57.6V
Maximum Output Current	10.5A
Maximum Output Power	504W

Cases Shape & Size

Case shape	On board/Power module
Width(W)	61mm Nom.
Height(H)	12.7mm Nom.
Depth(D)	116.8mm Nom.
Weight	200g Typ.

Other

Operating Temp. Range	-40 to 100°C
Cooling	Conduction cooling
Safety Standard(Certified)	UL60950-1 CSA C22.2 No.60950-1 EN60950-1

Safety Standard(Conformed)

Remarks	This page only shows representative characteristics. Please refer to the technical data for detailed specifications and conditions.
---------	---

! Images are for reference only and show exemplary products.
! This PDF document was created based on the data listed on the TDK Corporation website.
! All specifications are subject to change without notice.