SamHop Microelectronics Corp.

STM4433A


Jan.25 2005


P-Channel Enhancement Mode Field Effect Transistor

PRODUCT SUMMARY		
V_{DSS}	I_D	$R_{DS(ON)}$ (mΩ) Max
-30V	-6A	35 @ V_{GS} = -10V
		55 @ V_{GS} = -4.5V

FEATURES

- Super high dense cell design for low $R_{DS(ON)}$.
- Rugged and reliable.
- Surface Mount Package.





ABSOLUTE MAXIMUM RATINGS (T_A=25°C unless otherwise noted)

Parameter	Symbol	Limit	Unit
Drain-Source Voltage	V_{DS}	-30	V
Gate-Source Voltage	V_{GS}	±20	V
Drain Current-Continuous [a] @ T_J=25°C	I_D	-6	A
-Pulsed [b]	I_{DM}	-30	A
Drain-Source Diode Forward Current [a]	I_S	-1.7	A
Maximum Power Dissipation [a]	P_D	2.5	W
Operating Junction and Storage Temperature Range	T_J, T_{STG}	-55 to 150	°C

THERMAL CHARACTERISTICS

Thermal Resistance, Junction-to-Ambient [a]	$R_{\theta JA}$	50	°C/W

STM4433A

ELECTRICAL CHARACTERISTICS (T_A =25°C unless otherwise noted)

Parameter	Symbol	Condition	Min	Typ [c]	Max	Unit
OFF CHARACTERISTICS						
Drain-Source Breakdown Voltage	BV_{DSS}	V_{GS}=0V, I_D=-250uA	-30			V
Zero Gate Voltage Drain Current	I_{DSS}	V_{DS}=-24V, V_{GS}=0V			-1	uA
Gate-Body Leakage	I_{GSS}	V_{GS}=±20V, V_{DS}=0V			±100	nA
ON CHARACTERISTICS [b]						
Gate Threshold Voltage	$V_{GS(th)}$	V_{DS}=V_{GS}, I_D=-250uA	-1	-1.9	-3.0	V
Drain-Source On-State Resistance	$R_{DS(ON)}$	V_{GS}=-10V, I_D=-5.8A		21	35	m-ohm
		V_{GS}=-4.5V, I_D=-2.0A		40	55	m-ohm
On-State Drain Current	$I_{D(ON)}$	V_{DS}=-5V, V_{GS}=-10V	-20			A
Forward Transconductance	g_{FS}	V_{DS}=-15V, I_D=-5.8A		8.5		S
DYNAMIC CHARACTERISTICS [c]						
Input Capacitance	C_{ISS}	V_{DS}=-15V, V_{GS}=0V f=1.0MHz		920		pF
Output Capacitance	C_{OSS}			270		pF
Reverse Transfer Capacitance	C_{RSS}			170		pF
SWITCHING CHARACTERISTICS [c]						
Turn-On Delay Time	$t_{D(ON)}$	V_D=-15V, I_D=-1A, V_{GEN}=-10V, R_{GEN}=6-ohm		8.6		ns
Rise Time	t_r			35.3		ns
Turn-Off Delay Time	$t_{D(OFF)}$			36.9		ns
Fall Time	t_f			36.3		ns
Total Gate Charge	Q_g	V_{DS}=-15V, I_D=-5.8A, V_{GS}=-10V		17.5		nC
		V_{DS}=-15V, I_D=-5.8A, V_{GS}=-4.5V		9.4		nC
Gate-Source Charge	Q_{gs}	V_{DS}=-15V, I_D=-5.8A, V_{GS}=-10V		2.9		nC
Gate-Drain Charge	Q_{gd}			4.8		nC

STM4433A

ELECTRICAL CHARACTERISTICS (T_A=25°C unless otherwise noted)

Parameter	Symbol	Condition	Min	Typ [c]	Max	Unit
DRAIN-SOURCE DIODE CHARACTERISTICS [b]						
Diode Forward Voltage	V_{SD}	V_{GS} = 0V, Is =-1.7A		-0.77	-1.2	V

Notes

a.Surface Mounted on FR4 Board, t <=10sec.

b.Pulse Test:Pulse Width<=300us, Duty Cycle<= 2%.

c.Guaranteed by design, not subject to production testing.




Figure 1. Output Characteristics




Figure 2. Transfer Characteristics




Figure 3. Capacitance




Figure 4. On-Resistance Variation with Temperature

STM4433A




Figure 5. Gate Threshold Variation with Temperature




Figure 6. Breakdown Voltage Variation with Temperature




Figure 7. Transconductance Variation with Drain Current




Figure 8. Body Diode Forward Voltage Variation with Source Current




Figure 9. Gate Charge




Figure 10. Maximum Safe Operating Area




Figure 11. Switching Test Circuit




Figure 12. Switching Waveforms





Figure 13. Normalized Thermal Transient Impedance Curve

STM4433A

PACKAGE OUTLINE DIMENSIONS


SO-8



SYMBOLS	MILLIMETERS		INCHES	
	MIN	MAX	MIN	MAX
A	1.35	1.75	0.053	0.069
A1	0.10	0.25	0.004	0.010
D	4.80	4.98	0.189	0.196
E	3.81	3.99	0.150	0.157
H	5.79	6.20	0.228	0.244
L	0.41	1.27	0.016	0.050
θ	0°	8°	0°	8°

SO-8 Tape and Reel Data


SO-8 Carrier Tape



unit:mm

PACKAGE	A0	B0	K0	D0	D1	E	E1	E2	P0	P1	P2	T
SOP 8N 150mil	6.40	5.20	2.10	ϕ1.5 (MIN)	ϕ1.5 + 0.1 - 0.0	12.0 ±0.3	1.75	5.5 ±0.05	8.0	4.0	2.0 ±0.05	0.3 ±0.05

SO-8 Reel



UNIT:mm

TAPE SIZE	REEL SIZE	M	N	W	W1	H	K	S	G	R	V
12 mm	ϕ330	330 ± 1	62 ±1.5	12.4 + 0.2	16.8 - 0.4	ϕ12.75 + 0.15	---	2.0 ±0.15	---	---	---