RECTRON SEMICONDUCTOR
TECHNICAL SPECIFICATION

IMBR1045C THRU IMBR10200C


SCHOTTKY BARRIER RECTIFIER
VOLTAGE RANGE 45 to 200 Volts CURRENT 10.0 Ampere

FEATURES
* Low switching noise
* Low forward voltage drop
* Low thermal resistance
* High current capability
* High switching capability
* High surge capabitity
* High reliability

MECHANICAL DATA
* Case: ITo-220 molded plastic
* Epoxy: Device has UL flammability classification 94V-O
* Lead: MIL-STD-202E method 208C guaranteed
* Mounting position: Any



ITO-220



Dimensions in inches and (millimeters).

MAXIMUM RATINGS AND ELECTRICAL CHARACTERISTICS
Ratings at 25 °C ambient temperature unless otherwise specified.
Single phase, half wave, 60 Hz, resistive or inductive load.
For capacitive load, derate current by 20%.

MAXIMUM RATINGS (@ TA=25 °C unless otherwise noted)

RATINGS	SYMBOL	IMBR1045C	IMBR1060C	IMBR10100C	IMBR10150C	IMBR10200C	UNITS
Maximum Recurrent Peak Reverse Voltage	V_{RRM}	45	60	100	150	200	Volts
Maximum RMS Voltage	V_{RMS}	32	42	70	105	140	Volts
Maximum DC Blocking Voltage	V_{DC}	45	60	100	150	200	Volts
Maximum Average Forward Rectified Current at Derating Case Temperature	I_O	10					Amps
Peak Forward Surge Current 8.3 ms single half sine-wave superimposed on rated load (JEDEC method)	I_{FSM}	100					Amps
Typical Current Squared Time	I^2t	41					A^2S
Typical Thermal Resistance (Note 1)	$R_{\theta JC}$	2.0					°C/W
	$R_{\theta JA}$	40					
Operating Temperature Range	T_J	-55 to + 150					°C
Storage Temperature Range	T_{STG}	-55 to + 150					°C

ELECTRICAL CHARACTERISTICS(@TA=25 °C unless otherwise noted)

CHARACTERISTICS		SYMBOL	IMBR1045C	IMBR1060C	IMBR10100C	IMBR10150C	IMBR10200C	UNITS
Maximum Instantaneous Forward Voltage at 5.0A DC		V_F	.65	.75	.85	.90	.95	Volts
Maximum Average Reverse Current	@T_A = 25°C	I_R	0.2		0.1			mA
at Rated DC Blocking Voltage	@T_A = 150°C		80					mA

NOTES : 1. Thermal Resistance : Heat-sink mounted.
2. Suffix "A" = Common Anode.
3. Measured at 1 MHz and applied reverse voltage of 4.0 volts.
4. "ROHS compliant".

2019-11/47
REV : O

RATING AND CHARACTERISTICS CURVES (IMBR1045C THRU IMBR10200C)




FIG.1 TYPICAL FORWARD CURRENT DERATING CURVE




FIG.2 MAXIMUM REVERSE CHARACTERISTICS




FIG.3 MAXIMUM INSTANTANEOUS FORWARD CHARACTERISTICS





FIG.4 MAXIMUM NON-REPETITIVE FORWARD SURGE CURRENT

RECTRON

1. Internal Circuit



2. Marking on the body



3. Items marked on the inner box and carton

3.1 On the box (for –C)

CUSTOMER
TYPE
LOT NO.
QUANTITY
Q.A.
DATE

3.2 On the carton

CUSTOMER
TYPE
QUANTITY
LOT NO.
REMARK

PACKAGING OF DIODE AND BRIDGE RECTIFIERS

TUBE PACK

PACKAGE	PACKING CODE	EA PER BOX	INNER BOX SIZE (mm)	CARTON SIZE (mm)	EA PER CARTON	WEIGHT(Kg)
(I)TO-220/TO-220(A)	-C	2,000	550*140*92	572*308*120	4,000	11.80

DISCLAIMER NOTICE

Rectron Inc reserves the right to make changes without notice to any product specification herein, to make corrections, modifications, enhancements or other changes. Rectron Inc or anyone on its behalf assumes no responsibility or liability for any errors or inaccuracies. Data sheet specifications and its information contained are intended to provide a product description only. "Typical" parameters which may be included on RECTRON data sheets and/ or specifications can and do vary in different applications and actual performance may vary over time. Rectron Inc does not assume any liability arising out of the application or use of any product or circuit.

Rectron products are not designed, intended or authorized for use in medical, life-saving implant or other applications intended for life-sustaining or other related applications where a failure or malfunction of component or circuitry may directly or indirectly cause injury or threaten a life without expressed written approval of Rectron Inc. Customers using or selling Rectron components for use in such applications do so at their own risk and shall agree to fully indemnify Rectron Inc and its subsidiaries harmless against all claims, damages and expenditures.