Product data sheet Characteristics

2510KG1B

Switch, manual, 30A, 2 pole, 3 HP at 575 VAC, single phase, toggle operated, red 230 VAC indicator, NEMA 1 enclosure

Product availability: Stock - Normally stocked in distribution facility

SQUARE D

Price*: 145.04 USD



Main

Product	Single Unit Manual Switch	- 5
Туре	К	

Complementary

Current Rating	30 A	
Cable Entry	0.5" and 0.75" knock-outs (top and bottom)	
Horsepower Rating	2 hp 115 V AC	
	2 hp 230 V AC	
	3 hp 460 V AC	Š
	3 hp 575 V AC	
	1 hp 90 V DC	9
	2 hp 115 V DC	
	1.5 hp 230 V DC	*
Maximum Voltage Rating	600 V AC	
	230 V DC	
Number of Poles	2P	
Control Unit Type	Toggle	1
Number of Phases	1 phase	
Pilot Light	Red indicator, 230 V	
Starter Type	Non reversing	7
Electrical Connection	Screw clamp terminals	
Wire Gauge	AWG 14AWG 10 copper	
Height	AWG 14AWG 10 copper 4.25 in (107.95 mm)	
Width	2.44 in (61.98 mm)	
Depth	2.75 in (69.85 mm)	
		·

^{*} Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Environment

Certifications	UL listed file E42243 CCN NLRV CSA LR25490 class 3211 05
NEMA Enclosure Rating	NEMA 1 Plastic standard size

Ordering and shipping details

Category	21102 - 2510,2511,2512 K
Discount Schedule	CP1
GTIN	00785901554493
Nbr. of units in pkg.	1
Package weight(Lbs)	0.84 lb(US) (0.38 kg)
Returnability	Yes
Country of origin	MX

Packing Units

Package 1 Height	2.60 in (6.604 cm)
Package 1 width	3.10 in (7.874 cm)
Package 1 Length	4.80 in (12.192 cm)

Offer Sustainability

California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, whi is known to the State of California to cause cancer and birth defects or other reproductive harm. more information go to www.P65Warnings.ca.gov	
REACh Regulation	REACh Declaration	
REACh free of SVHC	Yes	
EU RoHS Directive	Not compliant	
China RoHS Regulation	China RoHS declaration Product out of China RoHS scope. Substance declaration for your information.	
PVC free	Yes	

Contractual warranty

Warranty	18 months	

Approximate Dimensions



