"High Frequency Ceramic Solutions"

900 MHz Balun **P/N 0900BL18B100**

Detail Specification: 08/27/04


General Specifications

Part Number	0900BL18B100
Frequency (MHz)	800 - 1000
Unbalanced Impedence	50 Ω
Differential Balanced Imp.	100 Ω
Insertion Loss	1.0 dB max.
Return Loss	9.5 dB min.
Phase Difference (degree)	180 ± 10
Amplitude Difference	2.0 dB max.

Operating Temperature	-40 to +85°C
Reel Quanity	3,000
Power Capacity	3 Watts max.


Mechanical Dimensions

	In	mm
L	0.126 ± 0.006	3.20 ± 0.15
W	0.063 ± 0.006	1.60 ± 0.15
T	0.033 ± 0.004	0.85 ± 0.10
a	0.022 ± 0.006	0.55 ± 0.15
b	0.014 ± 0.006	0.35 ± 0.15
c	0.012 +.004/-.008	0.30 +0.1/-0.2
g	0.016 ± 0.006	0.40 ± 0.15
p	0.039 ± 0.004	1.00 ± 0.10



Terminal Configuration

No.	Function
1	GND or DC feed
2	Unbalanced Port (1)
3	GND or DC feed
4	Balanced Port (2)
5	NC
6	Balanced Port (3)




Mounting Considerations

Mount these devices with brown mark facing up.


* Line width should be designed to provide proper impedance matching characteristics.


Units: mm

With DC feed



Without DC feed





Johanson Technology, Inc. reserves the right to make design changes without notice.
All sales are subject to Johanson Technology, Inc. terms and conditions.

JOHANSON TECHNOLOGY

www.johansontechnology.com

931 Via Alondra • Camarillo, CA 93012 • TEL 805.389.1166 FAX 805.389.1821


2003 Johanson Technology, Inc. All Rights Reserved

900 MHz Balun **P/N 0900BL18B100**


Detail Specification: 08/27/04

Typical Electrical Performance (T=25°C)

Insertion Loss



Return Loss



Johanson Technology, Inc. reserves the right to make design changes without notice.
All sales are subject to Johanson Technology, Inc. terms and conditions.

JOHANSON TECHNOLOGY

www.johansontechnology.com

931 Via Alondra • Camarillo, CA 93012 • TEL 805.389.1166 FAX 805.389.1821

2003 Johanson Technology, Inc. All Rights Reserved