


CATALOG LISTING
M101TL2 SERIES CHART 2
PAGE 1 OF 1
ISSUE 15
RELEASE NO. PR-3340
CHECK
REPLACES
DRAWN
D B W 14 MAY 73
LSD 18 MAR 73
CHICK
RASTER

MICRO SWITCH
FREEPORT, ILLINOIS, U.S.A.
A DIVISION OF HONEYWELL
FED. MFG. CODE 91929

CATALOG LISTING
101TL2 SERIES
CHART 2
SWITCH - TOGGLE



THIS DRAWING COVERS A PROPRIETARY ITEM AND IS THE PROPERTY OF MICRO SWITCH, A DIVISION OF HONEYWELL. THIS DRAWING IS NOT TO BE COPIED OR USED WITHOUT THE APPROVAL OF MICRO SWITCH.



- NOTES
- 1 - SWITCHES ARE CAPABLE OF WITHSTANDING A TEMPERATURE OF 160° F CONTINUOUSLY AT FULL RATED LOAD
 - 2 - CIRCUIT DESIGNATION, MICRO SWITCH CATALOG LISTING, DATE CODE AND "MS" NUMBER IDENTIFIED ON SIDE OF SWITCH
 - 3 - KEYWAY SHOWN ON LEFT SIDE
 - 4 - FURNISHED UNASSEMBLED
 - 5 - THESE SWITCHES ARE QUALIFIED UNDER MIL-S-3950
 - 6 - SUFFIX LETTER MUST BE ADDED FOR DESIRED TYPE TOGGLE LOCKING
 - 7 - SEE CHART FOR AVAILABLE LOCKING COMBINATIONS
 - 8 - CIRCUIT DIAGRAMS APPLY ONLY TO "ON" AND "MOM ON" POSITIONS
 - 9 - THE SEALING GROMMET SHALL SEAL ON A SMOOTH WIRE INSULATION OF .040 TO .083 DIAMETERS (16-20 GAGE)
 - 10 - UNUSED TERMINAL HOLES MAY BE SEALED WITH PLUGS M83723/28-20

SCALE FULL		
DO NOT SCALE PRINT		
UNLESS OTHERWISE NOTED		
DIMENSIONS ARE IN INCHES		
TOLERANCES ARE		
ONE PLACE (.0)	± .030	
TWO PLACE (.00)	± .015	
THREE PLACE (.000)	± .008	
ANGLES		
WEIGHT		

CAT. LIST.	AVAILABLE LOCKING COMBINATIONS FOR CONFIGURATION SEE LETTERED DETAILS	CIRCUIT WITH TOGGLE IN			CURRENT CAPACITY (AMPS)								MS NUMBER △ 6	
		EXTREME POSITION KEYWAY SIDE	CENTER	EXTREME POSITION OPPOSITE KEYWAY	RESISTIVE LOAD					LAMP LOAD		INDUCTIVE LOAD		
					DC VOLTS		AC VOLTS		30 VDC	115 VAC	30 VDC	115 VAC		
					30	115	250	115						230
101TL2-1 △	A,B,D,E,F,G,H,J,K,L,M,N,P	ON	OFF	ON	75	.75	.5	75	6	5	3	75	7.5	27787-21
101TL2-2 △	D, F, G	OFF	NONE	ON										27787-22
101TL2-3 △	D, F, G	ON	NONE	ON										27787-23
101TL2-21 △	E, F, K, M, N	NONE	OFF	ON										27787-24
101TL2-31 △	E, F, K, M	NONE	ON	ON										27787-33
101TL2-4 △	F, G	MOM OFF	NONE	ON	7.5	.75	.5	75	6	4	2	75	7.5	27787-29
101TL2-5 △	E, F, K, L, M, N	MOM ON	OFF	ON										27787-31
101TL2-6 △	F	MOM ON	NONE	OFF										27787-30
101TL2-7 △	E, L, N	MOM ON	OFF	MOM ON										27787-27
101TL2-8 △	F	MOM ON	NONE	ON										27787-26
101TL2-51 △	E	NONE	ON	MOM ON										27787-32
101TL2-61 △	E	MOM ON	OFF	NONE										27787-28
														27787-25



10 FROM BOTTOM OF KEYWAY TO MAJOR DIA OF 15/32 THREAD