EPCOS

SAW Components

Data Sheet G 1963 M

Data Sheet

Standard

Plastic package **SIP5K**

- B/G



Features

- TV IF filter with Nyquist slope and sound shelf
- High color carrier level
- Reduced group delay predistortion as compared with standard B/G, half
- Suitable for CENELEC EN 55020

Terminals

- Tinned CuFe alloy

Dimensions in mm, approx. weight 1,0 g

Pin configuration

1	Input
2	Input - ground
3	Chip carrier - ground
4	Output
5	Output



Type	Ordering code	Marking and package according to	Packing according to
G 1963 M	B39389-G1963-M100	C61157-A1-A15	F61074-V8067-Z000

Maximum ratings

Operable temperature range	T_A	–25/+65	˚C	
Storage temperature range	T_{stg}	–40/+85	˚C	
DC voltage	V_{DC}	12	V	between any terminals
AC voltage	V_{pp}	10	V	between any terminals

Characteristics

Reference temperature: T_A = 25 °C
Terminating source impedance: Z_S = 50 Ω
Terminating load impedance: Z_L = 2 kΩ || 3 pF

			min.	typ.	max.	
Insertion attenuation		α				
Reference level for the following data	37,40 MHz		12,7	14,2	15,7	dB
Relative attenuation		α_{rel}				
Picture carrier	38,90 MHz		4,9	5,9	6,9	dB
Color carrier	34,47 MHz		–0,4	0,6	1,6	dB
	34,15 MHz		—	3,2	—	dB
Sound carrier	33,40 MHz		19,1	20,1	21,1	dB
Adjacent picture carrier UHF	30,90 MHz		44,0	55,0	—	dB
VHF	31,90 MHz		42,0	46,0	—	dB
	32,40 MHz		42,0	46,0	—	dB
	40,15 MHz		42,0	50,0	—	dB
Adjacent sound carrier VHF	40,40 MHz		45,0	53,0	—	dB
UHF	41,40 MHz		42,0	49,0	—	dB
Lower sidelobe 25,00 ...	32,40 MHz		41,0	45,0	—	dB
Upper sidelobe 40,40 ...	45,00 MHz		36,0	40,0	—	dB
Reflected wave signal suppression						
1,1 µs ... 6,0 µs after main pulse (test pulse 250 ns, carrier frequency 37,40 MHz)			44,0	50,0	—	dB
Feedthrough signal suppression						
1,2 µs ... 1,1 µs before main pulse (test pulse 250 ns, carrier frequency 37,40 MHz)			50,0	56,0	—	dB
Group delay predistortion (reference frequency 38,90 MHz)		$\Delta\tau$				
	37,00 MHz		—	–85	—	ns
	34,47 MHz		—	0	—	ns
Impedance at 37,40 MHz						
Input: $Z_{IN} = R_{IN} \parallel C_{IN}$			—	1,8 || 14,8	—	kΩ || pF
Output: $Z_{OUT} = R_{OUT} \parallel C_{OUT}$			—	1,6 || 5,3	—	kΩ || pF
Temperature coefficient of frequency		TC_f	—	–72	—	ppm/K

Frequency response





Frequency response



Time domain response



Published by EPCOS AG
Surface Acoustic Wave Components Division, SAW CE MM PD
P.O. Box 80 17 09, D-81617 München

© EPCOS AG 2001. All Rights Reserved.

As far as patents or other rights of third parties are concerned, liability is only assumed for components per se, not for applications, processes and circuits implemented within components or assemblies.

The information describes the type of component and shall not be considered as assured characteristics.
Terms of delivery and rights to change design reserved.

For questions on technology, prices and delivery please contact the sales offices of EPCOS AG or the international representatives.

Due to technical requirements components may contain dangerous substances. For information on the type in question please also contact one of our sales offices.