

ASMT-Mx22/ASMT-MxE2

Moonstone[®] 3W High Brightness Power LED Light Source



Overview

The Broadcom[®] Moonstone[®] 3W high brightness power LED light source is a high-performance energy-efficient device that can handle high thermal and high driving current. The exposed pad design has excellent heat transfer from the package to the motherboard.

The cool white power LED is available in various color temperature ranging from 4000K to 10,000K and warm white power LED ranging from 2600K to 4000K.

The low profile package design is suitable for a wide variety of applications especially where height is a constraint.

The package is compatible with reflow soldering. This will give more freedom and flexibility to the light source designer.

Applications

- Sign backlight
- Safety, exit, and emergency sign lightings
- Specialty lighting, such as task lighting and reading lights
- Retail display
- Commercial lighting
- Accent or marker lightings, strip or step lightings
- Portable lightings, bicycle head lamp, torch lights
- Decorative lighting
- Architectural lighting
- Pathway lighting
- Street lighting
- Pedestrian street lighting
- Tunnel lighting


Features

- Available in cool white and warm white colors
- Energy efficient
- Exposed pad for excellent heat transfer
- Suitable for reflow soldering process
- High current operation
- Long operation life
- Wide viewing angle
- Silicone encapsulation
- Non-ESD sensitive (threshold > 16 kV)
- MSL 4 products

Specifications


- InGaN technology
- 3.5V (max.) at 350 mA
- 110° viewing angle

Figure 1: Package Dimensions

**NOTE:**

1. All dimensions are in millimeters (mm).
2. Unless otherwise stated, the tolerance for dimension is ± 0.1 mm.
3. Metal slug is connected to anode for electrically non-isolated option.

Part Numbering System



NOTE: For selection details, see [Option Selection Details](#).

Device Selection Guide ($T_J = 25^\circ\text{C}$)

| Part Number | Color | Luminous Flux, $\phi_V^{a,b}$ (lm) | | | Test Current (mA) | Dice Technology | Electrically Isolated Metal Slug |
|-----------------|---------------------|------------------------------------|------|------|-------------------|-----------------|----------------------------------|
| | | Min. | Typ. | Max. | | | |
| ASMT-MW22-NNP00 | Cool White | 110 | 120 | 140 | 350 | InGaN | Yes |
| ASMT-MY22-NMP00 | Warm White | 95 | 100 | 140 | 350 | InGaN | Yes |
| ASMT-MWE2-NNP00 | Cool White Diffused | 110 | 115 | 140 | 350 | InGaN | Yes |
| ASMT-MYE2-NMP00 | Warm White Diffused | 95 | 98 | 140 | 350 | InGaN | Yes |

a. ϕ_V is the total luminous flux output as measured with an integrating sphere at 25-ms mono pulse condition.

b. Flux tolerance is $\pm 10\%$.

Absolute Maximum Ratings

| Parameter | ASMT-Mx22/ASMT-MxE2 | Units |
|--|-------------------------------|-------|
| DC Forward Current ^a | 700 | mA |
| Peak Pulsing Current | 2400 | mA |
| Power Dissipation | 2730 | mW |
| LED Junction Temperature | 125 | °C |
| Operating Metal Slug Temperature Range at 350 mA | -40 to +110 | °C |
| Operating Metal Slug Temperature Range at 700 mA | -40 to +95 | °C |
| Storage Temperature Range | -40 to +120 | °C |
| Soldering Temperature | See Figure 11 | |
| Reverse Voltage ^b | Not recommended | |

a. Derate linearly based on [Figure 9](#).

b. Not designed for reverse bias operation.

Optical Characteristics at 350 mA ($T_J = 25^\circ\text{C}$)

| Part Number | Color | Correlated Color Temperature, CCT (Kelvin) | | Viewing Angle $2\theta_{1/2}$ ^a (Degrees) | Luminous Efficiency (lm/W) |
|-----------------|---------------------|--|-------|--|----------------------------|
| | | Min. | Max. | Typ. | Typ. |
| ASMT-MW22-NNP00 | Cool White | 4000 | 10000 | 110 | 107 |
| ASMT-MY22-NMP00 | Warm White | 2600 | 4000 | 110 | 89 |
| ASMT-MWE2-NNP00 | Cool White Diffused | 4000 | 10000 | 110 | 103 |
| ASMT-MYE2-NMP00 | Warm White Diffused | 2600 | 4000 | 110 | 88 |

a. $\theta_{1/2}$ is the off-axis angle where the luminous intensity is $1/2$ the peak intensity.

Electrical Characteristics at 350 mA ($T_J = 25^\circ\text{C}$)

| Dice Type | Forward Voltage V_F (Volts) | | | Thermal Resistance R_{θ_j-ms} ($^\circ\text{C/W}$) ^a | Temperature Coefficient of Forward Voltage (mV/ $^\circ\text{C}$), $\Delta V_F/\Delta T_J$ |
|-----------|-------------------------------|------|------|---|---|
| | Min. | Typ. | Max. | Typ. | Typ. |
| InGaN | 2.8 | 3.2 | 3.5 | 10 | -1.5 to -3.5 |

a. R_{θ_j-ms} is the thermal resistance from the LED junction to the metal slug.

Typical Characteristic at 700 mA ($T_J = 25^\circ\text{C}$)

| Part Number | Color | Luminous Flux, Φ_V (lm) | Forward Voltage, V_F (Volts) |
|-----------------|---------------------|------------------------------|--------------------------------|
| | | Typ. | Typ. |
| ASMT-MW22-NNP00 | Cool White | 205 | 3.6 |
| ASMT-MY22-NMP00 | Warm White | 170 | 3.6 |
| ASMT-MWE2-NNP00 | Cool White Diffused | 196 | 3.6 |
| ASMT-MYE2-NMP00 | Warm White Diffused | 167 | 3.6 |

Figure 2: Relative Intensity vs. Wavelength




Figure 3: Relative Luminous Flux vs. Forward Current




Figure 4: Forward Current vs. Forward Voltage




Figure 5: Radiation Pattern




Figure 6: Maximum Pulse Current vs. Pulse Duration. Derated based on $T_A = 25^\circ\text{C}$, $R_{\theta J-A} = 30^\circ\text{C/W}$.




Figure 7: Maximum Pulse Current vs. Pulse Duration. Derated based on $T_A = 85^\circ\text{C}$, $R_{\theta J-A} = 30^\circ\text{C/W}$.




Figure 8: Relative Light Output vs. Junction Temperature.




Figure 9: Maximum Forward Current vs. Ambient Temperature. Derated based on T_{JMAX} = 125°C, R_{θJ-A} = 20°C/W, 25°C/W, and 30°C/W.




Figure 10: Maximum Forward Current vs. Metal Slug Temperature. Derated based on T_{JMAX} = 125°C, R_{θJ-MS} = 10°C/W.




Figure 11: Recommended Reflow Soldering





Figure 12: Recommended Soldering Land Pattern



NOTE: For detailed information on reflow soldering of Broadcom surface mount LEDs, refer to Broadcom Application Note AN1060, *Surface Mounting SMT LED Indicator Components*.

Option Selection Details

ASMT – M x₁ x₂ x₃ – N x₄ x₅ x₆ x₇

x₄ – Minimum Flux Bin

x₅ – Maximum Flux Bin

x₆ – Color Bin Selection

x₇ – Packaging Option

Flux Bin Limit [x₄x₅]

| Bin | Flux (lm) at 150mA | |
|-----|--------------------|-------|
| | Min | Max |
| K | 56.0 | 73.0 |
| L | 73.0 | 95.0 |
| M | 95.0 | 110.0 |
| N | 110.0 | 125.0 |
| P | 125.0 | 140.0 |

NOTE: Tolerance for each bin limits is ±10%.

Color Bin Selection [x₃]

Individual reel will contain parts from one color bin selection only.

Cool White

| Selection | Bin ID |
|-----------|---------------------|
| 0 | Full Distribution |
| A | A only |
| B | B only |
| C | C only |
| D | D only |
| E | E only |
| F | F only |
| G | G only |
| H | H only |
| L | A and G only |
| M | B and H only |
| N | A and C only |
| P | B and D only |
| Q | E and C only |
| R | F and D only |
| S | G and H only |
| U | E and F only |
| W | C and D only |
| Z | A and B only |
| 1 | A, B, C, and D only |
| 2 | G, H, A, and B only |
| 4 | C, D, E, and F only |

Warm White


| Selection | Bin |
|-----------|---------------------|
| 0 | Full Distribution |
| A | A only |
| B | B only |
| C | C only |
| D | D only |
| E | E only |
| F | F only |
| N | A and C only |
| P | B and D only |
| Q | E and C only |
| R | F and D only |
| U | E and F only |
| W | C and D only |
| Z | A and B only |
| 1 | A, B, C, and D only |
| 4 | C, D, E, and F only |

Color Bin Limit

| Cool White | Color Limits (Chromaticity Coordinates) | | | | |
|------------|---|-------|-------|-------|-------|
| Bin A | X | 0.367 | 0.362 | 0.329 | 0.329 |
| | Y | 0.400 | 0.372 | 0.345 | 0.369 |
| Bin B | X | 0.362 | 0.356 | 0.329 | 0.329 |
| | Y | 0.372 | 0.330 | 0.302 | 0.345 |
| Bin C | X | 0.329 | 0.329 | 0.305 | 0.301 |
| | Y | 0.369 | 0.345 | 0.322 | 0.342 |
| Bin D | X | 0.329 | 0.329 | 0.311 | 0.305 |
| | Y | 0.345 | 0.302 | 0.285 | 0.322 |
| Bin E | X | 0.303 | 0.307 | 0.283 | 0.274 |
| | Y | 0.333 | 0.311 | 0.284 | 0.301 |
| Bin F | X | 0.307 | 0.311 | 0.290 | 0.283 |
| | Y | 0.311 | 0.285 | 0.265 | 0.284 |
| Bin G | X | 0.388 | 0.379 | 0.362 | 0.367 |
| | Y | 0.417 | 0.383 | 0.372 | 0.400 |
| Bin H | X | 0.379 | 0.369 | 0.356 | 0.362 |
| | Y | 0.383 | 0.343 | 0.330 | 0.372 |

Tolerance: ±0.01

Figure 13: Color Bins (Cool White)




Packaging Option [x7]

| Selection | Option |
|-----------|---------------|
| 0 | Tube |
| 1 | Tape and Reel |

| Warm White | Color Limits (Chromaticity Coordinates) | | | | |
|------------|---|-------|-------|-------|-------|
| Bin A | X | 0.452 | 0.488 | 0.470 | 0.438 |
| | Y | 0.434 | 0.447 | 0.414 | 0.403 |
| Bin B | X | 0.438 | 0.470 | 0.452 | 0.424 |
| | Y | 0.403 | 0.414 | 0.384 | 0.376 |
| Bin C | X | 0.407 | 0.418 | 0.452 | 0.438 |
| | Y | 0.393 | 0.422 | 0.434 | 0.403 |
| Bin D | X | 0.395 | 0.407 | 0.438 | 0.424 |
| | Y | 0.362 | 0.393 | 0.403 | 0.376 |
| Bin E | X | 0.381 | 0.387 | 0.418 | 0.407 |
| | Y | 0.377 | 0.404 | 0.422 | 0.393 |
| Bin F | X | 0.373 | 0.381 | 0.407 | 0.395 |
| | Y | 0.349 | 0.377 | 0.393 | 0.362 |

Tolerance: ±0.01

Figure 14: Color Bins (Warm White)




Example

ASMT-MW20-NLNZ0

- ASMT-MW20-Nxxxx – Cool White, Electrically Non-Isolated Heat Sink, Non-diffused
- x₄ = L – Minimum Flux Bin L
- x₅ = N – Maximum Flux Bin N
- x₆ = Z – Color Bin A and B only
- x₇ = 0 – Tube Option


Packing Tube – Option 0

Figure 15: Tube Dimensions




Tape and Reel – Option 1

Figure 16: Carrier Tape Dimensions




| Dimension | Value (in mm) |
|----------------|---------------|
| A ₀ | 8.80 ±0.10 |
| B ₀ | 16.45 ±0.10 |
| K ₀ | 3.60 ±0.10 |
| E | 1.75 ±0.10 |
| F | 11.50 ±0.10 |
| W | 24.0 ±0.10 |
| P | 16.0 ±0.10 |
| Quantity/Reel | 250 units |

Figure 17: Carrier Tape Leader and Trailer Dimensions



*Note: Tape & Reel Packaging only applicable as per this data sheet only.

Figure 18: Reel Dimensions



Handling Precautions

The encapsulation material of the product is made of silicone for better reliability of the product. As silicone is a soft material, do not press on the silicone or poke a sharp object onto the silicone. These actions might damage the product and cause premature failure. During assembly or handling, hold the unit only on the body. Refer to Broadcom Application Note AN 5288 for detailed information.

Moisture Sensitivity

This product is qualified as Moisture Sensitive Level 4 per JEDEC J-STD-020. Take precautions when handling this moisture-sensitive product to ensure the reliability of the product. Refer to Broadcom Application Note AN 5305 *Handling of Moisture Sensitive Surface Mount Devices* for details.

- Storage before use
 - An unopened moisture barrier bag (MBB) can be stored at <math><40^{\circ}\text{C}/90\% \text{RH}</math> for 12 months. If the actual shelf life has exceeded 12 months and the humidity indicator card (HIC) indicates that baking is not required, it is safe to reflow the LEDs per the original MSL rating.
 - Do not open the MBB prior to assembly (for example, for IQC).
- Control after opening the MBB
 - Read the HIC immediately upon opening the MBB.
 - The LEDs must be kept at <math><30^{\circ}\text{C}/60\% \text{RH}</math> at all times and all high temperature-related processes, including soldering, curing, or rework, must be completed within 72 hours.
- Control for unfinished reel

For any unused LEDs, they must be stored in a sealed MBB with desiccant or desiccator at <math><5\% \text{RH}</math>.
- Control of assembly boards

If the PCB soldered with the LEDs is to be subjected to other high temperature processes, the PCB need to be stored in a sealed MBB with desiccant or desiccator at <math><5\% \text{RH}</math> to ensure that no LEDs have exceeded their floor life of 72 hours.

- Baking is required if:
 - The HIC 10% indicator is not blue and the 5% indicator is pink.
 - The LEDs are exposed to conditions of >30°C/60% RH at any time.
 - The LEDs' floor life exceeded 72 hours.

Recommended baking condition: 60°C ± 5°C for 20 hours.

Disclaimer

Broadcom's products and software are not specifically designed, manufactured, or authorized for sale as parts, components, or assemblies for the planning, construction, maintenance, or direct operation of a nuclear facility or for use in medical devices or applications. The customer is solely responsible, and waives all rights to make claims against Broadcom or its suppliers, for all loss, damage, expense, or liability in connection with such use.

Broadcom, the pulse logo, Connecting everything, Avago Technologies, Avago, the A logo, and Moonstone are among the trademarks of Broadcom and/or its affiliates in the United States, certain other countries and/or the EU.

Copyright © 2017 by Broadcom. All Rights Reserved.

The term "Broadcom" refers to Broadcom Limited and/or its subsidiaries. For more information, please visit www.broadcom.com.

Broadcom reserves the right to make changes without further notice to any products or data herein to improve reliability, function, or design. Information furnished by Broadcom is believed to be accurate and reliable. However, Broadcom does not assume any liability arising out of the application or use of this information, nor the application or use of any product or circuit described herein, neither does it convey any license under its patent rights nor the rights of others.

