







Stecklänge / mating length




E = early mate, late break / voreilend

S = standard


L = late mate, early break / nacheilend



Bestückungsplan / contact layout



Leiterplatten- Lochbild / PCB drillhole pattern



Lötanschluss 0,6x0,6mm / solder terminal 0,6x0,6mm

Isolierwerkstoff / housing material : PBT GF 30

Bauart 4 / type 4

Anforderungsstufe 2 = 400 Steckzyklen / performance class 2 = 400 mating cycles

Fehlende Maße und Angaben nach IEC 60 603-2 / DIN EN 60 603-2

Missing information and dimensions per IEC 60 603-2 / DIN EN 60 603-2

Berückung siehe Zeichnung 294905

marking see drawing 294905

Copyright by ERNI GmbH
Proprietary notice pursuant to ISO 16016 to be observed.

Proprietary notice pursuant to ISO 16016 is to be observed.

Information:				Tolerances		 All Dimensions in mm		Scale		2:1			
All rights reserved. Only for Information. To ensure that this is the latest version of this drawing, please contact one of the ERNI companies before using.				Subject to modification without prior notice. Drawing will not be updated.				Designation					
								Messerleiste C/3 30 Löt <i>Male Connector C/3 30 solder</i>					
				B		13.08.2009				www.ERNI.com		254325	
				Index		Date							
								Class		STVC/3			
										I			
										A3			