SONY


SGM2016AM/AP

GaAs N-channel Dual-Gate MES FET

For the availability of this product, please contact the sales office.

Description

The SGM2016AM/AP is an N-channel dual-gate GaAs MES FET for UHF-band low-noise amplification. This FET is suitable for a wide range of applications including UHF TV tuners, cellular/cordless phone, and DBS IF amplifiers.



Features

- Low voltage operation
- Low noise NF = 1.2dB (typ.) at 900MHz
- High gain Ga = 21dB (typ.) at 900MHz
- High stability
- Built-in gate protection diode

Application

UHF-band high-frequency amplifier, mixer, and oscillator

Structure

GaAs, N-channel, dual-gate metal semiconductor field-effect transistor

Absolute Maximum Ratings (Ta = 25°C)

• Drain to source voltage	V_{DSX}	12	V
• Gate 1 to source voltage	V_{G1S}	–5	V
• Gate 2 to source voltage	V_{G2S}	–5	V
• Drain current	I_D	55	mA
• Allowable power dissipation	P_D	150	mW
• Channel temperature	Tch	150	°C
• Storage temperature	Tstg	–55 to +150	°C

Sony reserves the right to change products and specifications without prior notice. This information does not convey any license by any implication or otherwise under any patents or other right. Application circuits shown, if any, are typical examples illustrating the operation of the devices. Sony cannot assume responsibility for any problems arising out of the use of these circuits.


E96Y10-PS

Electrical Characteristics (Ta = 25°C)


Item	Symbol	Conditions	Min.	Typ.	Max.	Unit
Drain cut-off current	I_{DSX}	V_{DS} = 12V V_{G1S} = –4V V_{G2S} = 0V			50	µA
Gate 1 to source current	I_{G1SS}	V_{G1S} = –4.5V V_{G2S} = 0V V_{DS} = 0V			–8	µA
Gate 2 to source current	I_{G2SS}	V_{G2S} = –4.5V V_{G1S} = 0V V_{DS} = 0V			–8	µA
Drain saturation current	I_{DSS}	V_{DS} = 5V V_{G1S} = 0V V_{G2S} = 0V	10		35	mA
Gate 1 to source cut-off voltage	V_{G1S} (OFF)	V_{DS} = 5V I_D = 100µA V_{G2S} = 0V			–2.5	V
Gate 2 to source cut-off voltage	V_{G2S} (OFF)	V_{DS} = 5V I_D = 100µA V_{G1S} = 0V			–2.5	V
Forward transfer admittance	gm	V_{DS} = 5V I_D = 10mA V_{G2S} = 1.5V f = 1kHz	20	30		ms
Input capacitance	Ciss	V_{DS} = 5V I_D = 10mA V_{G2S} = 1.5V f = 1MHz		0.9	2.0	pF
Feedback capacitance	Crss			25	40	fF
Noise figure	NF	V_{DS} = 5V I_D = 10mA V_{G2S} = 1.5V f = 900MHz		1.2	2.0	dB
NF associated gain	Ga		17	21		dB

Typical Characteristics (Ta = 25°C)


I_D vs. V_{DS}




I_D vs. V_{G1S}




I_D vs. V_{G2S}




gm vs. V_{G1S}




NF vs. V_{G1S}




Ga vs. V_{G1S}



NF, Ga vs. I_D



NF, Ga vs. f



S-parameter vs. Frequency Characteristics (V_{DS} = 5V, V_{G2S} = 1.5V, I_D = 10mA) (Z_0 = 50Ω)

f (MHz)	S11		S21		S12		S22	
	MAG	ANG	MAG	ANG	MAG	ANG	MAG	ANG
100	0.999	–3.8	2.521	174.2	0.002	95.0	0.969	–1.3
200	0.994	–7.9	2.515	168.1	0.003	87.9	0.966	–3.0
300	0.981	–11.8	2.499	162.3	0.005	83.6	0.964	–4.2
400	0.969	–16.0	2.480	156.3	0.006	77.7	0.961	–6.1
500	0.952	–20.0	2.451	150.6	0.007	82.1	0.957	–7.2
600	0.935	–24.1	2.420	144.8	0.009	76.3	0.955	–8.8
700	0.917	–27.8	2.391	139.4	0.009	76.8	0.955	–9.9
800	0.896	–31.3	2.362	133.9	0.010	78.7	0.954	–11.5
900	0.877	–34.7	2.331	128.5	0.011	74.4	0.954	–12.8
1000	0.850	–38.0	2.294	122.9	0.012	82.6	0.953	–14.4
1100	0.822	–40.9	2.254	117.7	0.012	79.3	0.952	–15.6
1200	0.797	–44.0	2.216	112.4	0.012	72.4	0.949	–17.2
1300	0.769	–46.8	2.182	107.3	0.013	79.0	0.947	–18.2
1400	0.744	–49.7	2.153	102.1	0.013	81.5	0.946	–20.0
1500	0.717	–52.4	2.118	96.9	0.013	80.3	0.945	–21.3
1600	0.692	–54.9	2.076	91.8	0.013	83.7	0.945	–22.9
1700	0.668	–57.5	2.038	86.6	0.013	90.1	0.945	–24.1
1800	0.641	–59.6	2.005	81.4	0.013	98.4	0.945	–25.8
1900	0.617	–61.6	1.963	76.4	0.013	109.0	0.945	–27.3
2000	0.589	–63.4	1.929	71.5	0.013	113.0	0.945	–28.7


Noise Figure Characteristics (V_{DS} = 5V, V_{G2S} = 1.5V, I_D = 10mA)

f (MHz)	NFmin (dB)	Gamma Optimum		Rn (Ω)
		ANG	MAG	
200	0.73	0.94	7.5	40.0
300	0.79	0.90	10.8	39.5
400	0.85	0.87	13.9	39.0
500	0.92	0.84	16.8	38.5
600	0.99	0.81	19.5	37.9
700	1.05	0.78	22.0	37.4
800	1.11	0.75	24.5	36.8
900	1.18	0.72	26.8	36.1
1000	1.25	0.70	29.1	35.5
1100	1.32	0.67	31.4	34.8
1200	1.39	0.65	33.8	34.1
1300	1.46	0.63	36.1	33.4
1400	1.53	0.60	38.6	32.6
1500	1.61	0.58	41.2	31.9
1600	1.68	0.56	43.9	31.0
1700	1.76	0.54	46.8	30.2
1800	1.84	0.52	50.0	29.3
1900	1.92	0.50	53.4	28.5
2000	2.00	0.48	57.0	27.5

Package Outline Unit: mm

SGM2016AM

M-254




1. Source
2. Gate1
3. Gate2
4. Drain

SONY CODE	M-254
EIAJ CODE	————
JEDEC CODE	————

PACKAGE MASS	0.01g

SGM2016AP

M-255



1. Source
2. Drain
3. Gate2
4. Gate1

SONY CODE	M-255
EIAJ CODE	————
JEDEC CODE	————

PACKAGE MASS	0.01g