
GABJ501 thru GABJ506

Press Fit Automotive Rectifier
Voltage Range 100 to 600Volts Current 50 Amps

Technical Specification:

Features:

- Low leakage
- Low forward voltage drop
- High current capability
- High forward surge current capability



Dimensions in millimeters

Mechanical Data:

- Technology: Vacuum soldered
- Case: Copper case
- Polarity: As marked of case bottom
- Lead: Plated lead, solderable per MIL-STD-202E method 208C
- Mounting: Press Fit
- Weight: 0.229 ounces 6.48 grams

■Maximum Ratings and Electrical Characteristics

- Rating at 25°C ambient temperature unless otherwise specified.
- Single phase, half wave, 60Hz, resistive or inductive load.
- For capacitive load derate current by 20%.

Parameters	Symbols	GABJ501	GABJ502	GABJ503	GABJ504	GABJ506	Units
Maximum repetitive peak reverse voltage	V_{RRM}	100	200	300	400	600	Volts
Maximum RMS voltage	V_{RMS}	70	140	210	280	420	Volts
Maximum DC blocking voltage	V_{DC}	100	200	300	400	600	Volts
Maximum Average rectified forward current at T_C=105°C	$I_{(AV)}$	50					Amps
Peak forward surge current 8.3mS single half sine-wave superimposed on rated load (JEDEC Method)	I_{FSM}	600					Amps
Rating for fusing (t<8.3mS)	I^2t	1494					A^2S
Maximum instantaneous forward voltage drop at 100A	V_F	1.08					Volts
Maximum DC reverse current T_A=25°C at rated DC blocking voltage T_A=150°C	I_R	5.0 450					uA
Typical thermal resistance	$R_{\theta JL}$	0.8					°C/W
Operating and storage temperature range	T_J, T_{STG}	-65 to +175					°C

Notes: 1. Enough heatsink must be considered in application.

■Ratings and Characteristic Curves

FIG.1–TYPICAL FORWARD CURRENT DERATING CURVE




FIG.2–MAXIMUM NON–REPETITIVE PEAK FORWARD SURGE CURRENT




FIG.3–TYPICAL INSTANTANEOUS FORWARD CHARACTERISTICS




FIG.4– FORWARD POWER DISSIPATION

