MOSPEC


MBRF20100CK

Switchmode
Full Plastic Dual Schottky Barrier Power Rectifiers

SCHOTTKY BARRIER RECTIFIERS

20 AMPERES
100 VOLTS

Using the Schottky Barrier principle with a Refractory metal capable of high temperature operation metal. The proprietary barrier technology allows for reliable operation up to 175℃ junction temperature. Typical application are in switching Mode Power Supplies such as adaptors, DC/DC converters, free-wheeling and polarity protection diodes.




ITO-220AB


Features.

- ＊Low Forward Voltage.
- ＊Low Switching noise.
- ＊High Current Capacity
- ＊Guarantee Reverse Avalanche.
- ＊Guard-Ring for Stress Protection.
- ＊Low Power Loss & High efficiency.
- ＊175℃ Operating Junction Temperature
- ＊Low Stored Charge Majority Carrier Conduction.
- ＊Plastic Material used Carries Underwriters Laboratory Flammability Classification 94V-O

＊*In compliance with EU RoHs 2002/95/EC directives*



DIM	MILLIMETERS	
	MIN	MAX
A	14.90	15.15
B	13.35	13.55
C	10.00	10.10
D	6.55	6.65
E	2.65	2.75
F	1.55	1.65
G	1.15	1.25
H	0.55	0.65
I	2.50	2.60
J	3.00	3.20
K	1.10	1.20
L	0.55	0.65
M	4.40	4.60
N	1.15	1.25
O	3.35	3.45
P	2.65	2.75
Q	3.15	3.25
R	3.60	3.80



MAXIMUM RATINGS

Characteristic	Symbol	MBRF20100CK	Unit
Peak Repetitive Reverse Voltage Working Peak Reverse Voltage DC Blocking Voltage	V_{RRM} V_{RWM} V_R	100	V
RMS Reverse Voltage	$V_{R(RMS)}$	70	V
Average Rectifier Forward Current (per diode) Total Device (Rated V_R), T_C=125℃	$I_{F(AV)}$	10 20	A
Peak Repetitive Forward Current (Rate V_R, Square Wave, 20kHz)	I_{FM}	20	A
Non-Repetitive Peak Surge Current (Surge applied at rate load conditions halfware, single phase, 60Hz)	I_{FSM}	150	A
Operating and Storage Junction Temperature Range	T_J , T_{stg}	-65 to +175	℃

THERMAL RESISTANCES

Typical Thermal Resistance junction to case	$R_{\theta jc}$	3.4	℃/w

ELECTRIAL CHARACTERISTICS

Characteristic	Symbol	MBRF20100CK	Unit
Maximum Instantaneous Forward Voltage (per diode) (I_F =10 Amp T_C = 25℃) (I_F =10 Amp T_C = 125℃)	V_F	0.85 0.75	V
Maximum Instantaneous Reverse Current (Rated DC Voltage, T_C = 25℃) (Rated DC Voltage, T_C = 125℃)	I_R	0.01 10	mA

MBRF20100CK

FIG-1 FORWARD CURRENT DERATING CURVE




FIG-2 TYPICAL FORWARD CHARACTERISITICS




FIG-3 TYPICAL REVERSE CHARACTERISTICS




FIG-4 TYPICAL JUNCTION CAPACITANCE




FIG-5 PEAK FORWARD SURGE CURRENT

