International
IOR Rectifier

PD - 9.1262D

IRF7603

HEXFET® Power MOSFET

- Generation V Technology
- Ultra Low On-Resistance
- N-Channel MOSFET
- Very Small SOIC Package
- Low Profile (<1.1mm)
- Available in Tape & Reel
- Fast Switching



Top View

V_{DSS} = 30V

$R_{DS(on)}$ = 0.035Ω


Micro8

Description

Fifth Generation HEXFETs from International Rectifier utilize advanced processing techniques to achieve extremely low on-resistance per silicon area. This benefit, combined with the fast switching speed and ruggedized device design that HEXFET Power MOSFETs are well known for, provides the designer with an extremely efficient and reliable device for use in a wide variety of applications.

The new Micro8 package, with half the footprint area of the standard SO-8, provides the smallest footprint available in an SOIC outline. This makes the Micro8 an ideal device for applications where printed circuit board space is at a premium. The low profile (<1.1mm) of the Micro8 will allow it to fit easily into extremely thin application environments such as portable electronics and PCMCIA cards.

Absolute Maximum Ratings

	Parameter	Max.	Units
I_D @ T_A = 25°C	Continuous Drain Current, V_{GS} @ 10V	5.6	A
I_D @ T_A = 70°C	Continuous Drain Current, V_{GS} @ 10V	4.5	
I_{DM}	Pulsed Drain Current ①	30	
P_D @T_A = 25°C	Power Dissipation	1.8	W
	Linear Derating Factor	14	mW/°C
V_{GS}	Gate-to-Source Voltage	± 20	V
dv/dt	Peak Diode Recovery dv/dt ②	5.0	V/ns
T_J,T_{STG}	Junction and Storage Temperature Range	-55 to + 150	°C

Thermal Resistance

	Parameter	Typ.	Max.	Units
$R_{\theta JA}$	Maximum Junction-to-Ambient④	——	70	°C/W

All Micro8 Data Sheets reflect improved Thermal Resistance, Power and Current -Handling Ratings- effective only for product marked with Date Code 505 or later .

Electrical Characteristics @ T_J = 25°C (unless otherwise specified)

	Parameter	Min.	Typ.	Max.	Units	Conditions
$V_{(BR)DSS}$	Drain-to-Source Breakdown Voltage	30	——	——	V	V_{GS} = 0V, I_D = 250µA
$\Delta V_{(BR)DSS}/\Delta T_J$	Breakdown Voltage Temp. Coefficient	——	0.029	——	V/°C	Reference to 25°C, I_D = 1mA
$R_{DS(on)}$	Static Drain-to-Source On-Resistance	——	——	0.035	Ω	V_{GS} = 10V, I_D = 3.7A ③
		——	——	0.060		V_{GS} = 4.5V, I_D = 1.9A ③
$V_{GS(th)}$	Gate Threshold Voltage	1.0	——	——	V	V_{DS} = V_{GS}, I_D = 250µA
g_{fs}	Forward Transconductance	4.3	——	——	S	V_{DS} = 10V, I_D = 1.9A
I_{DSS}	Drain-to-Source Leakage Current	——	——	1.0	µA	V_{DS} = 24V, V_{GS} = 0V
		——	——	25		V_{DS} = 24V, V_{GS} = 0V, T_J = 125°C
I_{GSS}	Gate-to-Source Forward Leakage	——	——	-100	nA	V_{GS} = -20V
	Gate-to-Source Reverse Leakage	——	——	100		V_{GS} = 20V
Q_g	Total Gate Charge	——	18	27	nC	I_D = 3.7A
Q_{gs}	Gate-to-Source Charge	——	2.4	3.6		V_{DS} = 24V
Q_{gd}	Gate-to-Drain ("Miller") Charge	——	5.6	8.4		V_{GS} = 10V, See Fig. 6 and 9 ③
$t_{d(on)}$	Turn-On Delay Time	——	5.7	——	ns	V_{DD} = 15V
t_r	Rise Time	——	28	——		I_D = 3.7A
$t_{d(off)}$	Turn-Off Delay Time	——	18	——		R_G = 6.2Ω
t_f	Fall Time	——	12	——		R_D = 4.0Ω, See Fig. 10 ③
C_{iss}	Input Capacitance	——	520	——	pF	V_{GS} = 0V
C_{oss}	Output Capacitance	——	200	——		V_{DS} = 25V
C_{rss}	Reverse Transfer Capacitance	——	80	——		f = 1.0MHz, See Fig. 5

Source-Drain Ratings and Characteristics

	Parameter	Min.	Typ.	Max.	Units	Conditions
I_S	Continuous Source Current	——	——	1.8	A	MOSFET symbol showing the integral reverse p-n junction diode.
	(Body Diode)					
I_{SM}	Pulsed Source Current	——	——	30		
	(Body Diode) ①					
V_{SD}	Diode Forward Voltage	——	——	1.2	V	T_J = 25°C, I_S = 3.7A, V_{GS} = 0V ③
t_{rr}	Reverse Recovery Time	——	53	80	ns	T_J = 25°C, I_F = 3.7A
Q_{rr}	Reverse RecoveryCharge	——	87	130	nC	di/dt = 100A/µs ③



Notes:

① Repetitive rating; pulse width limited by max. junction temperature. (See fig. 11)

② I_{SD} ≤ 3.7A, di/dt ≤ 130A/µs, V_{DD} ≤ $V_{(BR)DSS}$, T_J ≤ 150°C

③ Pulse width ≤ 300µs; duty cycle ≤ 2%.

④ Surface mounted on FR-4 board, t ≤ 10sec.



Fig 1. Typical Output Characteristics



Fig 2. Typical Output Characteristics



Fig 3. Typical Transfer Characteristics



Fig 4. Normalized On-Resistance Vs. Temperature



Fig 5. Typical Capacitance Vs. Drain-to-Source Voltage



Fig 6. Typical Gate Charge Vs. Gate-to-Source Voltage



Fig 7. Typical Source-Drain Diode Forward Voltage



Fig 8. Maximum Safe Operating Area



Fig 9a. Basic Gate Charge Waveform



Fig 10a. Switching Time Test Circuit



Fig 9b. Gate Charge Test Circuit



Fig 10b. Switching Time Waveforms



Fig 11. Maximum Effective Transient Thermal Impedance, Junction-to-Ambient

Peak Diode Recovery dv/dt Test Circuit





* V_{GS} = 5V for Logic Level Devices

Fig 12. For N-Channel HEXFETS

Package Outline

Micro8 Outline

Dimensions are shown in millimeters (inches)





LEAD ASSIGNMENTS





DIM	INCHES		MILLIMETERS	
	MIN	MAX	MIN	MAX
A	.036	.044	0.91	1.11
A1	.004	.008	0.10	0.20
B	.010	.014	0.25	0.36
C	.005	.007	0.13	0.18
D	.116	.120	2.95	3.05
e	.0256 BASIC		0.65 BASIC	
e1	.0128 BASIC		0.33 BASIC	
E	.116	.120	2.95	3.05
H	.188	.198	4.78	5.03
L	.016	.026	0.41	0.66
θ	0°	6°	0°	6°

RECOMMENDED FOOTPRINT



NOTES:

1 DIMENSIONING AND TOLERANCING PER ANSI Y14.5M-1982.

2 CONTROLLING DIMENSION : INCH.

3 DIMENSIONS DO NOT INCLUDE MOLD FLASH.

Part Marking Information

Micro8

EXAMPLE : THIS IS AN IRF7501



Tape & Reel Information

Micro8

Dimensions are shown in millimeters (inches)



NOTES:
1. OUTLINE CONFORMS TO EIA-481 & EIA-541.
2. CONTROLLING DIMENSION : MILLIMETER.



NOTES :
1. CONTROLLING DIMENSION : MILLIMETER.
2. OUTLINE CONFORMS TO EIA-481 & EIA-541.

International
IOR Rectifier

WORLD HEADQUARTERS: 233 Kansas St., El Segundo, California 90245, Tel: (310) 322 3331
EUROPEAN HEADQUARTERS: Hurst Green, Oxted, Surrey RH8 9BB, UK Tel: ++ 44 1883 732020
IR CANADA: 7321 Victoria Park Ave., Suite 201, Markham, Ontario L3R 2Z8, Tel: (905) 475 1897
IR GERMANY: Saalburgstrasse 157, 61350 Bad Homburg Tel: ++ 49 6172 96590
IR ITALY: Via Liguria 49, 10071 Borgaro, Torino Tel: ++ 39 11 451 0111
IR FAR EAST: K&H Bldg., 2F, 30-4 Nishi-Ikebukuro 3-Chome, Toshima-Ku, Tokyo Japan 171 Tel: 81 3 3983 0086
IR SOUTHEAST ASIA: 315 Outram Road, #10-02 Tan Boon Liat Building, Singapore 0316 Tel: 65 221 8371