

Han L32 B-HBM-DL



Image is for illustration purposes only. Please refer to product description.

Part number	09 30 132 0301
Specification	Han L32 B-HBM-DL
HARTING eCatalogue	https://b2b.harting.com/09301320301

Identification

Category	Hoods/Housings
Series of hoods/housings	Han [®] B
Type of hood/housing	Bulkhead mounted housing

Version

Locking type	Double locking lever
Han-Easy Lock [®]	Yes
Size	L32 B
Field of application	Standard hoods/housings for industrial connectors

Technical characteristics

Limiting temperature	-40 ... +125 °C
Degree of protection acc. to IEC 60529	IP65
Type rating acc. to UL 50 / UL 50E	4 4X 12

Material properties

Material (hood/housing)	Aluminium die-cast
Surface (hood/housing)	Powder-coated
Colour (hood/housing)	RAL 7037 (dust grey)
Material (seal)	NBR
Material (locking)	Polycarbonate (PC) Stainless steel



Pushing Performance

Material properties

Colour (locking) RAL 7037 (dust grey)

Material flammability class acc. to UL 94
(locking levers)

V-0

Specifications and approvals

Approvals DNV GL

CE Yes

Commercial data

Packaging size 1

Net weight 0.01 g

Country of origin China

European customs tariff number 85389099

eCl@ss 27440202 Shell for industrial connectors