



SPECIFICATIONS

FREQUENCY RANGE: DC TO 2 GHz
 ATTENUATION RANGE: 0 TO 110 dB IN 1 dB STEPS
 IMPEDANCE: 50 OHMS
 ATTENUATION ACCURACY OVERALL: ± 0.5 dB OR 3%
 VSWR: DC TO 1000 MHz, 1.3:1 MAXIMUM
 1000 TO 1500 MHz, 1.5:1 MAXIMUM
 1500 TO 2000 MHz, 1.7:1 MAXIMUM
 AVERAGE POWER: 1 WATT WITH 1000 WATTS PEAK
 OPERATING TEMPERATURE: -20°C TO 85°C



PASTERNAK ENTERPRISES, INC.

P.O BOX 16759, IRVINE, CA 92623
 PHONE (949) 261-1920 FAX (949) 261-7451

WEB ADDRESS: www.pasternack.com
 E-MAIL ADDRESS: sales@pasternack.com

COAXIAL & FIBER OPTICS

DWG TITLE

PE7033

DES.

TWO STAGE BENCH ROTARY ATTENUATOR
 FREQUENCY RANGE: DC TO 2 GHz

SIZE A

FSCM NO. 53919

CAD FILE

082102

SCALE N/A

127

NOTES:

1. UNLESS OTHERWISE SPECIFIED ALL DIMENSIONS ARE NOMINAL.
2. ALL SPECIFICATIONS ARE SUBJECT TO CHANGE WITHOUT NOTICE AT ANY TIME.