# Terminal, Compression

by ANDERSON
Catalog ID: VACL138

VERSAtile Aluminum Compression Terminal, #1 str AL/CU, 1 H, 3/8"

- Rated at 34.5 KV. UL listed for aluminum or copper conductors. CSA certified.



* Representative image

## Product Details

### General

| | |
|---|---|
| Crimp Method | VERSAtile™ (Accomodates Conventional And Anderson Tools) |
| Die Size | *See Resources / Downloads for die selection and installation instructions |
| Material | Aluminum Alloy - Tin Plated |
| Material - Body | Aluminum |
| Number of Pad Holes | 1 |
| Style | Pressed Tubing |
| UPC | 096359334033 |

### Dimensions

| | |
|---|---|
| Diameter - Pad Bolt | 0.38 in |
| Weight | 0.098 lb |

### Conductor Related

| | |
|---|---|
| Conductor Compatibility | ACSR-Swan-4-6/1;ACSR-Swanate-4-7/1;ACSR-Sparrow-2-6/1;ACSR-Sparate-2-7/1;AAC-Rose-4-7;AAC-Iris-2-7;AAC-Pansy-1-7;AAAC 6201 Alloy-Alton-48.69-6/18;AAAC 6201 Alloy-Ames-77.47-6/18 |
| Conductor Diameter (VersaCrimp) - Maximum | 0.332 in |
| Conductor Diameter (VersaCrimp) - Minimum | 0.232 in |

### Certifications and Compliance

| | |
|---|---|
| UL Listed | Yes |

### Logistics

| | |
|---|---|
| Carton Quantity | 250 EA |

**For further technical assistance, please contact us**

**Domestic Customer Service**
Hubbell Power Systems
210 N. Allen Centralia, MO 65240 USA
Phone: (573) 682-5521
Fax: (573) 682-8475
Email: hpscs@hubbell.com

**International Customer Service**
Phone: +1-573-682-5521
Fax: +1-573-682-8516
Email: hpsintlcs@hubbell.com