

## **HIRSCHMANN MOBILITY**



# CELLULAR (2G/3G)/ AM/FM (LW/MW/SW/ Band II) Screw Antenna

CR 8521 RD S Pt no. 920-445-001

- Amplifier and duplexer are integrated into base
- Detachable anti-noise rod
- Road Vehicle Roof

### Subject to alterations

### Technical data


| Dimensions        |           | 64 x 46 x 47 mm               |
|-------------------|-----------|-------------------------------|
| Rod length        |           | 400 mm                        |
| Weight            |           | ca. 116 g                     |
| Tightening torque | max.      | 4 Nm                          |
| Temperature range |           | -40 - +85°C                   |
| Protection class  |           | IP6k9k (acc. ISO 20653)       |
| AM/FM             |           |                               |
| Frequency range   | AM:       | 0,15 - 16,2 MHz               |
|                   | FM:       | 87 - 108 MHZ                  |
| Impedance         |           | 150 Ohm                       |
| Gain              | AM:       | 10 dB                         |
|                   | FM:       | 6 dB                          |
| Voltage supply    |           | 12 VDC (9 - 16 VDC)           |
| Cable type        |           | RG 174                        |
| Cable length      | AM/FM:    | 240 +10 mm                    |
|                   | Power:    | 190 +10 mm                    |
| Connector         | AM/FM:    | M 10 x 0,75 male              |
|                   | Power:    | 2,8 mm blade terminal         |
| Cellular          |           |                               |
| Frequency range   | GSM 850:  | 824 - 894 MHz                 |
|                   | GSM 900:  | 880 - 960 MHz                 |
|                   | GSM 1800: | 1710 - 1880 MHz               |
|                   | GSM 1900: | 1850 - 1990 MHz               |
|                   | UMTS:     | 920 - 2170 MHz                |
| Impedance         |           | 50 Ohm                        |
| Gain              |           | 0 dB                          |
| Return loss       |           | > 10 dB                       |
| Transmitter power | max.      | 20 W pulsed acc. GSM standard |
| Cable type        |           | RG 174                        |
| Cable length      |           | 140 +10 mm                    |
| Connector         |           | FME male                      |


### Subject to alterations


### Technical drawings


## Ø 19 0.1 mm/0.75 ±0.003 in. 240 +10mm Product marking


### Antenna diagrams Typ. VSWR











### www.te.com/hirschmann-mobility hirschmann-mobility@te.com

TE, TE Connectivity, TE connectivity (logo), and EVERY CONNECTION COUNTS are trademarks. Hirschmann is a trademark.

GSM and UMTS are trademarks.

The information given herein, including drawings, illustrations and schematics which are intended for illustration purposes only, is believed to be reliable. However, TE Connectivity makes no warranties as to its accuracy or completeness and disclaims any liability in connection with its use. TE Connectivity's obligations shall only be as set forth in TE Connectivity's Standard Terms and Conditions of Sale for this product and in no case will TE Connectivity be liable for any incidental, indirect or consequential damages arising out of the sale, resale, use or misuse of the product. Users of TE Connectivity products should make their own evaluation to determine the suitability of each such product for the specific application.

© 2019 TE Connectivity Ltd. family of companies All Rights Reserved.

02/2019