

HiPerFRED™ Epitaxial Diode with soft recovery


Preliminary data

I_{FAV} = 15 A
V_{RRM} = 600 V
t_{rr} = 25 ns

V _{RSM} V	V _{RRM} V	Type
600	600	DSEP 15-06B



TO-220 AC



A = Anode, C = Cathode, TAB = Cathode

Symbol	Conditions	Maximum Ratings	
I _{FRMS}		35	A
I _{FAVM}	T _c = 130°C; rectangular, d = 0.5	15	A
I _{FSM}	T _{vJ} = 45°C; t _p = 10 ms (50 Hz), sine	110	A
E _{AS}	T _{vJ} = 25°C; non-repetitive; I _{AS} = 1 A; L = 100 µH L = 20 mH	0.1 20	mJ mJ
I _{AR}	V _A = 1.5·V _R typ.; f = 10 kHz; repetitive	0.1	A
T _{vJ}		-55...+175	°C
T _{VJM}		175	°C
T _{stg}		-55...+150	°C
P _{tot}	T _c = 25°C	95	W
M _d	mounting torque	0.4...0.6	Nm
Weight	typical	2	g

Symbol	Conditions	Characteristic Values	
		typ.	max.
I _R ①	T _{vJ} = 25°C V _R = V _{RRM} T _{vJ} = 150°C V _R = V _{RRM}	100 0.5	µA mA
V _F ②	I _F = 15 A; T _{vJ} = 150°C T _{vJ} = 25°C	1.55 2.52	V V
R _{thJC} R _{thCH}		0.5	K/W K/W
t _{rr}	I _F = 1 A; -di/dt = 100 A/µs; V _R = 30 V; T _{vJ} = 25°C	25	30 ns
I _{RM}	V _R = 100 V; I _F = 25 A; -di _F /dt = 100 A/µs T _{vJ} = 100°C	2.6	A

Pulse test: ① Pulse Width = 5 ms, Duty Cycle < 2.0 %
② Pulse Width = 300 µs, Duty Cycle < 2.0 %

Data according to IEC 60747 and per diode unless otherwise specified

IXYS reserves the right to change limits, test conditions and dimensions.