Product data sheet
Characteristics

QOU21251200
QOU Miniature Circuit Breaker, 125A, 2P, 120/240V, 10kA, Aux Switch

Price** : 584.00 USD



Main

Product or component type	Miniature circuit-breaker
Range of product	QOU
Circuit breaker type	Standard
Options	Auxiliary switch 120 V AC 1A

Complementary

Line Rated Current	125 A
Number of Poles	2P
Interrupt Rating	10 kA 120/240 V AC 10 kA 120 V AC 5 kA 60 V DC
Electrical connection	Slotted box lugs, line side Slotted box lugs, load side
[Ue] rated operational voltage	120/240 V AC 120 V AC 60 V DC
Mounting mode	Unit mount
AWG gauge	AWG 12...AWG 2/0 aluminium/copper
Height	4.45 in (113.03 mm)
Depth	2.95 in (74.93 mm)
Width	2.25 in (57.15 mm)
Tightening torque	5.08 N.m (45 lbf.in) AWG 12...AWG 2/0)

Environment

Product certifications	UL listed CSA IEC

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Ordering and shipping details

Category	00900-QOU BREAKERS & SWITCH
Discount Schedule	DE2
Returnability	No

Offer Sustainability

Sustainable offer status	Green Premium product
EU RoHS Directive	Compliant EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS declaration Product out of China RoHS scope. Substance declaration for your information.
Environmental Disclosure	Product Environmental Profile
Circularity Profile	No need of specific recycling operations
Halogen content performance	Halogen free product

Contractual warranty

Warranty	18 months