

ONLINE DATA SHEET
www.mysick.com

Photoelectric sensors
G10, Photoelectric retro-reflective sensor, Standard optics

GL10-N1551



SICK
Sensor Intelligence.

SICK
Sensor Intelligence.

Photoelectric sensors
G10, Photoelectric retro-reflective sensor, Standard optics

Type > GL10-N1551
Part No. > 1065892





Illustration may differ

At a glance

- Long sensing ranges: up to 15 m on PL80A reflector
- PinPoint LED with bright and precise light spot
- Immunity to ambient light
- 10 V DC ... 30 V DC or 24 V AC/DC … 240 V AC/DC power supply with PNP/NPN or relay output
- With or without sensitivity adjustment
- Small housing design
- Rugged sensor housing with metal-reinforced holes for assembly
- Q-Lock assembly system for mounting and aligning the sensor within a few seconds

Your benefits

- Long sensing ranges for maximum operating reserves
- Efficient installation: the GL10 and the Q-Lock assembly system save valuable hours when mounting and commissioning multiple sensors
- Universal DC or AC/DC power supply for even greater application flexibility
- Highly reliable and durable despite optical interference or mechanical loads
- Wide range of accessories simplifies sensor integration: aids for assembly, connecting cables, and reflectors

Features

Sensor/detection principle:	Photoelectric retro-reflective sensor, Dual lens
Dimensions (W x H x D):	20 mm x 50 mm x 39 mm
Housing design (light emission):	Rectangular
Sensing range max.::	0.15 m ... 10 m, 0.15 m ... 12 m [1) 2)]
Sensing range::	0.3 m ... 8 m, 0.3 m ... 9.5 m [3) 4)]
Type of light:	Visible red light
Light source:	PinPoint LED [5)]
Wave length:	625 nm
Special features:	High functional reliability on foil-wrapped objects
Light spot size (distance):	Ø 58 mm (5 m)

1) 3) PL80A 2) 4) P250 5) Average service life: 100,000 h at T_U = +25 °C

Mechanics/electronics

Supply voltage:	10 V DC ... 30 V DC [1)]
Ripple:	± 5 Vpp [2)]


© SICK AG. Subject to change without notice.

Power consumption:	≤ 20 mA
Output type:	NPN, open collector
Switching mode:	Light switching
Output current Imax.:	≤ 100 mA
Response time:	≤ 1 ms [3]
Connection type:	Cable, 3-wire, 2 m [4]
Cable material:	PVC
Conductor cross-section:	0.14 mm²
Circuit protection::::	A, B, C, D [5] [6] [7] [8]
Protection class:	III
Weight:	90 g
Polarisation filter:	✓
Special device:	-
Enclosure rating:	IP 67
EMC:	EN 60947-5-2
Ambient operating temperature:	-30 °C ... +60 °C
Ambient storage temperature:	-40 °C ... +70 °C
UL File No.:	NRKH.E348498 & NRKH7.E348498
Further standards:	UL325 [9]
Switching frequency max.:	500 Hz [10]
Housing material:	PVC / PMMA, Plastic


[1] Limit values: operation in short-circuit protected network max. 8 A [2] May not exceed or fall below U_V tolerances [3] Signal transit time with resistive load [4] Do not bend below 0 °C [5] A = V_S connections reverse-polarity protected [6] B = inputs and output reverse-polarity protected [7] C = interference suppression [8] D = outputs overcurrent and short-circuit protected [9] Complies with the UL325 standard when used with sturdy protection hood (e.g. BEF-G10WSG, 2071960). [10] With light/dark ratio 1:1

© SICK AG. Subject to change without notice.

Dimensional drawing




Adjustments possible




© SICK AG. Subject to change without notice.

Connection diagram




Characteristic curve



|1| REF-IRF-56
|2| PL20A
|3| PL30A
|4| P250
|5| PL40A
|6| PL80A


© SICK AG. Subject to change without notice.

Sensing range diagram



|1| REF-IRF-56
|2| PL20A
|3| PL30A
|4| P250
|5| PL40A
|6| PL80A

Light spot size



© SICK AG. Subject to change without notice.

A4 4c int43

Australia
Phone +61 3 9457 0600
1800 33 48 02 – tollfree
E-Mail sales@sick.com.au

Belgium/Luxembourg
Phone +32 (0)2 466 55 66
E-Mail info@sick.be

Brasil
Phone +55 11 3215-4900
E-Mail marketing@sick.com.br

Canada
Phone +1 905 771 14 44
E-Mail information@sick.com

Česká republika
Phone +420 2 57 91 18 50
E-Mail sick@sick.cz

China
Phone +86 4000 121 000
E-Mail info.china@sick.net.cn
Phone +852-2153 6300
E-Mail ghk@sick.com.hk

Danmark
Phone +45 45 82 64 00
E-Mail sick@sick.dk

Deutschland
Phone +49 211 5301-301
E-Mail info@sick.de

España
Phone +34 93 480 31 00
E-Mail info@sick.es

France
Phone +33 1 64 62 35 00
E-Mail info@sick.fr

Great Britain
Phone +44 (0)1727 831121
E-Mail info@sick.co.uk

India
Phone +91–22–4033 8333
E-Mail info@sick-india.com

Israel
Phone +972-4-6881000
E-Mail info@sick-sensors.com

Italia
Phone +39 02 27 43 41
E-Mail info@sick.it

Japan
Phone +81 (0)3 5309 2112
E-Mail support@sick.jp

Magyarország
Phone +36 1 371 2680
E-Mail office@sick.hu

Nederland
Phone +31 (0)30 229 25 44
E-Mail info@sick.nl

Norge
Phone +47 67 81 50 00
E-Mail sick@sick.no

Österreich
Phone +43 (0)22 36 62 28 8-0
E-Mail office@sick.at

Polska
Phone +48 22 837 40 50
E-Mail info@sick.pl

România
Phone +40 356 171 120
E-Mail office@sick.ro

Russia
Phone +7-495-775-05-30
E-Mail info@sick.ru

Schweiz
Phone +41 41 619 29 39
E-Mail contact@sick.ch

Singapore
Phone +65 6744 3732
E-Mail sales.gsg@sick.com

Slovenija
Phone +386 (0)1-47 69 990
E-Mail office@sick.si

South Africa
Phone +27 11 472 3733
E-Mail info@sickautomation.co.za

South Korea
Phone +82 2 786 6321/4
E-Mail info@sickkorea.net

Suomi
Phone +358-9-25 15 800
E-Mail sick@sick.fi

Sverige
Phone +46 10 110 10 00
E-Mail info@sick.se

Taiwan
Phone +886 2 2375-6288
E-Mail sales@sick.com.tw

Türkiye
Phone +90 (216) 528 50 00
E-Mail info@sick.com.tr

United Arab Emirates
Phone +971 (0) 4 88 65 878
E-Mail info@sick.ae

USA/México
Phone +1(952) 941-6780
1 (800) 325-7425 – tollfree
E-Mail info@sickusa.com

More representatives and agencies
at **www.sick.com**

SICK
Sensor Intelligence.