


Sales Region	Worldwide (except Japan)
Series	ALE
Model	ALE-Rack mount
Status	 Production
Option	Positive polarity
Option Lineup	Please refer to here.
Accessories	Please refer to the catalog



Electrical Characteristics

Input	3-phase
Input Voltage Range[AC]	180 to 264VAC
Input Frequency Range	47 to 63Hz
Rated Output Voltage[DC]	30000Vdc
Output Voltage Range[DC]	0 to 30000V
Average Capacitor Charging Power	4000J/sec
Peak Capacitor Charging Power	5000J/sec
Charge Current	333mA
Continuous DC Current	130mA
Continuous DC Power	4kW
Polarity	Positive
Power Factor	0.85
Efficiency	85% Typ.

Package Type & Size

Package / Mounting	Rack mount
Width(W)	482mm Nom. (18.98in Nom.)
Height(H)	178mm Nom. (7.01in Nom.)
Depth(D)	432mm Nom. (17.01in Nom.)
Weight	30kg Typ. (66.1lbs Typ.)

Other

Operating Temp. Range	-20 to 45°C
Storage Temp. Range	-40 to 85°C
Cooling	Forced air
Safety Standard(Certified)	
Safety Standard(Conformed)	

Remarks This page only shows representative characteristics. Please refer to the technical data for detailed specifications and conditions.