

Customer Information Sheet

DRAWING No.: P1113XX3

SHEET 2 OF 2

IF IN DOUBT - ASK

(C)

NOT TO SCALE

THIRD ANGLE PROJECTION

ALL DIMENSIONS IN mm

SPECIFICATIONS:

MATERIAL:

PLUNGER = P1113CA3, P1113CV3 = BRASS
P1113SS3 = HIGH CARBON STEEL

BARREL = BRASS

SPRING = SPRING STEEL

FINISH:

PLUNGER:

P1113CA3, P1113CV3 = 0.25µ MIN GOLD
OVER 2.0µ MIN NICKEL

P1113SS3 = 2.0µ MIN NICKEL OVER

BARREL = 0.25µ MIN GOLD OVER 0.5µ COPPER

SPRING = GOLD PLATED

ELECTRICAL:

CURRENT RATING = 2A MAX

CONTACT RESISTANCE = 50mΩ MAX

MECHANICAL:

DURABILITY = 100,000 CYCLES

FULL TRAVEL = 3.18mm


SPRING FORCE:

FULL TRAVEL = 0.75N ±0.25N (76.5g ±33%)

2.20mm TRAVEL = 0.54N ±0.11N (55g ±20%)

ENVIRONMENTAL:


TEMPERATURE RANGE = -40°C TO +180°C




NOTES:

1. RECOMMENDED CLEARANCE HOLE SIZE = $\varnothing 2.20 \pm 0.05$ mm.
RECOMMENDED INTERFERENCE HOLE SIZE = $\varnothing 2.00$ mm.
2. SUITABLE FOR A MINIMUM DISTANCE BETWEEN CENTRES OF 3.00mm.
3. THIS PART IS SIMILAR TO P1113XX2 APART FROM POWER RATING THAT WAS 5A MAX AND MATERIAL / FINISH OF SPRING AND PLUNGER VARIANT P1113SS3.


PROBE HEAD VARIANTS



CONCAVE RADIUS HEAD
P1113CA3



CONVEX HEAD
P1113SS3



CONVEX RADIUS HEAD
P1113CV3

ORDER CODE:

P1113XX3

PROBE HEAD
VARIANT (SEE BELOW)

SB	6	08.11.17	20842
NAME	ISS.	DATE	C/NOTE
APPROVED:		S.BENNETT	
CHECKED:		M.PLESTED	
DRAWN:		M. G. PLESTED	
CUSTOMER REF.:			
ASSEMBLY DRG:			

HARWIN

www.harwin.com
technical@harwin.com

THIS DRAWING AND ANY INFORMATION OR DESCRIPTIVE MATTER SET OUT HEREON ARE CONFIDENTIAL AND COPYRIGHT PROPERTY OF THE HARWIN GROUP AND MUST NOT BE DISCLOSED, LOANED, COPIED OR USED FOR MANUFACTURING, TENDERING OR FOR ANY OTHER PURPOSE WITHOUT THEIR WRITTEN PERMISSION.

TOLERANCES

X. = ±1mm
X.X = ±0.50mm
X.XX = ±0.10mm
X.XXX = ±0.01mm

ANGLES = ±5°

UNLESS STATED

MATERIAL:

SEE ABOVE

FINISH: SEE ABOVE

S/AREA: mm²

TITLE:

3.00mm MIN. CENTRE
ONE-PIECE SPRING PROBE

DRAWING NUMBER:

P1113XX3

SHT
2 OF 2