
Three Phase Rectifier Bridges

PSD 50

I_{dAVM} = 80 A
V_{RRM} = 800-1800 V

Preliminary Data Sheet

V_{RSM} V	V_{RRM} V	Type
800	800	PSD 50/08
1200	1200	PSD 50/12
1400	1400	PSD 50/14
1600	1600	PSD 50/16
1800	1800	PSD 50/18





Symbol	Test Conditions			Maximum Ratings	
I_{dAVM}	T_C = 110°C, module			80	A
I_{FSM}	T_{VJ} = 45°C	t = 10 ms	(50 Hz), sine	675	A
	V_R = 0	t = 8.3 ms	(60 Hz), sine	730	A
	T_{VJ} = T_{VJM}	t = 10 ms	(50 Hz), sine	660	A
	V_R = 0	t = 8.3 ms	(60 Hz), sine	600	A
$\int i^2 dt$	T_{VJ} = 45°C	t = 10 ms	(50 Hz), sine	2550	$A^2 s$
	V_R = 0	t = 8.3 ms	(60 Hz), sine	2550	$A^2 s$
	T_{VJ} = T_{VJM}	t = 10 ms	(50 Hz), sine	2025	$A^2 s$
	V_R = 0	t = 8.3 ms	(60 Hz), sine	2025	$A^2 s$
T_{VJ}				-40 ... + 150	°C
T_{VJM}				150	°C
T_{stg}				-40 ... + 125	°C
V_{ISOL}	50/60 HZ, RMS	t = 1 min		2500	V ~
	I_{ISOL} ≤ 1 mA	t = 1 s		3000	V ~
M_d	Mounting torque		(M5)	5	Nm
	Terminal connection torque		(M5)	5	Nm
Weight	typ.			220	g


Symbol	Test Conditions			Characteristic Value	
I_R	V_R = V_{RRM}	T_{VJ} = 25°C	≤	0.3	mA
	V_R = V_{RRM}	T_{VJ} = T_{VJM}	≤	5	mA
V_F	I_F = 150 A	T_{VJ} = 25°C	≤	1.6	V
V_{TO}	For power-loss calculations only			0.8	V
r_T	T_{VJ} = T_{VJM}			5	mΩ
R_{thJC}	per diode; DC current			1.1	K/W
	per module			0.183	K/W
R_{thJK}	per diode; DC current			1.52	K/W
	per module			0.253	K/W
d_S	Creeping distance on surface			8.0	mm
d_A	Creeping distance in air			4.5	mm
a	Max. allowable acceleration			50	m/s^2

Features
- Package with screw terminals
- Isolation voltage 3000 V~
- Planar glasspassivated chips
- Blocking voltage up to 1800 V
- Low forward voltage drop
- UL registered E 148688

Applications
- Supplies for DC power equipment
- Input rectifiers for PWM inverter
- Battery DC power supplies
- Field supply for DC motors

Advantages
- Easy to mount with two screws
- Space and weight savings
- Improved temperature and power cycling capability

Package, style and outline
Dimensions in mm (1mm = 0.0394“)



POWERSEM GmbH, Walpersdorfer Str. 53
91126 D- Schwabach
Phone: 09122 - 9764-0 Fax.: 09122 - 9764-20

© 2005 POWERSEM reserves the right to change limits, test conditions and dimensions