

IGBT Module-H Bridge　150A, 600V　PBMB150E6

□ 回路図 : *CIRCUIT*



□ 外形寸法図 : *OUTLINE DRAWING*



Dimension: [mm]

□ 最大定格 : *MAXIMUM RATINGS* (T_C=25℃)

Item		Symbol	Rated Value	Unit
コレクタ・エミッタ間電圧 Collector-Emitter Voltage		V_{CES}	600	V
ゲート・エミッタ間電圧 Gate-Emitter Voltage		V_{GES}	±20	V
コレクタ電流 Collector Current	DC	I_C	150	A
	1ms	I_{CP}	300	
コレクタ損失 Collector Power Dissipation		P_C	560	W
接合温度 Junction Temperature Range		T_j	−40～+150	℃
保存温度 Storage Temperature Range		T_{stg}	−40～+125	℃
絶縁耐圧(Terminal to Base AC, 1minute) Isolation Voltage		V_{ISO}	2,500	$V_{(RMS)}$
締め付けトルク Mounting Torque	Module Base to Heatsink	F_{tor}	2	N・m (kgf・cm)
	Busbar to Main Terminal		2 (20.4)	

□ 電気的特性 : *ELECTRICAL CHARACTERISTICS* (T_C=25℃)

Characteristic		Symbol	Test Condition	Min.	Typ.	Max.	Unit
コレクタ遮断電流 Collector-Emitter Cut-Off Current		I_{CES}	V_{CE}= 600V, V_{GE}= 0V	−	−	1.0	mA
ゲート漏れ電流 Gate-Emitter Leakage Current		I_{GES}	V_{GE}= ±20V, V_{CE}= 0V	−	−	1.0	μA
コレクタ・エミッタ間飽和電圧 Collector-Emitter Saturation Voltage		$V_{CE(sat)}$	I_C= 150A, V_{GE}= 15V	−	2.1	2.6	V
ゲートしきい値電圧 Gate-Emitter Threshold Voltage		$V_{GE(th)}$	V_{CE}= 5V, I_C= 150mA	4.0	−	8.0	V
入力容量 Input Capacitance		C_{ies}	V_{CE}= 10V, V_{GE}= 0V, f= 1MHz	−	5,000	−	pF
スイッチング時間 Switching Time	上昇時間 Rise Time	t_r	V_{CC}= 300V R_L= 2.0Ω R_G= 5.1Ω V_{GE}= ±15V	−	0.15	0.30	μs
	ターンオン時間 Turn-on Time	t_{on}		−	0.25	0.40	
	下降時間 Fall Time	t_f		−	0.10	0.35	
	ターンオフ時間 Turn-off Time	t_{off}		−	0.35	0.70	

□フリーホイーリングダイオードの特性: *FREE WHEELING DIODE RATINGS & CHARACTERISTICS* (T_C=25℃)

Item		Symbol	Rated Value	Unit
順電流 Forward Current	DC	I_F	150	A
	1ms	I_{FM}	300	

Characteristic	Symbol	Test Condition	Min.	Typ.	Max.	Unit
順電圧 Peak Forward Voltage	V_F	I_F= 150A, V_{GE}= 0V	−	1.9	2.4	V
逆回復時間 Reverse Recovery Time	t_{rr}	I_F= 150A, V_{GE}= −10V di/dt= 300A/μs	−	0.15	0.25	μs

□ 熱的特性 : *THERMAL CHARACTERISTICS*

Characteristic		Symbol	Test Condition	Min.	Typ.	Max.	Unit
熱抵抗 Thermal Impedance	IGBT	Rth(j-c)	Junction to Case (Tc測定点チップ直下)	−	−	0.22	℃/W
	Diode			−	−	0.45	

ＰＢＭＢ１５０Ｅ６

Fig.1- Output Characteristics (Typical)




Fig.2- Output Characteristics (Typical)




Fig.3- Collector to Emitter On Voltage vs. Gate to Emitter Voltage (Typical)




Fig.4- Collector to Emitter On Voltage vs. Gate to Emitter Voltage (Typical)




Fig.5- Gate Charge vs. Collector to Emitter Voltage (Typical)





Fig.6- Capacitance vs. Collector to Emitter Voltage (Typical)



ＰＢＭＢ１５０Ｅ６

Fig.7- Collector Current vs. Switching Time (Typical)




Fig.8- Series Gate Impedance vs. Switching Time (Typical)




Fig.9- Collector Current vs. Switching Time




Fig.10- Series Gate Impedance vs. Switching Time




Fig.11- Collector Current vs. Switching Loss





Fig.12- Series Gate Impedance vs. Switching Loss



ＰＢＭＢ１５０Ｅ６

Fig.13- Forward Characteristics of Free Wheeling Diode (Typical)




Fig.14- Reverse Recovery Characteristics (Typical)




Fig.15- Reverse Bias Safe Operating Area




Fig.16- Transient Thermal Impedance

