FAIRCHILD SEMICONDUCTOR®

April 2007

74VHC373
Octal D-Type Latch with 3-STATE Outputs

Features

- High Speed: t_{PD} = 5.0ns (typ) @ V_{CC} = 5V
- High Noise Immunity: $V_{NIH} = V_{NIL}$ = 28% V_{CC} (Min.)
- Power Down Protection is provided on all inputs
- Low Noise: V_{OLP} = 0.6V (Typ.)
- Low Power Dissipation: I_{CC} = 4μA (Max) @ T_A = 25°C
- Pin and Function Compatible with 74HC373

General Description

The VHC373 is an advanced high speed CMOS octal D-type latch with 3-STATE output fabricated with silicon gate CMOS technology. It achieves the high speed operation similar to equivalent Bipolar Schottky TTL while maintaining the CMOS low power dissipation. This 8-bit D-type latch is controlled by a latch enable input (LE) and an output enable input ($\overline{OE}$). The latches appear transparent to data when latch enable (LE) is HIGH. When LE is LOW, the data that meets the setup time is LATCHED. When the $\overline{OE}$ input is HIGH, the eight outputs are in a high impedance state.


An input protection circuit ensures that 0V to 7V can be applied to the input pins without regard to the supply voltage. This device can be used to interface 5V to 3V systems and two supply systems such as battery back up. This circuit prevents device destruction due to mismatched supply and input voltages.

Ordering Information

Order Number	Package Number	Package Description
74VHC373M	M20B	20-Lead Small Outline Integrated Circuit (SOIC), JEDEC MS-013, 0.300" Wide
74VHC373SJ	M20D	20-Lead Small Outline Package (SOP), EIAJ TYPE II, 5.3mm Wide
74VHC373MTC	MTC20	20-Lead Thin Shrink Small Outline Package (TSSOP), JEDEC MO-153, 4.4mm Wide

Surface mount packages are also available on Tape and Reel. Specify by appending the suffix letter “X” to the ordering number. Pb-Free package per JEDEC J-STD-020B.

Connection Diagram




Pin Descriptions

Pin Names	Description
D_0–D_7	Data Inputs
LE	Latch Enable Input
$\overline{OE}$	Output Enable Input
O_0–O_7	3-STATE Outputs

©1993 Fairchild Semiconductor Corporation

Logic Symbol

IEEE/IEC



Functional Description

The VHC373 contains eight D-type latches with 3-STATE standard outputs. When the Latch Enable (LE) input is HIGH, data on the D_n inputs enters the latches. In this condition the latches are transparent, i.e., a latch output will change state each time its D input changes. When LE is LOW, the latches store the information that was present on the D inputs a setup time preceding the HIGH-to-LOW transition of LE. The 3-STATE standard outputs are controlled by the Output Enable ($\overline{OE}$) input. When $\overline{OE}$ is LOW, the standard outputs are in the 2-state mode. When $\overline{OE}$ is HIGH, the standard outputs are in the high impedance mode but this does not interfere with entering new data into the latches.

Truth Table

Inputs			Outputs
LE	**$\overline{OE}$**	**D_n**	**O_n**
X	H	X	Z
H	L	L	L
H	L	H	H
L	L	X	O_0

H = HIGH Voltage Level


L = LOW Voltage Level

Z = High Impedance

X = Immaterial

O_0 = Previous O_0 before HIGH-to-LOW transition of Latch Enable

Logic Diagram



Please note that this diagram is provided only for the understanding of logic operations and should not be used to estimate propagation delays.

Figure 1.

©1993 Fairchild Semiconductor Corporation

Absolute Maximum Ratings

Stresses exceeding the absolute maximum ratings may damage the device. The device may not function or be operable above the recommended operating conditions and stressing the parts to these levels is not recommended. In addition, extended exposure to stresses above the recommended operating conditions may affect device reliability. The absolute maximum ratings are stress ratings only.

Symbol	Parameter	Rating
V_{CC}	Supply Voltage	–0.5V to +7.0V
V_{IN}	DC Input Voltage	–0.5V to +7.0V
V_{OUT}	DC Output Voltage	–0.5V to V_{CC} + 0.5V
I_{IK}	Input Diode Current	–20mA
I_{OK}	Output Diode Current	±20mA
I_{OUT}	DC Output Current	±25mA
I_{CC}	DC V_{CC}/GND Current	±75mA
T_{STG}	Storage Temperature	–65°C to +150°C
T_L	Lead Temperature (Soldering, 10 seconds)	260°C

Recommended Operating Conditions(1)

The Recommended Operating Conditions table defines the conditions for actual device operation. Recommended operating conditions are specified to ensure optimal performance to the datasheet specifications. Fairchild does not recommend exceeding them or designing to absolute maximum ratings.

Symbol	Parameter	Rating
V_{CC}	Supply Voltage	2.0V to +5.5V
V_{IN}	Input Voltage	0V to +5.5V
V_{OUT}	Output Voltage	0V to V_{CC}
T_{OPR}	Operating Temperature	–40°C to +85°C
t_r, t_f	Input Rise and Fall Time,	
	V_{CC} = 3.3V ± 0.3V	0ns/V ~ 100ns/V
	V_{CC} = 5.0V ± 0.5V	0ns/V ~ 20ns/V

Note:

1. Unused inputs must be held HIGH or LOW. They may not float.

©1993 Fairchild Semiconductor Corporation

DC Electrical Characteristics

Symbol	Parameter	V_{CC} (V)	Conditions		T_A = 25°C Min.	T_A = 25°C Typ.	T_A = 25°C Max.	T_A = –40°C to +85°C Min.	T_A = –40°C to +85°C Max.	Units
V_{IH}	HIGH Level Input Voltage	2.0			1.50			1.50		V
		3.0–5.5			0.7 x V_{CC}			0.7 x V_{CC}		
V_{IL}	LOW Level Input Voltage	2.0					0.50		0.50	V
		3.0–5.5					0.3 x V_{CC}		0.3 x V_{CC}	
V_{OH}	HIGH Level Output Voltage	2.0	$V_{IN} = V_{IH}$ or V_{IL}	I_{OH} = –50µA	1.9	2.0		1.9		V
		3.0			2.9	3.0		2.9		
		4.5			4.4	4.5		4.4		
		3.0		I_{OH} = –4mA	2.58			2.48		
		4.5		I_{OH} = –8mA	3.94			3.80		
V_{OL}	LOW Level Output Voltage	2.0	$V_{IN} = V_{IH}$ or V_{IL}	I_{OL} = 50µA		0.0	0.1		0.1	V
		3.0				0.0	0.1		0.1	
		4.5				0.0	0.1		0.1	
		3.0		I_{OL} = 4mA			0.36		0.44	
		4.5		I_{OL} = 8mA			0.36		0.44	
I_{OZ}	3-STATE Output Off-State Current	5.5	$V_{IN} = V_{IH}$ or V_{IL}; $V_{OUT} = V_{CC}$ or GND				±0.25		±2.5	µA
I_{IN}	Input Leakage Current	0–5.5	V_{IN} = 5.5V or GND				±0.1		±1.0	µA
I_{CC}	Quiescent Supply Current	5.5	$V_{IN} = V_{CC}$ or GND				4.0		40.0	µA

Noise Characteristics

Symbol	Parameter	V_{CC} (V)	Conditions	T_A = 25°C Typ.	T_A = 25°C Limits	Units
V_{OLP}[2]	Quiet Output Maximum Dynamic V_{OL}	5.0	C_L = 50pF	0.6	0.9	V
V_{OLV}[2]	Quiet Output Minimum Dynamic V_{OL}	5.0	C_L = 50pF	–0.6	–0.9	V
V_{IHD}[2]	Minimum HIGH Level Dynamic Input Voltage	5.0	C_L = 50pF		3.5	V
V_{ILD}[2]	Maximum LOW Level Dynamic Input Voltage	5.0	C_L = 50pF		1.5	V

Note:

2. Parameter guaranteed by design.

©1993 Fairchild Semiconductor Corporation

AC Electrical Characteristics

Symbol	Parameter	V_{CC} (V)	Conditions		T_A = +25°C			T_A = –40°C to +85°C		Units
					Min.	Typ.	Max.	Min.	Max.	
t_{PLH}, t_{PHL}	Propagation Delay Time (LE to O_n)	3.3 ± 0.3		C_L = 15pF		7.0	11.0	1.0	13.0	ns
				C_L = 50pF		9.5	14.5	1.0	16.5	
		5.0 ± 0.5		C_L = 15pF		4.9	7.2	1.0	8.5	ns
				C_L = 50pF		6.4	9.2	1.0	10.5	
t_{PLH}, t_{PHL}	Propagation Delay Time (D to O_n)	3.3 ± 0.3		C_L = 15pF		7.3	11.4	1.0	13.5	ns
				C_L = 50pF		9.8	14.9	1.0	17.0	
		5.0 ± 0.5		C_L = 15pF		5.0	7.2	1.0	8.5	
				C_L = 50pF		6.5	9.2	1.0	10.5	
t_{PZL}, t_{PZH}	3-STATE Output Enable Time	3.3 ± 0.3	R_L = 1kΩ	C_L = 15pF		7.3	11.4	1.0	13.5	ns
				C_L = 50pF		9.8	14.9	1.0	17.0	
		5.0 ± 0.5		C_L = 15pF		5.5	8.1	1.0	9.5	ns
				C_L = 50pF		7.0	10.1	1.0	11.5	
t_{PLZ}, t_{PHZ}	3-STATE Output Disable Time	3.3 ± 0.3	R_L = 1kΩ	C_L = 50pF		9.5	13.2	1.0	15.0	ns
		5.0 ± 0.5		C_L = 50pF		6.5	9.2	1.0	10.5	
t_{OSLH}, t_{OSHL}	Output to Output Skew	3.3 ± 0.3	(3)	C_L = 50pF			1.5		1.5	ns
		5.0 ± 0.5		C_L = 50pF			1.0		1.0	
C_{IN}	Input Capacitance		V_{CC} = Open			4	10		10	pF
C_{OUT}	Output Capacitance		V_{CC} = 5.0V			6				pF
C_{PD}	Power Dissipation Capacitance		(4)			27				pF

Notes:

3. Parameter guaranteed by design. $t_{OSLH} = |t_{PLH\ max} - t_{PLH\ min}|$; $t_{OSHL} = |t_{PHL\ max} - t_{PHL}\ min|$
4. C_{PD} is defined as the value of the internal equivalent capacitance which is calculated from the operating current consumption without load. Average operating current can be obtained by the equation: I_{CC} (opr.) = $C_{PD} \cdot V_{CC} \cdot f_{IN} + I_{CC}/8$ (per Latch). The total C_{PD} when n pcs. of the Latch operates can be calculated by the equation: C_{PD}(total) = 14 + 13n.

AC Operating Requirements

Symbol	Parameter	V_{CC} (V)	T_A = +25°C			T_A = –40°C to +85°C		Units
			Min.	Typ.	Max.	Min.	Max.	
t_W(H)	Minimum Pulse Width (LE)	3.3 ± 0.3	5.0			5.0		ns
		5.0 ± 0.5	5.0			5.0		
t_S	Minimum Set-Up Time	3.3 ± 0.3	4.0			4.0		ns
		5.0 ± 0.5	4.0			4.0		
t_H	Minimum Hold Time	3.3 ± 0.3	1.0			1.0		ns
		5.0 ± 0.5	1.0			1.0		

©1993 Fairchild Semiconductor Corporation

Physical Dimensions

Dimensions are in inches (millimeters) unless otherwise noted.





Figure 2. 20-Lead Small Outline Integrated Circuit (SOIC), JEDEC MS-013, 0.300" Wide
Package Number M20B

Physical Dimensions (Continued)

Dimensions are in millimeters unless otherwise noted.



NOTES:


A. CONFORMS TO EIAJ EDR-7320 REGISTRATION, ESTABLISHED IN DECEMBER, 1998.
B. DIMENSIONS ARE IN MILLIMETERS.
C. DIMENSIONS ARE EXCLUSIVE OF BURRS, MOLD FLASH, AND TIE BAR EXTRUSIONS.

M20DREVC

Figure 3. 20-Lead Small Outline Package (SOP), EIAJ TYPE II, 5.3mm Wide
Package Number M20D

Physical Dimensions (Continued)

Dimensions are in millimeters unless otherwise noted.



DIMENSIONS ARE IN MILLIMETERS

NOTES:

A. CONFORMS TO JEDEC REGISTRATION MO-153, VARIATION AC, REF NOTE 6, DATE 7/93.

B. DIMENSIONS ARE IN MILLIMETERS.

C. DIMENSIONS ARE EXCLUSIVE OF BURRS, MOLDS FLASH, AND TIE BAR EXTRUSIONS.

D. DIMENSIONS AND TOLERANCES PER ANSI Y14.5M, 1982.

MTC20REVD1

Figure 4. 20-Lead Thin Shrink Small Outline Package (TSSOP), JEDEC MO-153, 4.4mm Wide
Package Number MTC20

FAIRCHILD
SEMICONDUCTOR®

TRADEMARKS

The following are registered and unregistered trademarks Fairchild Semiconductor owns or is authorized to use and is not intended to be an exhaustive list of all such trademarks.

ACEx®
Across the board. Around the world.™
ActiveArray™
Bottomless™
Build it Now™
CoolFET™
CROSSVOLT™
CTL™
Current Transfer Logic™
DOME™
E²CMOS™
EcoSPARK®
EnSigna™
FACT Quiet Series™
FACT®
FAST®
FASTr™
FPS™
FRFET®
GlobalOptoisolator™
GTO™
HiSeC™
i-Lo™
ImpliedDisconnect™
IntelliMAX™
ISOPLANAR™
MICROCOUPLER™
MicroPak™
MICROWIRE™
MSX™
MSXPro™
OCX™
OCXPro™
OPTOLOGIC®
OPTOPLANAR®
PACMAN™
POP™
Power220®
Power247®
PowerEdge™
PowerSaver™
PowerTrench®
Programmable Active Droop™
QFET®
QS™
QT Optoelectronics™
Quiet Series™
RapidConfigure™
RapidConnect™
ScalarPump™
SMART START™
SPM®
STEALTH™
SuperFET™
SuperSOT™-3
SuperSOT™-6
SuperSOT™-8
SyncFET™
TCM™
The Power Franchise®
™
TinyBoost™
TinyBuck™
TinyLogic®
TINYOPTO™
TinyPower™
TinyWire™
TruTranslation™
μSerDes™
UHC®
UniFET™
VCX™
Wire™

DISCLAIMER

FAIRCHILD SEMICONDUCTOR RESERVES THE RIGHT TO MAKE CHANGES WITHOUT FURTHER NOTICE TO ANY PRODUCTS HEREIN TO IMPROVE RELIABILITY, FUNCTION OR DESIGN. FAIRCHILD DOES NOT ASSUME ANY LIABILITY ARISING OUT OF THE APPLICATION OR USE OF ANY PRODUCT OR CIRCUIT DESCRIBED HEREIN; NEITHER DOES IT CONVEY ANY LICENSE UNDER ITS PATENT RIGHTS, NOR THE RIGHTS OF OTHERS. THESE SPECIFICATIONS DO NOT EXPAND THE TERMS OF FAIRCHILD'S WORLDWIDE TERMS AND CONDITIONS, SPECIFICALLY THE WARRANTY THEREIN, WHICH COVERS THESE PRODUCTS.

LIFE SUPPORT POLICY

FAIRCHILD'S PRODUCTS ARE NOT AUTHORIZED FOR USE AS CRITICAL COMPONENTS IN LIFE SUPPORT DEVICES OR SYSTEMS WITHOUT THE EXPRESS WRITTEN APPROVAL OF FAIRCHILD SEMICONDUCTOR CORPORATION.

As used herein:

1. Life support devices or systems are devices or systems which, (a) are intended for surgical implant into the body or (b) support or sustain life, and (c) whose failure to perform when properly used in accordance with instructions for use provided in the labeling, can be reasonably expected to result in a significant injury of the user.
2. A critical component in any component of a life support, device, or system whose failure to perform can be reasonably expected to cause the failure of the life support device or system, or to affect its safety or effectiveness.

PRODUCT STATUS DEFINITIONS

Definition of Terms

Datasheet Identification	Product Status	Definition
Advance Information	Formative or In Design	This datasheet contains the design specifications for product development. Specifications may change in any manner without notice.
Preliminary	First Production	This datasheet contains preliminary data; supplementary data will be published at a later date. Fairchild Semiconductor reserves the right to make changes at any time without notice to improve design.
No Identification Needed	Full Production	This datasheet contains final specifications. Fairchild Semiconductor reserves the right to make changes at any time without notice to improve design.
Obsolete	Not In Production	This datasheet contains specifications on a product that has been discontinued by Fairchild Semiconductor. The datasheet is printed for reference information only.

Rev. I24

©1993 Fairchild Semiconductor Corporation