

Han 3A HTE, plastic (7-12mm)



Image is for illustration purposes only. Please refer to product description.

| | |
|--------------------|---|
| Part number | 19 20 003 0415 |
| Specification | Han 3A HTE, plastic (7-12mm) |
| HARTING eCatalogue | https://b2b.harting.com/19200030415 |

Identification

| | |
|-----------------------------|-----------------------------|
| Category | Hoods/Housings |
| Series of hoods/housings | Han A [®] |
| Type of hood/housing | Hood |
| Description of hood/housing | With integrated cable gland |

Version

| | |
|----------------------|---|
| Locking type | Single locking lever |
| Size | 3 A |
| Version | Top entry |
| Cable entry | 1x Integrated |
| Field of application | Standard Hoods/housings for industrial applications |

Technical characteristics

| | |
|--|---|
| Limiting temperature | -40 ... +125 °C |
| Degree of protection acc. to IEC 60529 | IP44 IP67 with seal screw 09 20 000 9918 |
| Type rating acc. to UL 50 / UL 50E | 4 4X 12 |
| Cable diameter | 7 ... 12 mm |

Material properties

| | |
|-------------------------|------------------------|
| Material (hood/housing) | Polycarbonate (PC) |
| Colour (hood/housing) | RAL 7032 (pebble grey) |



Pushing Performance

Material properties

| | |
|---|-----------|
| Material flammability class acc. to UL 94 | V-0 |
| RoHS | compliant |
| ELV status | compliant |
| China RoHS | e |
| REACH Annex XVII substances | No |
| REACH ANNEX XIV substances | No |
| REACH SVHC substances | No |

Specifications and approvals

| | |
|-----------|--|
| Approvals | DNV GL |
| UL / CSA | UL 1977 ECBT2.E235076 CSA-C22.2 No. 182.3 ECBT8.E235076 |
| CE | Yes |

Commercial data

| | |
|--------------------------------|--|
| Packaging size | 10 |
| Net weight | 20 g |
| Country of origin | Germany |
| European customs tariff number | 85389099 |
| eCl@ss | 27440202 Shell for industrial connectors |