B70SR24125A/B/C/D

24V Output DC/DC Converter, Box Type Package



FEATURES

- Wide input voltage range, 36~106V
- 300W Output
- Full Load Efficiency up to 92.5% @48Vin; 92.5%@72Vin
- Parallel Connection of multiple units
- Box type package with metal base plate
- Package Dimension: 190.0x76.0x43.5mm (7.48”x2.99”x1.71”)
- Operating Temperature Range - 40°C to +85°C
- Intergrated fuseholder (option)
- Input Reverse Polarity Protection
- Minimized Inrush current
- Input UVLO, Output OCL, Short circuit protection, OVP, OTP
- Enable on/off (option)
- 1500Vac Isolation
- IP67 Protection
- RoHs Compliant
- ISO 9001, ISO 14001 certified manufacturing facility
- UL60950-1
- CE Mark
- EMC compatible: EN12895, CISPR11 ClassB
- Electrical transient conduction: ISO7637-2

The B70SR24125, a wide input voltage range of 36~106V, and single isolated output converter, is the latest product offering from a world leader in power systems technology and manufacturing — Delta Electronics, Inc. Such box type DCDC converter can provide 300W, 24V regulated DC output voltage with full load efficiency up to 92.5% @72Vin; The B70SR24125 offers input UVLO, output over current limit, short circuit, output over voltage, over temperature, and input reverse polarity protections, It has an option for intergrated fuse holder and enable on/off function. It also has parallel function; and allows a wide operating temperature range of –40°C to +85°C. With creative design technology and optimization of component placement, this converter possess outstanding electrical and thermal performance, as well as high reliability under extremely harsh operating conditions. The B70SR24125 meets IP67 protecion (not include the connector and fuseholder).

Input Characteristics

Item	Condition	Min.	Typ.	Max.	Unit
Continuous Input Voltage		36	72	106	VDC
Max Input voltage	10 minutes, normal operating			126	VDC
Input Under-Voltage Lockout, Turn-On Voltage Threshold		33	34	35	VDC
Input Under-Voltage Lockout, Turn-Off Voltage Threshold		31	32	22	VDC
Lockout Hysteresis Voltage		1	2	3	VDC
Enable logic turn on		20			VDC
Enable logic turn off				5	VDC
Max Input Current	Vin=36V, 100% Load		9.3	10	A
Reflected input ripple current	Vin=72V, Vpp			0.2	A
No-Load Input Current	Vin=48V		30	50	mA
	Vin=72V, 80V		22	40	mA
Off converter input current	Vin=72V		8	15	mA
Max Reverse Polarity Input Voltage				106	VDC
Max Inrush current				10	A

Output Characteristics

Item	Conditions	Min.	Typ.	Max.	Unit
Operating Output Current Range		0		12.5	A
Output Voltage Set Point	Io=0	24.7	25	25.3	V
	Io=12.5A	24.2	24.5	24.8	V
Output Voltage Ripple and Noise,	Vin=48V, Io=12.5A, peak to peak, 20MHz bandwidth		100	150	mV
	RMS		25	40	mV
	Vin=72V, 80V, Io=12.5A, peak to peak, 20MHz bandwidth		130	200	mV
	RMS		35	50	mV
Output Current Limit		13	14.5	16	A
Short current	Vin=72V, Auto restart, RMS value		7		A
Current share accuracy	12.5A for each module		8	12	%
Start-up time from input			700	1000	mS
Start-up time from enable			400	600	mS
Rise time			130	200	mS
Output Voltage Protection		27	29	31	V
Output Voltage Current Transient	Positive voltage step, 9.375A to 6.25A load dynamic, 0.1A/us slew rate		100	200	mV
	Nagetive voltage step, 6.25A to 9.375A load dynamic, 0.1A/us slew rate		100	200	mV
Maximum Output Capacitance	ESR>10mohm			5000	μF
Output overshoot				3	%
Efficiency @ 100% Load	Vin=48V	90.5	92.5		%
Efficiency @ 100% Load	Vin=72V	90.5	92.5		%
Efficiency @ 100% Load	Vin=80V	90.5	92.5		%
Efficiency @ 60% Load	Vin=48V	91.0	93.0		%
Efficiency @ 60% Load	Vin=72V	91.0	93.0		%
Efficiency @ 60% Load	Vin=80V	91.0	93.0		%

General Characteristics

Item	Conditions	Min.	Typ.	Max.	Unit
Isolation Voltage,	Input to Output, Input to Case			1500	VAC
	Ouput to Case			500	VAC
Isolation Resistance, Input to Output		10			MΩ
Isolation Capacitance, Input to Output			5000		pF
Switching Frequency			175		KHz
MTBF	Ta=25ºC, 80%load		4.5		Mhours
Weight			900		g

Environmental Specifications

Parameter	Conditions	Min.		Max.	Unit
Storage Temperature Range		-40		+125	℃
Operating Temperature Range	Ambient Temperature	-40		+85	℃
Maximum permitted meta plate temperature	Vin=72V, Io=10A, Refer to figure19			97	℃
Over Temperature Protection	NTC Temperature		118		℃
Humidity (non condensing)				95	% rel. H
Water Protection Level	Without connector&fuseholder	IP67			
Vibration	IEC 60068-2-6	10G/15~200HZ/3 PLANES			
Shock	IEC 60068-2-27	50G 3 PLANES			
Emission	EN12895	30-1000MHz 34-45dBuV/m			
Immunity	EN12895, EN61000-4-3	10V/m /27-1000MHz AM; 10V/m /900MHz PM			
ESD	EN12895, EN61000-4-2	Direct: ±2KV ±4KV; Air: ±2KV ±4KV ±8KV			

Notes

1 Specifications typical at Ta=+25℃, nominal input voltage and rated full load output current unless otherwise noted.
2 Specifications are subject to change without notice.

ELECTRICAL CURVES




Figure 1: *Efficiency vs. Output current @ Vin=48V,72V,80V*




Figure 2: *Vout vs. Vin @ Full load*




Figure 3: *Input current vs. Input voltage @ Full load*




Figure 4: *Output voltage vs. Output current OCL Performance @72Vin*




Figure 5: *Output voltage vs. Output current @Vin=72V. Droop function.*




Figure 6: *Current share accuracy vs. Total output current 2 in parallel.*

ELECTRICAL CURVES (continous)




Figure 7: *Dynamic response to load step 6.25A~9.375A with 0.1A/uS slew rate at 72Vin*
CH1:VOUT, 100mV/div, 500uS/div




Figure 8: *Vout start up with Enable on at 72Vin,12.5A Iout, TOP:Enable, 50V/div, 100mS/div*
BOTTOM: VOUT, 10V/div, 100mS/div




Figure 9: *Output ripple & noise at 72Vin, 24A Iout*
CH1:VOUT, 50mV/div, 5uS/div




Figure 10: *Output over voltage protection at 72Vin, 24A Iout*
CH1:VOUT, 20V/div, 50mS/div




Figure 11: *Output short current @Vin=72V*
CH1:Io, 10A/div, 200mS/div




Figure 12: *Inrush current @ Vin=72V*
CH1:Iin, 2A/div, 200nS/div; Max current 4.3A, I2t=1.5E-7 A²S

FEATURES DESCRIPTIONS

Output Over-Current Limit and Short Protection

The modules include internal output over-current limit (OCL) and short circuit protection (SCP) circuits, the OCL set point is lower than that of the SCP; The response of SCP circuit is much fast than that of the OCL circuit. The slowly increase of the output current will let module enter OCL protection when the current exceeds the OCL set point, while the fast increase of the output current will let module enter SCP when the current exceeds the SCP set point.

When the modules enter OCL protection, the output voltage will decrease while the output current is kept constant, the output voltage will soft start to set point when the overload condition is removed.

The module will enter hiccup mode when it triggers the SCP set point. The module will try to restart after shutdown. If the overload condition still exists, the module will shut down again. This restart trial will continue until the overload condition is removed.

Output Over-Voltage Protection

The power module includes an internal output over-voltage protection(OVP) circuit, which monitors the voltage on the output terminals. If this voltage exceeds the OVP set point, the module will shut down, and then restart after a fixed delay time (hiccup mode), please refer to figure6 for detail.

Over-Temperature Protection

The over-temperature protection consists of circuitry that provides protection from thermal damage. If the temperature exceeds the preset temperature threshold the module will shut down,and all components will not exceed their absolute maximum temperature ratings.The module will restart after the temperature is within specification.

Enable On/Off

B70SR24125C has Enable control function. The Enable PIN is designed on the primary side of converter, the converter will turn on when the Enable PIN connected to VIN+, and turn off when the Enable PIN connected to VIN- or floating.




Figure 13: *suggested Enable connection*

Input Reverse Voltage Protection

The input reverse voltage protection is provided by an diode on the input line, the standoff voltage for the reverse protection shall be no less than -106V.

Parallel connection of multiple units

Two units parallel operation is verified, please contact Delta if more than two units need to be paralleled.
While parallelling multiple units, the impedance of the cables from unit to junction point of each unit should be within ±5% of each other.




Figure 14: *suggested parallel connections*

EMC

The converter has the internal EMI filters and meet the EMC standards EN12895 30-1000MHz 34-45dBuV/m.The test result is showed as below
Conditions: Vin=72V, Io=12.5A, 10m measure distance




Figure 15: *test result(Vertical)*




Figure 16: *test result(Horizontal)*

THERMAL CONSIDERATION

The following figure shows the location to monitor the temperature of base plate. Before customer decides to use this DCDC converter, a thermal evaluation need to be did to make sure the temperature of base plate is lower than that read from below thermal curves (Figure18~20 base on different input voltage).




Figure 17: *Thermal test setsup*

THERMAL CURVE




Figure 18: *Output Power vs. base plate temperature @Vin=48V*

THERMAL CURVES




Figure 19: *Output Power vs. base plate temperature @Vin=72V*





Figure 20: *Output Power vs. base plate temperature @Vin=80V*

Mechanical Drawing


Mechanical Dimensions



B70SR24125A(C)

Pin Connections	
Pin	Function Description
1	OUTPUT -
2	OUTPUT +
3	INPUT -
4	INPUT +

- All dimensions in mm (inches)
- Tolerance:X.X±0.5（X.XX±0.02)
  X.XX±0.25 (X.XXX±0.010)
- Connector:
  MOLEX MINI-FIT Sr™ Header
  (MOLEX P/N :42819-4213)




B70SR24125B(C)

Pin	Function Description
1	OUTPUT -
2	OUTPUT +
3	INPUT -
4	INPUT +

- All dimensions in mm (inches)
- Tolerance:X.X±0.5 (X.XX±0.02)
  X.XX±0.25 (X.XXX±0.010)
- Connector:
  Deutsch DTP Receptacles
  (DEUTSCH P/N :DTP04-4P)

Mechanical Drawing

Mechanical Dimensions




B70SR24125C(C)

Pin Connections

Pin	Function Description
1	OUTPUT -
2	OUTPUT +
3	INPUT -
4	INPUT +
5	ENABLE

- All dimensions in mm (inches)
- Tolerance:X.X±0.5 (X.XX±0.02)
  X.XX±0.25 (X.XXX±0.010)
- Connector:
  MOLEX MINI-FIT Sr™ Header
  (MOLEX P/N :42819-5213)



B70SR24125D(C)

Pin	Function Description
1	OUTPUT -
2	OUTPUT +
3	INPUT -
4	INPUT +

- All dimensions in mm (inches)
- Tolerance:X.X±0.5 (X.XX±0.02)
  X.XX±0.25 (X.XXX±0.010)
- Connector:
  MOLEX MINI-FIT Sr™ Header
  (MOLEX P/N :42819-4213)

Physical Outline

Case Size	:	190.0x76.0x43.5 mm (7.48”x2.99”x1.71”)
Case Material	:	Case: PC; Plate: AL6063

Part Numbering System

B	70	S	R	24	125	C				C
Form Factor	Input Voltage	Number of Outputs	Product Series	Output Voltage	Output Current	Option Code				Option Fitting
							With Built-in fuse holder	Enable pin	Sealed connector & fuse holder	Connector Kit
B- Box	70 – 36V~106V	S – Single	R – Regular	24 – 24V	125 – 12.5A	A	YES	NO	NO	1xhousing+ 4 terminals
						B	YES	NO	YES	1xhousing+ 4 terminals
						C	NO	YES	NO	1xhousing+ 5 terminals
						D	NO	NO	NO	1xhousing+ 4 terminals

Model List

Input Voltage Range	Input		Output		EFF @72VIN 100% LOAD
B70SR24125(A\B\C\D)	36V~106V	10A	24V	12.5A	92.5%

CONTACT: www.deltaww.com/dcdc

USA:
Telephone:
East Coast: 978-656-3993
West Coast: 510-668-5100
Fax: (978) 656 3964
Email: DCDC@delta-corp.com

Europe:
Phone: +31-20-655-0967
Fax: +31-20-655-0999
Email: DCDC@delta-es.com

Asia & the rest of world:
Telephone: +886 3 4526107
ext 6220~6224
Fax: +886 3 4513485
Email: DCDC@delta.com.tw

WARRANTY

Delta offers a two (2) years limited warranty. Complete warranty information is listed on our web site or is available upon request from Delta.

Information furnished by Delta is believed to be accurate and reliable. However, no responsibility is assumed by Delta for its use, nor for any infringements of patents or other rights of third parties, which may result from its use. No license is granted by implication or otherwise under any patent or patent rights of Delta. Delta reserves the right to revise these specifications at any time, without notice.

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Delta:

B70SR24125A