



General Description

The MDU2511S uses advanced MagnaChip's MOSFET Technology, which provides high performance in on-state resistance, fast switching performance and excellent quality. MDU2511S is suitable device for DC/DC Converter and general purpose applications.

Features

- $V_{DS} = 30V$
- $I_D = 188A$ @ $V_{GS} = 10V$
- $R_{DS(ON)} < 1.7 m\Omega$ @ $V_{GS} = 10V$
- $R_{DS(ON)} < 2.1 m\Omega$ @ $V_{GS} = 4.5V$
- 100% UIL Tested
- 100% Rg Tested
- SBD Built In



PDFN56

Absolute Maximum Ratings ($T_a = 25^\circ C$)

Characteristics		Symbol	Rating	Unit
Drain-Source Voltage		V_{DSS}	30	V
Gate-Source Voltage		V_{GSS}	± 20	V
Continuous Drain Current ⁽¹⁾	$T_C = 25^\circ C$	I_D	188.0	A
	$T_C = 100^\circ C$		118.9	
	$T_A = 25^\circ C$		45.0 ⁽³⁾	
	$T_A = 70^\circ C$		36.0 ⁽³⁾	
Pulsed Drain Current		I_{DM}	300	
Power Dissipation	$T_C = 25^\circ C$	P_D	96.2	W
	$T_C = 100^\circ C$		38.5	
	$T_A = 25^\circ C$		5.6 ⁽³⁾	
	$T_A = 70^\circ C$		3.6 ⁽³⁾	
Single Pulse Avalanche Energy ⁽²⁾		E_{AS}	320.0	mJ
Junction and Storage Temperature Range		T_J, T_{stg}	-55~150	$^\circ C$

Thermal Characteristics

Characteristics	Symbol	Rating	Unit
Thermal Resistance, Junction-to-Ambient ⁽¹⁾	$R_{\theta JA}$	22.7	$^\circ C/W$
Thermal Resistance, Junction-to-Case	$R_{\theta JC}$	1.3	

Ordering Information

Part Number	Temp. Range	Package	Packing	RoHS Status
MDU2511SVRH	-55~150°C	PDFN56	Tape & Reel	Halogen Free

Electrical Characteristics (T_J = 25°C)

Characteristics	Symbol	Test Condition	Min	Typ	Max	Unit
Static Characteristics						
Drain-Source Breakdown Voltage	BV _{DSS}	I _D = 250μA, V _{GS} = 0V	30	-	-	V
Gate Threshold Voltage	V _{GS(th)}	V _{DS} = V _{GS} , I _D = 250μA	1.3	1.9	2.7	
Drain Cut-Off Current	I _{DSS}	V _{DS} = 24V, V _{GS} = 0V	-	-	500	μA
Gate Leakage Current	I _{GSS}	V _{GS} = ±20V, V _{DS} = 0V	-	-	±0.1	
Drain-Source ON Resistance	R _{DS(on)}	V _{GS} = 10V, I _D = 22A	-	1.2	1.7	mΩ
		T _J = 125°C	-	1.7	2.4	
		V _{GS} = 4.5V, I _D = 20A	-	1.5	2.1	
Forward Transconductance	g _{fs}	V _{DS} = 5V, I _D = 22A	-	70	-	S
Dynamic Characteristics						
Total Gate Charge	Q _{g(4.5V)}	V _{DS} = 15.0V, I _D = 22A, V _{GS} = 10V	32.7	46.7	60.7	nC
Gate-Source Charge	Q _{gs}		-	15.5	-	
Gate-Drain Charge	Q _{gd}		-	17.9	-	
Input Capacitance	C _{iss}	V _{DS} = 15.0V, V _{GS} = 0V, f = 1.0MHz	5267	7023	8427	pF
Reverse Transfer Capacitance	C _{rss}		489	652	782	
Output Capacitance	C _{oss}		897	1197	1436	
Turn-On Delay Time	t _{d(on)}	V _{GS} = 10V, V _{DS} = 15.0V, I _D = 22A, R _G = 3.0Ω	-	24.5	-	ns
Rise Time	t _r		-	14.6	-	
Turn-Off Delay Time	t _{d(off)}		-	80.3	-	
Fall Time	t _f		-	22.8	-	
Gate Resistance	R _g	f = 1 MHz		1.0	2.0	Ω
Drain-Source Body Diode Characteristics						
Source-Drain Diode Forward Voltage	V _{SD}	I _S = 1A, V _{GS} = 0V	-	0.33	0.7	V
Body Diode Reverse Recovery Time	t _{rr}	I _F = 22A, di/dt = 100A/μs	-	42.7	-	ns
Body Diode Reverse Recovery Charge	Q _{rr}		-	49.5	-	nC

Note :

1. Surface mounted FR-4 board by JEDEC (jesd51-7). Continuous current at T_C = 25°C is silicon limited
2. E_{AS} is tested at starting T_J = 25°C, L = 0.1mH, I_{AS} = 40.0A, V_{DD} = 27V, V_{GS} = 10V.
3. T < 10sec.




Fig.1 On-Region Characteristics




Fig.2 On-Resistance Variation with Drain Current and Gate Voltage




Fig.3 On-Resistance Variation with Temperature




Fig.4 On-Resistance Variation with Gate to Source Voltage




Fig.5 Transfer Characteristics




Fig.6 Body Diode Forward Voltage Variation with Source Current and Temperature




Fig.7 Gate Charge Characteristics




Fig.8 Capacitance Characteristics




Fig.9 Maximum Safe Operating Area




Fig.10 Maximum Drain Current vs. Case Temperature





Fig.11 Transient Thermal Response Curve

Package Dimension


PDFN56 (5x6mm)

Dimensions are in millimeters, unless otherwise specified



Dimension	MILLIMETERS	
	Min	Max
A	0.90	1.10
b	0.33	0.51
C	0.20	0.34
D1	4.50	5.10
D2	-	4.22
E	5.90	6.30
E1	5.50	6.10
E2	-	4.30
e	1.27BSC	
H	0.41	0.71
K	0.20	-
L	0.51	0.71
α	0°	12°

Land Pattern



DISCLAIMER:

The Products are not designed for use in hostile environments, including, without limitation, aircraft, nuclear power generation, medical appliances, and devices or systems in which malfunction of any Product can reasonably be expected to result in a personal injury. Seller's customers using or selling Seller's products for use in such applications do so at their own risk and agree to fully defend and indemnify Seller.

MagnaChip reserves the right to change the specifications and circuitry without notice at any time. MagnaChip does not consider responsibility for use of any circuitry other than circuitry entirely included in a MagnaChip product. [MagnaChip](#) is a registered trademark of MagnaChip Semiconductor Ltd.