


ZWS15B-15/CO2



Sales Region	Worldwide
Series	ZWS-B
Status	Production
Feature	
Option	With coating on both sides of PCB model
Option Lineup	<a href="#">Please refer to here.</a>
Recommended EMC Filter	<a href="#">Please refer to here.</a>
Accessories	<a href="#">Please refer to the catalog</a>



Electrical Characteristics	
Input Voltage Range[AC]	85 to 265V
Input Voltage Range[DC]	120 to 370V
Efficiency	84% Typ.
Rated Output Voltage[DC]	15V
Output Voltage Range[DC]	13.5 to 16.5V
Maximum Output Current	1A
Maximum Output Power	15W

Cases Shape & Size	
Case'□ shape	PC board
Width(W)	50mm Nom.
Height(H)	22mm Nom.
Depth(D)	87.5mm Nom.
Weight	55g Typ.

Other	
Operating Temp. Range	-10 to 70°C
Cooling	Convection cooling
Safety Standard(Certified)	UL60950-1
	CSA C22.2 No.60950-1
	EN60950-1
	EN50178 (OV II)
Safety Standard(Conformed)	Den-an
Remarks	This page only shows representative characteristics. Please refer to the technical data for detailed specifications and conditions.

! Images are for reference only and show exemplary products.  
! This PDF document was created based on the data listed on the TDK Corporation website.  
! All specifications are subject to change without notice.