

Data sheet | Item number: 706-100/537-100

Connection cable; 37-pole; with solder pin; Male connector; open-ended;
Length: 1 m; Conductor cross-section: 0.25 mm²



www.wago.com/706-100/537-100

Data Notes

Note	When using more than 10 wires, the maximum current per wire must be reduced to 1 A.
------	---

Electrical data

Operating voltage	≤ AC/DC 35 V
Current per wire (max.)	2 A

Connection data

Pole No.	37
Connection type (1)	System
Pole number 1	37
Pluggable connectors	D-sub male connector
Connection type 2	Open-ended
Cable type	LiYCY
Wire cross-section	0.25 mm ²
Color code	per DIN VDE 47100

Physical data

Cable length	1 m
--------------	-----

Material data

Weight	1.1 g
--------	-------

Environmental requirements

Surrounding air temperature (operation)	-20 ... 50 °C
---	---------------

Commercial data

PU (SPU)	1 Stück
----------	---------

Subject to changes. Please also observe the further product documentation!

WAGO GmbH & Co. KG
Hansastr. 27
32423 Minden
Phone: +49571 887-0 | Fax: +49571 887-169
Email: info.de@wago.com | Web: www.wago.com

Do you have any questions about our products?
We are always happy to take your call at +49 (571) 887-44222.



Packaging type	box
Country of origin	FR
GTIN	4050821835493

Downloads

Environmental Product Compliance

Compliance Search

Environmental Product Compliance 706-100/537-100	URL	Download
Connection cable; 37-pole; with solder pin; Male connector; open-ended; Length: 1 m; Conductor cross-section: 0.25 mm ²		

Installation Notes

Subject to changes. Please also observe the further product documentation!

WAGO GmbH & Co. KG
Hansastr. 27
32423 Minden
Phone: +49571 887-0 | Fax: +49571 887-169
Email: info.de@wago.com | Web: www.wago.com

Do you have any questions about our products?
We are always happy to take your call at +49 (571) 887-44222.