New Jersey Semi-Conductor Products, Inc.

20 STERN AVE.
SPRINGFIELD, NEW JERSEY 07081
U.S.A.

TELEPHONE: (973) 376-2922
(212) 227-6005
FAX: (973) 376-8960

161CMQ... SERIES

SCHOTTKY RECTIFIER 160 Amp



TO-249AA


Major Ratings and Characteristics

Characteristics		161CMQ...	Units
$I_{F(AV)}$	Rectangular waveform	160	A
V_{RRM}	range	30 to 50	V
I_{FSM}	@tp = 5 µs sine	11,500	A
V_F	@80 Apk, T_J = 125°C (per leg)	0.63	V
T_J	range	-55 to 175	°C

Description/ Features

The 161CMQ isolated center tap Schottky rectifier module series has been optimized for low reverse leakage at high temperature. The proprietary barrier technology allows for reliable operation up to 175° C junction temperature. Typical applications are in switching power supplies, converters, free-wheeling diodes, and reverse battery protection.

- 175° C T_J operation
- Isolated heatsink
- Center tap module
- Multiple leads per terminal for high frequency, high current PC board mounting
- High purity, high temperature epoxy encapsulation for enhanced mechanical strength and moisture resistance
- Low forward voltage drop
- High frequency operation
- Guard ring for enhanced ruggedness and long term reliability
- Low profile, high current package



Outline D-60 (Modified JEDEC TO-249AA)
Dimensions in millimeters and (inches)

Quality Semi-Conductors

Download from alldatasheet.com

Voltage Ratings

Part number		161CMQ030	161CMQ035	161CMQ040	161CMQ045	161CMQ050
V_R	Max. DC Reverse Voltage (V)	30	35	40	45	50
V_{RWM}	Max. Working Peak Reverse Voltage (V)					

Absolute Maximum Ratings

	Parameters	161CMQ	Units	Conditions	
$I_{F(AV)}$	Max. Average Forward Current * See Fig. 5	160	A	50% duty cycle @ T_C = 101 °C, rectangular wave form	
I_{FSM}	Max. Peak One Cycle Non-Repetitive Surge Current (Per Leg) * See Fig. 7	11,500	A	5µs Sine or 3µs Rect. pulse	Following any rated load condition and with rated V_{RRM} applied
		900		10ms Sine or 6ms Rect. pulse	
E_{AS}	Non-Repetitive Avalanche Energy (Per Leg)	108	mJ	T_J = 25 °C, I_{AS} = 16 Amps, L = 0.84 mH	
I_{AR}	Repetitive Avalanche Current (Per Leg)	16	A	Current decaying linearly to zero in 1 µsec Frequency limited by T_J max. V_A = 1.5 x V_R typical	

Electrical Specifications

	Parameters	161CMQ	Units	Conditions	
V_{FM}	Max. Forward Voltage Drop (Per Leg) * See Fig. 1 (1)	0.71	V	@ 80A	T_J = 25 °C
		0.88	V	@ 160A	
		0.63	V	@ 80A	T_J = 125 °C
		0.79	V	@ 160A	
I_{RM}	Max. Reverse Leakage Current (Per Leg) * See Fig. 2 (1)	5	mA	T_J = 25 °C	V_R = rated V_R
		45	mA	T_J = 125 °C	
C_T	Max. Junction Capacitance (Per Leg)	2600	pF	V_R = 5V_{DC}, (test signal range 100Khz to 1Mhz) 25°C	
L_S	Typical Series Inductance (Per Leg)	8.0	nH	Measured from terminal hole to terminal hole	
dv/dt	Max. Voltage Rate of Change (Rated V_R)	10000	V/ µs		

(1) Pulse Width < 300µs, Duty Cycle <2%

Thermal-Mechanical Specifications

	Parameters		161CMQ	Units	Conditions
T_J	Max. Junction Temperature Range		-55 to 175	°C	
T_{stg}	Max. Storage Temperature Range		-55 to 175	°C	
R_{thJC}	Max. Thermal Resistance Junction to Case (Per Leg)		1.0	°C/W	DC operation * See Fig. 4
R_{thJC}	Max. Thermal Resistance Junction to Case (Per Package)		0.50	°C/W	DC operation
R_{thCS}	Typical Thermal Resistance, Case to Heatsink		0.10	°C/W	Mounting surface, smooth and greased
wt	Approximate Weight		58 (2.0)	g (oz.)	
T	Mounting Torque	Min.	40 (35)	Kg-cm (lbf-in)	
		Max.	58 (50)		
	Case Style		TO-249AA		JEDEC

Download from alldatasheet.com