General Cable

Product Data Sheet

RoHS Compliant Directive 2002/95/EC

Part Number:	C2040A	Revision Date:	1/9/2013

1C 20 AWG 10/30 TC PVC **HOOK UP WIRE**

A. CONSTRUCTION

		DIAMETERS
Conductor:	#20 AWG 10/30 Tinned Copper	.038" Nom
Insulation:	.016" Polyvinyl Chloride (PVC)	.070" Nom
Print Legend:	***CAROL A 20 AWG RU AWM 80C VW-1 E18621-8 --- CSA LL69381 FT-1 TR64 90C --- MADE IN USA ****	
Note *	NOTE: THIS PRODUCT IS ONLY MARKED 80C AS PER UL STYLE 1007, HOWEVER, IT ALSO MEETS 105C AS PER UL STYLE 1569	

B. INDUSTRY APPROVALS

UL Standard 758	AWM Style 1007 / 1569
CSA International	Type TR64

C. ELECTRICAL PROPERTIES

Temperature:	-20°C to +105°C
Suggested Working Voltage:	300V Max
Conductor DCR:	10.9 Ohms/M' @ 20°C (Max)

D. CUSTOMER APPROVAL

Signature: _____

Date: _____

Note: Data subject to change without notice. Contact your Customer Service representative for latest information.