


◆FEATURES

1. Small in size and wide capacitance range.
Max. 470 μ F is available.
2. Temperature characteristic is X7R in EIA code.
3. Superior humidity characteristic and long life.
4. Excellent high frequency characteristic due to low ESR.
5. High rated ripple current.
6. 250V_{dc} items are available.
7. Resin(UL94 V-0) used for coating.
8. Pb-free design(also ceramic dielectric)

◆APPLICATIONS

1. Smoothing circuit of switching mode AC-DC or DC-DC converter.
2. Noise suppressor for various kinds of equipments.
3. By-pass or decoupling circuits.
4. Automotive equipments.

◆CONSTRUCTION



◆RATINGS

1. Category Temperature Range	-55 to +125°C
2. Rated Voltage Range	25, 50, 100, 250 V _{dc}
3. Rated Capacitance Range	0.1 to 470 μ F
4. Rated Capacitance Tolerance	M($\pm$ 20%)
5. Temperature Characteristics	X7R
6. Rated Ripple Current	See No.5 on the following table

◆SPECIFICATIONS

No.	Items		Specification	Test Condition	
1	Withstand Voltage	Between Terminals	No abnormality.	250% of rated voltage shall be applied for 5 seconds. (Only 250V _{dc} products : 475V)	
		Terminals to Coating Resin			
2	Insulation Resistance		100/C _R (M Ω) or 4000(M Ω) whichever is less.	Rated voltage shall be applied for 60 $\pm$ 5 seconds at temperature 25 $\pm$ 2°C.	
3	Rated Capacitance		Within specified tolerance.		
				CR $\leq$ 10 μ F	CR>10 μ F
4	Dissipation Factor		5.0% maximum.	Temperature	25 $\pm$ 2°C
				Frequency	1 $\pm$ 0.1kHz 120 $\pm$ 12Hz
				Voltage	1 $\pm$ 0.2V _{rms} 0.5 $\pm$ 0.2V _{rms}


As customer requirement, Chemi-Con has submits the test results according to AEC-Q200 for Multilayer ceramic capacitors. Please contact us for more information.

◆SPECIFICATIONS


No.	Items		Specification								Test Condition																	
5	Rated Ripple Current		Size code	32	43	55	76	80	90	99	10kHz to 1MHz (sine curve) Ripple voltage Vp shall be less than the rated voltage.																	
			Arms	0.3	0.8	1.0	1.5	2.0	3.0	4.0																		
6	Robustness of Terminations	Tension	No visible damage.								The force applied shall be :																	
	Bending										Time : 2times.																	
7	Vibration		Appearance : No abnormality. Capacitance : To meet the initial specification. D.F. : To meet the initial specification.								Amplitude : 1.5mm Frequency range : 10-55-10Hz (1 min) Direction and time : 2 hours each to X, Y, Z axis. Total 6 hours.																	
8	Solderability		Min. 75% of surface of the termination shall be covered with new solder.								<table><tr><td>Solder</td><td>Pb Free</td></tr><tr><td>Solder Temperature</td><td>245±5°C</td></tr><tr><td>Dipping Time</td><td>2±0.5sec.</td></tr></table>			Solder	Pb Free	Solder Temperature	245±5°C	Dipping Time	2±0.5sec.									
Solder	Pb Free																											
Solder Temperature	245±5°C																											
Dipping Time	2±0.5sec.																											
9	Resistance to Soldering Heat		Appearance : No abnormality. ΔC/C : ± 15% D.F. : To meet the initial specification. I.R. : To meet the initial specification.								Solder Temperature : 350±10°C Dipping Time : 3±0.5 sec. Depth : 1.5 to 2mm																	
10	Temperature Cycle		Appearance : No abnormality. ΔC/C : ± 15% D.F. : To meet the initial specification. I.R. : To meet the initial specification.								<table><tr><td>Step</td><td>Temperature (°C)</td><td>(min.)</td></tr><tr><td>1</td><td>Min. Category temperature ±3</td><td>30±3</td></tr><tr><td>2</td><td>Room temperature</td><td>3 max.</td></tr><tr><td>3</td><td>Max. Category temperature ±3</td><td>30±3</td></tr><tr><td>4</td><td>Room temperature</td><td>3 max.</td></tr></table> For 5 cycles for above temperature cycle.			Step	Temperature (°C)	(min.)	1	Min. Category temperature ±3	30±3	2	Room temperature	3 max.	3	Max. Category temperature ±3	30±3	4	Room temperature	3 max.
Step	Temperature (°C)	(min.)																										
1	Min. Category temperature ±3	30±3																										
2	Room temperature	3 max.																										
3	Max. Category temperature ±3	30±3																										
4	Room temperature	3 max.																										
11	Humidity Load Life		Appearance : No abnormality. ΔC/C : ± 20% D.F. : 10% maximum I.R. : 25/CR(MΩ) or 1000(MΩ) whichever is less.								Temperature : 40±2°C Humidity : 90 to 95%RH Voltage : Rated voltage Time : 500± ²⁴ ₀ hours																	
12	Endurance		Appearance : No abnormality. ΔC/C : ± 20% D.F. : 10% maximum I.R. : 50/CR(MΩ) or 1000(MΩ) whichever is less.								Temperature : 125±3°C Voltage : Rated voltage Time : 1000± ⁴⁸ ₀ hours																	

*C_R : Rated Capacitance(μF)

◆PART NUMBERING SYSTEM



◆DIMENSIONS



Please refer to "Part Numbering System" of the beginning of a catalog for the details.



DIPPED RADIAL LEAD MULTILAYER CERAMIC CAPACITORS

NTDSeries

◆STANDARD RATINGS

Rated voltage (Vdc)	Rated Capacitance (μF)	Dimensions (mm)					Maximum ripple current (Arms)	Part Number	Taping Quantity per reel (pcs. / box)						
		Lmax.	Wmax.	Tmax.	F±0.8	φd±0.05									
25	3.3	5.0	6.0	3.5	5.0	0.5	0.3	KTD250B335M32A0T00	2,000						
	4.7							KTD250B475M32A0T00	2,000						
	6.8							KTD250B685M43A0T00	2,000						
	10	6.5	6.5	4.0	5.0	0.5	0.8	KTD250B106M43A0T00	2,000						
	15							KTD250B156M43A0T00	2,000						
	15							KTD250B156M55A0T00	2,000						
	22	7.5	9.0	4.5	5.0	0.5	1.0	KTD250B226M55A0T00	2,000						
	33							KTD250B336M55A0T00	2,000						
	47							KTD250B476M76A0T00	1,000						
	68	13.5	15.0	6.0	10.0	0.6	2.0	KTD250B686M80A0B00	—						
	100			8.0				KTD250B107M80A0B00	—						
	150			6.0				KTD250B157M90A0B00	—						
	220	22.5	20.0	8.0	20.0	0.8	3.0	KTD250B227M90A0B00	—						
	330			8.0				KTD250B337M99A0B00	—						
	470			11.5				KTD250B477M99A0B00	—						
50	1.0	5.0	6.0	3.5	5.0	0.5	0.3	KTD500B105M32A0T00	2,000						
	1.5							KTD500B155M32A0T00	2,000						
	2.2							KTD500B225M32A0T00	2,000						
	3.3							KTD500B335M32A0T00	2,000						
	4.7	6.5	6.5	4.0	5.0	0.5	0.8	KTD500B475M43A0T00	2,000						
	6.8							KTD500B685M43A0T00	2,000						
	10							KTD500B106M55A0T00	2,000						
	15	7.5	9.0	4.5	5.0	0.5	1.0	KTD500B156M55A0T00	2,000						
	22							10.0	11.5	5.0	5.0	1.5	KTD500B226M76A0T00	1,500	
	33												13.5	15.0	5.5
	47	22.5	20.0	6.0	20.0	0.8	3.0								
	68			6.0				KTD500B686M90A0B00	—						
	100			7.0				KTD500B107M90A0B00	—						
	150	28.5	20.0	7.5	25.0	0.8	4.0	KTD500B157M99A0B00	—						
	220			10.0				KTD500B227M99A0B00	—						
100	0.33			5.0				6.0	3.5	5.0	0.5	0.3	KTD101B334M32A0T00	2,000	
	0.47	KTD101B474M32A0T00	2,000												
	0.68	KTD101B684M32A0T00	2,000												
	1.0	KTD101B105M32A0T00	2,000												
	1.5	KTD101B155M32A0T00	2,000												
	2.2	KTD101B225M32A0T00	2,000												
	1.5	6.5	6.5	4.0	5.0	0.5	0.8	KTD101B155M43A0T00	2,000						
	2.2							KTD101B225M43A0T00	2,000						
	3.3							KTD101B335M43A0T00	2,000						
	4.7							KTD101B475M43A0T00	2,000						
	3.3							KTD101B335M55A0T00	2,000						
	4.7							KTD101B475M55A0T00	2,000						
	6.8	7.5	9.0	4.5	5.0	0.5	1.0	KTD101B685M55A0T00	2,000						
	4.7			KTD101B685M55A0T00				2,000							
	6.8			5.0				KTD101B685M76A0T00	1,500						
10	13.5	15.0	5.0	10.0	0.6	2.0	KTD101B106M80A0B00	—							
15			6.0				KTD101B156M80A0B00	—							
22			22.5				20.0	6.0	20.0	0.8	3.0	KTD101B226M90A0B00	—		
33	KTD101B336M90A0B00	—													
47	28.5	20.0		7.5	25.0	0.8						4.0	KTD101B476M99A0B00	—	
68			KTD101B686M99A0B00	—											
100			9.0	KTD101B107M99A0B00			—								
250			0.1	5.0			6.0	3.5	5.0	0.5	0.3		KTD251B104M32A0T00	2,000	
	0.15	KTD251B154M32A0T00	2,000												
	0.22	KTD251B224M32A0T00	2,000												
	0.33	KTD251B334M32A0T00	2,000												
	0.47	6.5	6.5	4.0	5.0	0.5	0.8	KTD251B474M43A0T00	2,000						
	0.68							KTD251B684M43A0T00	2,000						
	1.0							KTD251B105M55A0T00	2,000						
	1.5	7.5	9.0	4.5	5.0	0.5	1.0	KTD251B155M55A0T00	2,000						
	2.2							10.0	11.5	6.0	5.0	0.5	1.5	KTD251B225M76A0T00	1,000
	2.2													13.5	15.0
	3.3	22.5	20.0	6.0	20.0	0.8	3.0							KTD251B335M90A0B00	—
	4.7							KTD251B475M90A0B00	—						
	6.8							KTD251B685M99A0B00	—						
	10							KTD251B106M99A0B00	—						
	15							28.5	20.0	7.5	25.0	0.8	4.0	KTD251B156M99A0B00	—

※Please consult with us when you consider the rating other than a standard table.