

Inductors

Commercial, Subminiature, Molded, Shielded



FEATURES

- Classification is Grade 1, Class A
- Ultra-reliable molded shielded inductor
- Inductance range is 0.10 μH to 10 000 μH
- 0.136" [3.45 mm] diameter by 0.335" [8.51 mm] length
- Molded epoxy envelope
- Subminiature size for high density circuits and high inductance-to-size ratio
- Utmost reliability, electrical performance and minimum coupling in high density packaging


RoHS
COMPLIANT

ELECTRICAL SPECIFICATIONS

Inductance Tolerance: $\pm 10\%$ on Q-Meter at specified frequency

Dielectric Strength: 700 VRMS at sea level

Operating Temperature: - 55 °C to + 105 °C

Self-Resonant Frequency: Measured per MIL-PRF-15305

Q: Measured on a Q-Meter at specified frequency

Rating: Maximum based on 1/3 watt dissipation

MECHANICAL SPECIFICATIONS

Terminal Strength: Meets five pound pull test; three 360° rotations in alternate directions per MIL-PRF-15305 (latest revision)

DENSITY SPECIFICATIONS

Weight: 0.50 gram maximum

Shielding: Less than 3 % coupling with two units mounted side by side at 1000 cycles


ENVIRONMENTAL SPECIFICATIONS

Moisture: Meets requirements of MIL-PRF-15305

Vibration: High frequency, 10 Hz to 2000 Hz at 20 g $\pm 10\%$ maximum for 12 logarithmic swings each of 20 minute duration repeated for each of three mutually perpendicular planes

Shock: 100 g, 6 ms

DIMENSIONS in inches [millimeters]



STANDARD ELECTRICAL SPECIFICATIONS

MODEL	IND. (μH)	TOL.	Q MIN.	TEST FREQ. MIN. (MHz)	SELF- RESONANT FREQ. MIN. (MHz)	DCR MAX. (Ohms)	RATED DC CURRENT (mA)	INCREMENTAL* CURRENT (mA)	PHENOLIC
IMS-2SWWD-3	0.10	$\pm 10\%$	42	25	480	0.087	1038	> 1650	
IMS-2SWWD-3	0.12	$\pm 10\%$	42	25	460	0.090	1021	> 1630	
IMS-2SWWD-3	0.15	$\pm 10\%$	42	25	400	0.098	978	> 1550	
IMS-2SWWD-3	0.18	$\pm 10\%$	42	25	360	0.117	895	> 1420	
IMS-2SWWD-3	0.22	$\pm 10\%$	42	25	340	0.141	815	> 1330	
IMS-2SWWD-3	0.27	$\pm 10\%$	42	25	320	0.157	773	> 1230	
IMS-2SWWD-3	0.33	$\pm 10\%$	42	25	295	0.178	726	> 1140	
IMS-2SWWD-3	0.39	$\pm 10\%$	42	25	275	0.208	671	> 1060	
IMS-2SWWD-3	0.47	$\pm 10\%$	41	25	250	0.257	604	> 960	
IMS-2SWWD-3	0.56	$\pm 10\%$	39	25	238	0.283	576	> 915	
IMS-2SWWD-3	0.68	$\pm 10\%$	36	25	224	0.337	527	> 840	
IMS-2SWWD-3	0.82	$\pm 10\%$	35	25	205	0.470	447	> 720	

* **Incremental Current:** The DC current required to cause a 5 % reduction in the nominal inductance value


STANDARD ELECTRICAL SPECIFICATIONS									
MODEL	IND. (μH)	TOL.	Q MIN.	TEST FREQ. MIN. (MHz)	SELF- RESONANT FREQ. MIN. (MHz)	DCR MAX. (Ohms)	RATED DC CURRENT (mA)	INCREMENTAL* CURRENT (mA)	
IMS-2SWWD-30	1.0	± 10 %	38	25	135	0.170	678	> 1180	IRON
IMS-2SWWD-30	1.2	± 10 %	38	7.9	124	0.177	664	> 1150	
IMS-2SWWD-30	1.5	± 10 %	38	7.9	114	0.212	607	> 1050	
IMS-2SWWD-30	1.8	± 10 %	38	7.9	105	0.242	568	> 990	
IMS-2SWWD-30	2.2	± 10 %	38	7.9	95	0.263	545	> 950	
IMS-2SWWD-30	2.7	± 10 %	38	7.9	85	0.300	510	> 880	
IMS-2SWWD-30	3.3	± 10 %	38	7.9	78	0.345	476	> 820	
IMS-2SWWD-30	3.9	± 10 %	42	7.9	74	0.411	436	> 755	
IMS-2SWWD-30	4.7	± 10 %	42	7.9	68	0.562	373	> 650	
IMS-2SWWD-30	5.6	± 10 %	42	7.9	62	0.742	324	> 565	
IMS-2SWWD-30	6.8	± 10 %	45	7.9	55	1.00	280	> 485	
IMS-2SWWD-30	8.2	± 10 %	47	7.9	51	1.20	255	> 440	
IMS-2SWWD-30	10	± 10 %	51	7.9	45	1.84	206	> 335	
IMS-2SWWD-30	12	± 10 %	51	2.5	41	2.60	173	> 300	
IMS-2SWWD-30	15	± 10 %	35	2.5	48	0.635	314	200	FERRITE
IMS-2SWWD-30	18	± 10 %	35	2.5	44	0.728	293	175	
IMS-2SWWD-30	22	± 10 %	35	2.5	37	0.825	275	160	
IMS-2SWWD-30	27	± 10 %	35	2.5	32	0.950	256	155	
IMS-2SWWD-30	33	± 10 %	36	2.5	30	1.26	223	150	
IMS-2SWWD-30	39	± 10 %	36	2.5	27	1.42	210	145	
IMS-2SWWD-30	47	± 10 %	36	2.5	23	1.72	191	140	
IMS-2SWWD-30	56	± 10 %	38	2.5	21	2.03	175	130	
IMS-2SWWD-30	68	± 10 %	38	2.5	18.5	2.29	165	120	
IMS-2SWWD-30	82	± 10 %	36	2.5	17.0	2.55	157	115	
IMS-2SWWD-30	100	± 10 %	36	2.5	15.5	2.92	146	100	
IMS-2SWWD-30	120	± 10 %	43	0.79	14.5	3.30	154	80	
IMS-2SWWD-30	150	± 10 %	43	0.79	13.0	4.30	147	68	
IMS-2SWWD-30	180	± 10 %	43	0.79	11.5	5.40	120	64	
IMS-2SWWD-30	220	± 10 %	45	0.79	10.0	6.65	108	60	
IMS-2SWWD-30	270	± 10 %	47	0.79	9.5	7.6	101	58	
IMS-2SWWD-30	330	± 10 %	47	0.79	8.5	8.5	96	56	
IMS-2SWWD-30	390	± 10 %	47	0.79	8.0	10.0	88	54	
IMS-2SWWD-30	470	± 10 %	47	0.79	7.2	13.5	76	52	
IMS-2SWWD-30	560	± 10 %	51	0.79	6.4	14.5	73	50	
IMS-2SWWD-30	680	± 10 %	51	0.79	5.8	6.0	70	48	
IMS-2SWWD-30	820	± 10 %	48	0.79	5.3	19.0	64	47	
IMS-2SWWD-30	1000	± 10 %	48	0.79	4.8	21.5	60	45	
IMS-2SWWD-30	1200	± 10 %	45	0.25	2.9	23	52	40	
IMS-2SWWD-30	1500	± 10 %	45	0.25	2.8	30	46	35	
IMS-2SWWD-30	1800	± 10 %	45	0.25	2.6	33	44	32	

* **Incremental Current:** The DC current required to cause a 5 % reduction in the nominal inductance value

MARKING
- Color coded per MIL-PRF-15305 (latest revision)



ORDERING INFORMATION				
IMS-2SWWD-30	1.0 μ H	10 %	ER	e2
MODEL	INDUCTANCE VALUE	INDUCTANCE TOLERANCE	PACKAGE CODE	JEDEC LEAD (Pb)-FREE STANDARD





Disclaimer

All product specifications and data are subject to change without notice.

Vishay Intertechnology, Inc., its affiliates, agents, and employees, and all persons acting on its or their behalf (collectively, "Vishay"), disclaim any and all liability for any errors, inaccuracies or incompleteness contained herein or in any other disclosure relating to any product.

Vishay disclaims any and all liability arising out of the use or application of any product described herein or of any information provided herein to the maximum extent permitted by law. The product specifications do not expand or otherwise modify Vishay's terms and conditions of purchase, including but not limited to the warranty expressed therein, which apply to these products.

No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted by this document or by any conduct of Vishay.

The products shown herein are not designed for use in medical, life-saving, or life-sustaining applications unless otherwise expressly indicated. Customers using or selling Vishay products not expressly indicated for use in such applications do so entirely at their own risk and agree to fully indemnify Vishay for any damages arising or resulting from such use or sale. Please contact authorized Vishay personnel to obtain written terms and conditions regarding products designed for such applications.

Product names and markings noted herein may be trademarks of their respective owners.