

P-tec Corp.  
2405 Commerce Circle  
Alamosa Co. 81101  
www.p-tec.net

Tel:(800)688-0613  
Tel:(719) 589 3122  
Fax:(719) 589 3592  
sales@p-tec.net



## PLH006 Series SMD LED SOT23 Package

### Features

- \*Flat Lens Package 3.0 x 2.8 x 1.1 mm
- \*GaP Green Chip used
- \*High Light Output
- \*IC Compatible
- \*3000 pcs per Reel
- \*RoHS Compliant

### Absolute Maximum Ratings at $T_A = 25^\circ\text{C}$

Power Dissipation .....	70mW
Reverse Voltage (<100 $\mu\text{A}$ ) .....	5.0V
Max Forward Current .....	25mA
Peak Forward Current (1/10 Duty Cycle, 0.1ms Pulse Width) .....	50mA
Operating Temperature Range .....	-30°C to + 85°C
Storage Temperature Range .....	-40°C to + 85°C
Reflow Soldering Temperature .....	260° for 5 seconds

### Electrical & Optical Characteristics at $T_A = 25^\circ\text{C}$

Part Number	Emitting Color	Chip Material	Peak Wave Length	Dominant Wave Length	Viewing Angle $2\theta_{1/2}$	Forward Voltage @20mA (V)		Luminous Intensity @20mA (mcd)	
						Typ	Max	Min	Typ
Water Clear Lens			nm	nm	Deg	Typ	Max	Min	Typ
PLH006-WCG13	Green	GaP	570	567	140°	2.1	2.8	4.0	8.5

All dimensions are in **Millimeters**. Tolerance is  $\pm 0.25\text{mm}$  unless otherwise specified.

