

# HPU31B SERIES

## 30W Desk top type medical power supplies for Home health care applications

### Description:

The HPU31B series of AC/DC switching mode power supplies provide 30 Watts of continuous output power . All supplies are UL94V-1 min compliant, include IEC-320-C18 input for worldwide applications. They are suited for use in Home health care applications. All models meet FCC Part-18 class B and CISPR-11 EN55011 class B emission Limits and are designed to comply with UL/c-UL(UL 60601-1) ,TUV/T-mark (EN 60601-1) and new CE requirements. All units are 100% burned in and tested.



### Features:

- Wide Input Voltage 90 to 264 VAC,47 to 63 Hz
- IEC-320-C8 Input Inlet
- Single Output
- Output Voltage Available From 5VDC Thru 48VDC
- Optional Output Connector (See appendix)
- Over Voltage Protection (Crowbar Design)
- Input Surge Current, Over Voltage And Over Load protection
- CEC level V and Energy Star 2.0 Compliance
- Approved as Limited Power Source (LPS).
- Class II
- 2 year warranty

### Safety Approvals :



### Electrical Characteristics:

Sym.	Parameter	Test Conditions	Min.	Typ.	Max.	Unit
V <sub>in</sub>	Input Voltage	Operating Voltage	90		264	VAC
f <sub>in</sub>	Input Frequency		47		63	Hz
P <sub>o</sub>	Output Power Range	V <sub>in</sub> =90 to 264VAC	0		30	W
V <sub>o</sub>	Output Voltage Range		See rating chart			V
I <sub>o</sub>	Output Current Range		See rating chart			A
I <sub>il</sub>	Input Current (Low Line)	I <sub>o</sub> =Full load, V <sub>in</sub> =115 VAC			0.9	A
I <sub>ih</sub>	Input Current (High Line)	I <sub>o</sub> =Full load, V <sub>in</sub> =230 VAC			0.34	A
I <sub>rl</sub>	Low Line Inrush Current	I <sub>o</sub> =Full load, 25°C ,Cool start, V <sub>in</sub> =115VAC		16	24	A
I <sub>rh</sub>	High Line Inrush Current	I <sub>o</sub> =Full load, 25°C ,Cool start, V <sub>in</sub> = 230VAC		32	48	A
Eff	Efficiency	I <sub>o</sub> =Full Load, V <sub>in</sub> =230VAC	78	85	88	%
REG-i	Line Regulation	I <sub>o</sub> =Full Load		0.5		%
REG-o	Load Regulation	V <sub>in</sub> =230VAC		5		%
OVP	Over Voltage Protection		112		132	%
OCP	Over Current Protection		110		150	%
T <sub>tr</sub>	Time of Transient Response	I <sub>o</sub> =Full Load to Half Load, V <sub>in</sub> =100VAC			4	mS
Thold	Hold-Up Time	I <sub>o</sub> =Full Load, V <sub>in</sub> =110VAC	12			mS
T <sub>s</sub>	Start Up Time	I <sub>o</sub> =Full Load, V <sub>in</sub> =100VAC	0.3	1.5	2	S
V <sub>rn</sub>	Ripple & Noise (Peak to Peak)	Full Load, V <sub>in</sub> =90VAC			1	%
TC	Temperature Coefficient	All output	-0.04		0.04	%/°C

### Environmental :

Sym.	Parameter	Test Conditions	Min.	Typ.	Max.	Unit
T <sub>oper</sub>	Operating Temperature		0	40	70	°C
T <sub>stg</sub>	Storage Temperature		-40		85	°C
H <sub>r</sub>	Relative Humidity		5		95	%
MTBF	Operating Temperature at 25°C, Calculated per MIL-HDBK-217F		0.1M			Hrs
P <sub>d</sub>	Derate linearly from 100% load at 40°C to 50% load at 70°C					

### Safety Specifications:

Sym.	Parameter	Test Conditions	Min.	Typ.	Max.	Unit
V <sub>ps</sub>	Dielectric Withstanding Voltage for Primary to secondary	Primary to secondary	5600			VDC
CISPR	EMI requirements for CISPR-11	V <sub>in</sub> =220VAC	B			CLASS
FCC	EMI requirements for FCC PART-18	V <sub>in</sub> =110VAC	B			CLASS

# HPU31B SERIES

30W Desk top type medical power supplies for Home health care applications

## Output Voltage And Current Rating Chart (Single Output) :

Model Number	Output Voltage	Output Current	Total Regulation	Maximum Output Power
HPU31B-102	5 ~ 6 VDC	4.00 ~ 3.33 A	5%	20W
HPU31B-103	6 ~ 8 VDC	3.83 ~ 2.87 A	5%	23W
HPU31B-104	8 ~ 11 VDC	3.38 ~ 2.45 A	5%	27W
HPU31B-105	11 ~ 13 VDC	2.74 ~ 2.30 A	5%	30W
HPU31B-106	13 ~ 16 VDC	2.30 ~ 1.88 A	5%	30W
HPU31B-107	16 ~ 21 VDC	1.88 ~ 1.43 A	5%	30W
HPU31B-108	21 ~ 27 VDC	1.43 ~ 1.11 A	5%	30W
HPU31B-109	27 ~ 33 VDC	1.11 ~ 0.91 A	3%	30W
HPU31B-110	33 ~ 40 VDC	0.91 ~ 0.75 A	3%	30W
HPU31B-111	40 ~ 48 VDC	0.75 ~ 0.63 A	3%	30W

## Mechanical Specifications:

- Note:
1. Dimensions are shown in inches or mm.
  2. Weight: 265-280gs approx.
  3. Optional output connector:  
See page Appendix.

