



Rating: 1A 12V DC
 Contact Resistance: 100 mΩ Max.
 Operating temperature: -25℃~85℃
 Operating force: 30N Min
 Operating Life: 5,000cycles

⑫	Separator	1	Thermoplastics	White		
⑪	Cover/2	1	Thermoplastics	White		
⑩	Cover/1	1	Thermoplastics	White		
⑨	Housing	1	Thermoplastics	White		
⑧	Sleeve	1	Copper Alloy	Ni Plating		
⑦	Spring Contact	1	Copper Alloy	Ni Plating		
⑥	Switch B Contact	1	Copper Alloy	Ni Plating		
⑤	Switch A Contact	1	Copper Alloy	Ni Plating		
④	Left Contact	1	Copper Alloy	Ni Plating		
③	Right Contact	1	Copper Alloy	Ni Plating		
②	Mic Contact	1	Copper Alloy	Ni Plating		
①	Ground Contact	1	Copper Alloy	Ni Plating		
ITEM	PART NAME	TER.NO.	QTY.	MATERIAL	FINISHING	REMARK
APPROVALS		DATE				
DRAWN		J.X.Zhong		2019/8/8		
CHECKED		TITLE:				ELECTRONICS CO.,LTD
APPROVALS		PART NO.		PHONE JACKES		
TOLERANCES ARE		30~Ø以上	±0.30	ANGLE	PART NO. PJ-617	
		10~30	±0.20		SCALE: 1:1	
		5~10	±0.15	±2'	PROJ:	
		~5	±0.10		SHEET 1 of 1	

ECN NO.	REV.	DATE.	DESCRIPTION.	CHANGE.	CHECK.	APPRO.
	A		NEW			