



- Note:
- Material:
 - Housing: High temperature thermoplastic with g.f,UL94V-0
 - Contact: copper alloy,t=0.20mm
 - Shell: copper alloy,t=0.25mm
 - Specification:
 - Current rating:1.5PIN 1.8A Max/2,3,4PIN 1A Max.
 - Dielectric withstanding voltage: 100 V(ac) for 1 min.
 - Contact resistance: 30 mΩ Max.
 - Insulation resistance: 100 MΩ Min.
 - Total mating force: 3.57 Kgf Max.
 - Total unmating force: 1.0 Kgf Min.
 - Temperature range: -30°C~80°C

5	GND
4	ID
3	D+
2	D-
1	VBUS
	PIN NAME
	PIN ASSIGNMENT

公差一览表	
PRODUCT CHART DWG	
TOLERANCE UNLESS OTHERWISE	公差
X	±0.30
.X	±0.25
.XX	±0.20
.XXX	±0.10
X	±5°
.X	±2°
.XX	±1°
.XXX	±0.5°

产品图		深圳市精拓金电子有限公司	
UNIT	MM	制图	林属升
SCALE	1:1	审核	郭治富
DATE	2013/11/02	核准	黄国荣
PRODUCT PART NO.	920-A62A2021S10104	产品料号	
PRODUCT NAME	MICRO5P 5脚插回P7 25无引脚长1.1	产品名称	
PRODUCT NO.	有注册脚插端子SMT	角法	
VER	A0	版本	

目錄	变更内容	日期
MAPX	MODIFICATION	DATE