



MASK22~MASK210

Surface Mount Schottky Rectifiers

Features

- Low profile package
- Ideal for automated placement
- Ultrafast reverse recovery time
- Low power losses, high efficiency
- Low forward voltage drop
- High surge capability
- High temperature soldering:
260°C/10 seconds at terminals
- Component in accordance to
RoHS 2002/95/1 and WEEE 2002/96/EC



Mechanical Data

- **Case:** JEDEC MSMA molded plastic body over glass passivated chip
- **Terminals:** Solder plated, solderable per J-STD-002B and JESD22-B102D
- **Polarity:** Laser band denotes cathode end

Major Ratings and Characteristics

$I_{F(AV)}$	2.0 A
V_{RRM}	20 V to 100 V
I_{FSM}	50 A
V_F	0.50V, 0.55V, 0.70V, 0.85V
$T_j \text{ max.}$	125 °C

Maximum Ratings & Thermal Characteristics

($T_A = 25\text{ °C}$ unless otherwise noted)

Items	Symbol	MASK 22	MASK 23	MASK 24	MASK 25	MASK 26	MASK 28	MASK 210	UNIT
Maximum repetitive peak reverse voltage	V_{RRM}	20	30	40	50	60	80	100	V
Maximum RMS voltage	V_{RMS}	14	21	28	35	42	56	70	V
Maximum DC blocking voltage	V_{DC}	20	30	40	50	60	80	100	V
Maximum average forward rectified current	$I_{F(AV)}$	2.0							A
Peak forward surge current 8.3 ms single half sine-wave superimposed on rated load	I_{FSM}	50							A
Voltage rate of change (rated V_R)	dv/dt	10000							V/ μ s
Thermal resistance from junction to lead ⁽¹⁾	$R_{\theta JL}$	35							°C/W
Operating junction and storage temperature range	T_J, T_{STG}	-65 to +125							°C

Note 1: Mounted on P.C.B. with 0.2 x 0.2" (5.0 x 5.0mm) copper pad areas.

Electrical Characteristics

($T_A = 25\text{ °C}$ unless otherwise noted)

Items	Test conditions	Symbol	MASK 22	MASK23~MASK24	MASK25~MASK26	MASK28~MASK210	UNIT
Instantaneous forward voltage	$I_F=2.0A^{(2)}$	V_F	0.50	0.55	0.70	0.85	V
Reverse current	$V_R=V_{DC}$ $T_A=25\text{ °C}$ $T_A=100\text{ °C}$	I_R	0.5 10				mA

Note 2: Pulse test: 300 μ s pulse width, 1% duty cycle.



MASK22~MASK210

Surface Mount Schottky Rectifiers

Characteristic Curves ($T_A=25^\circ\text{C}$ unless otherwise noted)

Fig.1 Forward Current Derating Curve




Fig.2 Maximum Non-Repetitive Peak Forward Surge Current




Fig.3 Typical Instantaneous Forward Characteristics





Fig.4 Typical Reverse Leakage Characteristics






MASK22~MASK210

Surface Mount Schottky Rectifiers

Package Outline



Dimensions in millimeters and (inches)

Notice

- Product is intended for use in general electronics applications.
- Product should be worked less than the ratings; if exceeded, may cause permanent damage or introduce latent failure mechanisms.
- The absolute maximum ratings are rated values and must not be exceeded during operation. The following are the general derating methods you design a circuit with a device.
 - $I_{F(AV)}$: We recommend that the worst case current be no greater than 80%.
 - I_{FSM} : This rating specifies the non-repetitive peak current. This is only applied for an abnormal operation, which the general during the lifespan of the device.
 - T_J : Derate this rating when using a device in order to ensure high reliability. We recommend that the device be used at a T_J of below 125°C.

- TRR is registered trademark of Rising-sun Technology. Rising-sun Technology reserves the right to make changes to any product in this specification to improve reliability, functional characteristics, or design without notice.
- Rising-sun Technology does not assure any liability arising out of the applications or any product described in this specification.
- Rising-sun Technology advises customers to obtain the latest version of the device information before placing orders to verify that the required information is current.